

VIEWBOARD ACCESSORIES
VB-WIFI-006

Key Features

Product Description

The ViewSonic® VB-WIFI-006 Wireless Module delivers a faster and more reliable wireless internet connection for ViewBoard and Presentation Display*. It supports tri-frequency bands—2.4GHz, 5GHz, and 6GHz—along with Wi-Fi 6E (802.11ax standard). Ideal for high-bandwidth applications such as video streaming, videoconferencing, and voice calls, it ensures each connected device performs at an optimal level.*Compatible with selected models, please check with your local sales representatives.

Visit Us

www.viewsonic.com

WIFI-STANDARD

802.11a/b/g/n/ac/ax

OPERATING FREQUENCYWIFI: 2.4GHz & 5GHz & 6GHz
BT: 2.4GHz AP: 2.4GHz & 5GHz**MODULATION**

WIFI: 2.4G : 2412-2484MHz (18.98 dBm)
5G : 5180-5825MHz (13.93dBm)
6G : 5930-7110MHz (15 dBm)
*The 6E frequency band varies based on the national regulations for open frequency bands.

BT: Support 2.1/3.0/4.0/5.3 BLE

POWER

Requirements: 5V/1A

Consumption: < 5W

DIMENSIONPhysical: 224 (L) x 32 (H) x 25 (D) mm/
8.82 (L) x 1.26 (H) x 0.98 (D) inPackaging: 447 (L) x 300 (H) x 382 (D) mm/
17.6 (L) x 11.81 (H) x 15.04 (D)
in**WEIGHT**

Net: 93g/ 0.21lb

Gross: 113g/ 0.25lb

OPERATING CONDITION

Temperature: 32°F to 104°F (0°C to 40°C)

Humidity: 10% ~ 90% non-condensing

STORAGE / SHIPPING CONDITION

Temperature: -4°F to 140°F (-20°C to 60°C)

Humidity: 10% ~ 90% non-condensing

COMPLIANCE

NCC,RoHS, DoC

PACKAGE CONTENTS1. VB-WIFI-006
2. QSG