

Key Features


Higher Brightness. Longer Lamp Life.

- Auto Power Off
- 22,000:1 contrast ratio
- SuperColor™ Technology
- 5 colour modes
- Vertical Keystone



Product Description

The ViewSonic PA503S offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, PA503S projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColour™ technology offers a wider range of displayable colour ensuring true-to-life colour accuracy in both bright and dark environments without sacrificing image quality.



1. Keypad
2. LED indicator
3. Lamp cover
4. Security lock
5. Zoom/Focus

8. Audio in/out
9. HDMI
10. Dual VGA
11. VGA out
12. Mini USB

15. RS232

SPECIFICATION

Projection System:	0.55" SVGA
Native Resolution:	800x600
Brightness:	4000 (ANSI Lumens)
Contrast Ratio with SuperEco Mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source Type:	190W UHP Lamp
Light Source Life (hours) with Normal Mode:	5000
Light Source Life (hours) with SuperEco Mode:	15000
Lens:	F=2.56-2.68, f=22-24.1mm
Projection Offset:	120%+/-5%
Throw Ratio:	1.96-2.15
Optical Zoom:	1.1x
Digital Zoom:	0.8x-2.0x
Image Size:	30"-300"
Throw Distance:	1.19m-13.11m (100"@3.98m)
Keystone:	+/- 40° (V)
Audible Noise (Normal):	31dB
Audible Noise (Eco):	27dB
Input Lag:	16ms
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K-102KHz
Vertical Scan Rate:	23-120Hz

INPUT

Computer in (share with component):	2
Composite:	1
HDMI:	1 (HDMI 1.4/ HDCP 1.4)
Audio-in (3.5mm):	1

OUTPUT

Monitor out:	1
Audio-out (3.5mm):	1
Speaker:	2W

CONTROL

RS232 (DB 9-pin male):	1
USB Type Mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.2kg
Gross Weight:	3.24kg
Dimensions (WxDxH) with Adjustment Foot:	294x218x110mm
Packing Dimensions:	365x300x188mm
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Hindi, Arabic, Vietnamese, Greek, Total 23 languages
User Guide Language:	English, S-Chinese, T-Chinese, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Total 15 languages

STANDARD ACCESSORY

Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	Yes
Air Filter:	Yes (CN Only)
Warranty Card:	Yes (CN Only)

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-108
Air Filter:	RSPL
Wall/Ceiling Mount:	PJ-WMK-007
Carry Bag:	PJ-CASE-008