



i3-TECHNOLOGIES

i3ALLSYNC HDMI
TOUCH

Share your screen instantly.



Share your screen wirelessly from any device with our i3ALLSYNC HDMI Transmitter. Start sharing at the push of a button, without any installation. It is as easy as that!

All you need is the i3ALLSYNC wireless presenting app on your display, which is integrated on i3TOUCH P11, P12, E10r and i3HUDDLE. Plug the transmitter in to your laptop (or other suitable device). Press the button to share your screen. It's simple, fast and effective.



Plug & play

Connect the transmitter to your laptop (or other compatible device) and press the button to share.



No software needed

No need to install the i3ALLSYNC software on to your laptop.



User-friendly

Start sharing your screen at the push of a button.



Touch back

Control your computer from the display screen without remote.

Works with

macOS



The i3ALLSYNC Hardware Transmitter is OS independent.

Touchback only available on Windows and macOS (as transmitter). Make sure that your device supports touch functionality.

Specifications

Product information

Model name	i3ALLSYNC HDMI Transmitter
Product order code	VSV0005930
Size	65 mm x 65 mm x 20 mm (HDMI cable: 150 mm and USB cable 250 mm)
Transmission quality	Real time wireless mirroring of image (1080p supported at 60hz) and sound
Compatible device	HDMI supported PC, tablet, camcorder, game console, etc Smart pad such as Galaxy Tab, iPad and smartphone supported if gender charger is connected.
OS Independent	Compatible with Windows, Mac, Android and Linux
Wi-Fi	WiFi 802.11 b/g/n 2.4G 2T2R
Power Supply	USB input 5V 1A
Splitscreen support	Available only on i3HUDDLE
Operating range	In connection range of WiFi router.
Touch back	Control your computer from the display screen without remote.

Slide Switch

Presentation Mode	The latency between the transmitter and receiver means less latency and delay in presentation.
Video Mode	Smooth video display due to higher frames per second. User enjoys better video and audio experience.

Environmental conditions

Operating Temperature	-5°C - 45°C
Operating Humidity	20% - 80% RH Non Condensation
Storage temperature	-20°C - 60°C
Storage Humidity	5% - 93% RH Non Condensation

LED

Color	Led Action	Status
Red	Lights up constantly	Standby
Red	Flash three seconds and stop three seconds	Connection failed
Red	Blink	Error
Green	Blink	Pairing
Green	Lights up constantly	Paired and Ready
Blue	Lights up constantly	Mirroring
Yellow	Lights up constantly	Without HDMI source
White	Blink	Waiting for pairing

Package content

i3ALLSYNC HDMI Transmitter
How-to-use manual

Optional accessories

i3ALLSYNC Transmitter storage
