

Panel

Diagonal Size	13
Type	Edge LED
Resolution	1920*1080 (Full HD)
Pixel Pitch(mm)	0.153 x 0.153
Active Display Area(mm)	293.76 (H) x 165.24 (V)
Brightness(Typ.)	300 nit
Contrast Ratio	800:01:00
Viewing Angle(H/V)	178/178
Response Time(G-to-G)	8ms(Typ.)
Display Colors	16.7 M (real 6bit, dither 8bit)
Color Gamut	45%
Operation Hour	16/7
Haze	10%

Display

Dynamic C/R	MEGA
H-Scanning Frequency	30 ~ 81kHz
V-Scanning Frequency	48 ~ 75HZ
Maximum Pixel Frequency	594MHz

Sound

Speaker Type	Built in Speaker(5W)
--------------	----------------------

Connectivity

Input	
RGB	-
Video	HDMI 1.4 (1)
HDCP	HDCP 2.2
Usb	USB 2.0 x 1
Output	
Audio	Stereo Mini Jack
External Control	RS232C(in) thru stereo jack, RJ45

Power

Type	Adapter
Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60
Power Consumption	
Max[W/h]	

Typical[W/h]	13.0
Rating[W/h]	25.0
BTU(Max)	93.8
Sleep mode	0.5

Mechanical Specification

Dimension (mm)	Set	322.0x193.5x28.2
	Package	376x132x248
Weight (kg)	Set	0.9
	Package	1.7(TBD)
VESA Mount (mm)		100 X 100
Protection Glass		N/A
Stand Type		Bar Type Simple Stand (Inbox)
Media Player Option Type		N/A
Bezel Width (mm)		12.2mm

Operation

Operating Temperature	0 °C ~ 40 °C	Humidity
-----------------------	--------------	----------

Feature

Key Features		Small Signage Display Slim & Light
Special Features		H/W : Temperature Sensor, Pivot I Speaker(5W 1ch), IP5x Rating, Wi- Home UI, Button Lock, Hot key op
Internal Player	Processor	Cortex A72 1.7GHz Quad-Core CP
	On-Chip Cache Memory	L1 Instruction Cache : 48KBL1 Dat
	Clock Speed	1.7GHz
	Main Memory Interface	2.5GB LPDDR4 1.5GHz 64bitGraph
	Graphics	Output resolution : 3840x2160 (Sc
	Storage (FDM)	8GB (3.88GB Occupied by O/S, 4.1
	Multimedia	*Video Decoder : MPEG-1/2/4, H. JPEG, PNG, VP8, VP9 *Audio Deco
	IO Ports	USB 2.0
	Operating System	Tizen 4.0 (VDLinux)

Certification

Safety	60950-1
EMC	Class B

Accessory

Included		Quick Setup Guide, Warranty Card Type Simple Stand
Optional	Stand	Bar Type Simple Stand(inbox)
	Mount	-
	Specialty	N/A
	Tray	N/A

Media Player

Media Player	N/A
---------------------	-----

Hz

_____ 27. Mai

10 % ~ 80 %

Signage with Built-in MagicInfo S6, SSSP 6.0
Display, Clock Battery(168hrs Clock Keeping), Built in
-FISW : Auto Source Switching & Recovery,LFD
otion, Plug&Play (Initial Setting)
U
a Cache : 32KB L2 Cache : 2MB
ic resolution : 1920x1080
cale up from graphic processing result.)
12GB Available)
263, H.264/AVC, UHD H.264/AVC, VC-1, HEVC,
oder : AC3 (DD), MPEG

d,Power Cord, Remote Controller, Batteries, Bar
