



**Bedienfreundliche, einfache 1-Chip DLP™-
Laserprojektoren für scharfe Bilder in hellen
Räumen mit flexibler Integration in
Unterrichtsräume oder Büros**

PT-FRZ60

DLP™-Bildtechnologie, Quartet Colour Harmonizer, Rich Colour Enhancer und Optimierung durch digitale Modulation mit Dynamic Contrast 2 sorgen für herausragende Helligkeit, Farbqualität und Schärfe unabhängig vom Umgebungslicht. Flexibles zweifaches Zoomobjektiv mit V/H Lens-Shift sowie DIGITAL LINK und CEC-

Key Features

1-Chip DLP-Laserprojektor, 6.200 Lumen (Mitte), WUXGA

DLP™-Bildtechnologie, Quartet Colour Harmonizer, Rich Colour Enhancer und Optimierung durch digitale Modulation mit Dynamic Contrast 2

Bis zu 20.000 Stunden wartungsfreier Betrieb dank staubdichtem optischen Block und langlebigem Lasersystem

Flexibles zweifaches Zoomobjektiv (1,46 – 2,94:1) mit V/H Lens-Shift

Unterstützt unkomprimierte 4K/60p-Eingangssignale über HDCP 2.2-kompatible HDMI®-Eingänge oder DIGITAL LINK-Anschluss





PT-FRZ60

<https://eu.connect.panasonic.com/de/de/projektoren/pt-frz60-series/pt-frz60>

Projector type	1-Chip DLP™ projector
Display method	DLP™ chip x 1, DLP™ projection system
Display Device -> Panel size	17.0 mm (0.67 in) diagonal (16:10 aspect ratio)
Display Device -> Number of pixels	2,304,000 (1920 x 1200 pixels)
Light source	Laser diodes
Light output	6,000 lm
Light output (ANSI)	6,000 lm
Light output (Center) *4	6,200 lm (Center)
Time until light output declines to 50 %	20,000 hours [NORMAL]
-> NORMAL	
Resolution	1920 x 1200 pixels
Contrast Ratio (typ.)	20,000:1 (Full On/Full Off, Picture Mode: Dynamic, Dynamic Contrast 1, Operating Mode: Normal)
Screen size (diagonal)	1.02–7.62 m (40–300 in), 16:10 aspect ratio
Center-to-corner zone ratio	90%
Lens	2.0x manual zoom (throw ratio: 1.46–2.94:1), manual focus, F 2.0–3.4, f 21.5–43.0 mm
Lens shift -> Vertical(from center of screen)	+64 %, -44 % (manual)
Lens shift -> Horizontal(from center of screen)	+34 %, -27 % (manual)
Keystone correction range	Vertical: ±40 °, Horizontal: ±20 °
Installation	Ceiling/floor, front/rear, free 360-degree installation
Terminals -> HDMI™ IN	HDMI™ 19-pin x 2 (Compatible with HDCP 2.3, Deep Color, 4K/60p signal input*4), CEC supported
Terminals -> COMPUTER IN (D-SUB 15pin)	D-sub HD 15-pin (female) x 1 (RGB/YPBPR/YCBCR)
Terminals -> COMPUTER OUT (D-SUB 15pin)	D-sub HD 15-pin (female) x 1 (RGB/YPBPR/YCBCR)
Terminals -> VIDEO IN	Pin jack x 1 (composite video)
Terminals -> AUDIO IN(M3 Stereo Mini Jack)	Pin jack x 1 (L, R)
Terminals -> AUDIO IN(Pin Jack L/R)	M3 x 1/M3 x 1
Terminals -> AUDIO OUT(M3 Stereo Mini Jack)	M3 x 1 (Variable)
Terminals -> SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals -> DIGITAL LINK IN / LAN	RJ-45 x 1 for network and DIGITAL LINK connections (HDBaseT™ compliant), PJLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.3 compatible, Deep Color compatible, 4K/60p signal input*4
Terminals -> LAN	RJ-45 x 1 for network connection, PJLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
Terminals -> USB TYPE A	USB connector (Type A) x 1 (Output 5 V/2 A)
Power supply	AC 100–240 V, 50/60 Hz
Maximum power consumption	540 W (5.8–2.3 A)
On-mode power consumption(Operating mode) -> Normal	[NORMAL] 490 W
On-mode power consumption(Operating mode) -> Eco	[ECO] 385 W
On-mode power consumption(Operating mode) -> Quiet	[QUIET] 385 W
Standby power consumption -> Normal	10 W (Standby Mode) [NORMAL]
Standby power consumption -> ECO	0.5 W (Standby Mode) [ECO]
Cabinet materials	Molded plastic
Filter	No
Operation noise -> Normal	35 dB [NORMAL]
Operation noise -> Quiet	30 dB [QUIET]
Dimensions (W x H x D)	498 x 168*5 x 492 mm (19 5/8" x 6 5/8" *5 x 19 3/8")
Dimensions -> Width (including protruding parts)	498 mm (19 5/8")
Dimensions -> Height (including protruding parts)	168 mm (6 5/8")
Dimensions -> Depth (including lens)	492 mm (19 3/8")
Weight	Approx. 16.1 kg (35.5 lbs)
Operating environment -> Operating temperature	0–45 °C (32–113 °F)

Operating Environment -> Operating humidity (No condensation)	10-80 % (no condensation)
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software
Footnote Description	<ol style="list-style-type: none"> 1. When [PICTURE MODE] is set to [DYNAMIC], [DAYLIGHT VIEW] is set to [OFF], [DYNAMIC CONTRAST] is set to [OFF], [LIGHT OUTPUT] is set to [100%], and [AUTO POWER SAVE] is set to [OFF]. 2. Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped. 3. Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped. 4. Average light-output value of all shipped products measured at the center of the screen. 5. Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, Normal Mode, Dynamic Contrast 2, temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m3 of airborne particulate matter. Estimated time until light output declines to 50 % varies depending on environment. 6. 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI@. 7. With legs at shortest position. 8. Average value. May differ depending on the actual unit.