

H117ST

Go big! Short throw HD Ready home entertainment projector









- Lights on viewing 3800 ANSI lumens
- Short throw lens 100" image from just over a metre away
- Easy connectivity HDMI, VGA, USB power
- Clear, powerful audio 10W speaker



Feel the action and experience every moment on the big screen for immersive gaming and live sports with a dedicated gaming and sport mode.

Convenient and easy to set up, this compact high brightness projector is ideal for well-lit environments so sports fans can enjoy live action with family or friends with the lights on. Boasting Amazing colour technology, it delivers accurate true-to-life colour reproduction for movie lovers. It also supports low input latency – perfect for games that rely on rapid reactions.

Specifications

EAN: 5055387664999, Colour: White Display/image Display technology DIPTM Resolution WXGA (1280x800) 3,800 lumens Brightness Contrast ratio 30,000:1 Native aspect ratio 16:10 Aspect ratio - compatible 4:3.16:9 Keystone correction - vertical +/-40° 15.38 ~ 91.15Khz Horizontal scan rate 50 ~ 85(120 for 3D)Hz Vertical scan rate Uniformity 75% Screen size 0.91m ~ 7.7m (35.64" ~ 302.98") diagonal Lamp info Light source type Lamp Lamp watts 203 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+) Lamp life hours (up to) Optical 0.52:1 Throw ratio Projection distance (m) 0.4m - 3.4m Focal length (mm) 7.51 Native offset 112% Connectivity Connections Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 General Noise level (min) 26dB 28dB Noise level (max) PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 3D compatibility 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D 3D Security bar, Kensington Lock, Password protected interface Security

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, OSD / display languages Turkish, Vietnamese

Chinese (simplified), Spanish, Swedish, Chinese (traditional),

5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Operating conditions Remote control Card style

Speaker count Watts per speaker 10W In the box AC power cord

Remote control Battery Basic user manual 33.00ms

Input lag Optional wireless models WHD200 Power

100 ~ 240V, 50 ~ 60Hz Power supply Power consumption (standby) 0.5W

Power consumption (min) 187W Power consumption (max) 225W Weight and dimensions

316 x 244 x 108 Dimensions (W x D x H) mm 3.83 kg Gross weight Net weight 3.26 kg





