

The EB-L635SU short-throw, 6,000 lumens laser projector is ideal for users who need to produce large images in tight spaces.

As the market leader in 3LCD technology, Epson continues to improve its high brightness laser projectors with more compact short-throw display solutions. The EB-L635SU delivers effective, practical and creative applications to meet the display needs in education, corporates, museums and visitor attractions. All achieved without sacrificing image quality or lens shift flexibility.

Experience brighter and bolder displays

The EB-L635SU produces more engaging and impactful displays even in brightly lit environments. It offers impressive 6,000-lumen brightness and WUXGA Full HD resolution at an affordable price. This means you can upgrade to laser performance and reliability, with reduced power consumption. It also features: 0.8:1 throw ratio, 4K input support, detail enhancement technology, edge blending and wide lens shift to fit challenging installation environments. The EB-L635SU is capable of large format and blended displays, without any reduction in clarity or vivid detail.

Install with ease

The EB-L635SU includes many professional features which make installation simple, even when producing more advanced displays. This stylish and compact projector offers 360-degree installation, without compromising the display quality, and supports 16:6 ultra-widescreen, which means you can maximise the visible display space available. Also, with split-screen capability you can display two or four images from different sources simultaneously; and geometric correction and edge blending help create one large, seamless image using multiple displays. Also available in white.

Scale to suit your environment

Unlike a flat-panel display, there's no glare, fingerprints or wasted wall space, and the image can be scaled to fit the required display size. Whether it's for education, corporate, retail or visitor attractions, the viewing experience can be unrestricted and more engaging for the audience.

Connect and control

The EB-L635SU offers many ways to connect, show multiple sources simulateneously and present wirelessly. The future-proofed connectivity options include: HDMI (input and output) and HDBaseT with 4K signal support, 5GHz wireless with enterprise security, built-in media player, built-in Miracast and support for Epson's ELPWP10 wireless presentation system. It is also easy to set up and navigate thanks to the intuitive on-screen user guide.

KEY FEATURES

- 6,000-lumen brightness Crisp images and bright colours, even in well-lit rooms
- WUXGA resolution
 Sharp Full HD images for excellent clarity
- Futureproofed connectivity options 4K input support, HDMI, HDBaseT, integrated Wi-Fi and screen mirroring
- Easy, flexible installation Lightweight and compact design with wide lens shift
- Short-throw projection Large images in tight spaces (0.8:1 throw ratio)



PRODUCT SPECIFICATIONS

TECHNOLOGY	
Loundeball	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.67 inch with C2 Fine
IMAGE	
Color Light Output	6,000 Lumen- 4,200 Lumen(economy) In accordance with IDMS15.4
White Light Output	6,000 Lumen - 4,200 Lumen(economy) In accordance with ISO 21118:2020
Resolution	WUXGA
Resolution Enhancement	Full HD
Aspect Ratio	16:10
On-Screen Pixel Count	2,304,000
Contrast Ratio	Over 5,000,000: 1
Light source	Laser
Laser Light source	20,000 hoursDurability High, 30,000 hoursDurability Eco
Keystone Correction	Manual vertical: ±30 °, Manual horizontal ±30 °
Colour Video Processing	10 Bits
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.80 - 1.07:1
Zoom	Digital, Factor:1 - 1.35
Lens	Optical
Lens Shift	Manual - Vertical ±50 %, horizontal ±20 %
Screen Size	50 inches - 200 inches
	0.9 m - 3.5 m
Projection Distance Wide	1.7
Projection Lens F Number Projection Lens Focal Length	
	11.76 mm
	Monuel
Projection Lens Focus	Manual
Projection Lens Focus CONNECTIVITY	
Projection Lens Focus CONNECTIVITY	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN
Projection Lens Focus	
Projection Lens Focus CONNECTIVITY	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN
Projection Lens Focus CONNECTIVITY Interfaces	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT,
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES	USB 2.0-A, USB 2.0, RS-232C, Ethemet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES Security	USB 2.0-A, USB 2.0, RS-232C, Ethemet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES Security 2D Colour Modes	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES Security 2D Colour Modes	USB 2.0-A, USB 2.0, RS-232C, Ethemet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Dynamic, Cinema, Presentation, sRGB, DICOM SIM
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES Security 2D Colour Modes	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Dynamic, Cinema, Presentation, sRGB, DICOM SIM 21:9 aspect ratio support, A/V mute, Arc Correction, Auto Power On, Auto source search, Built
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES Security 2D Colour Modes	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Dynamic, Cinema, Presentation, sRGB, DICOM SIM 21:9 aspect ratio support, A/V mute, Arc Correction, Auto Power On, Auto source search, Built in speaker, CEC compatible, Customizable user logo, Daisy chain Multi-Projection, Digital
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES Security 2D Colour Modes	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11 <i>a/b/g/n/ac</i> , Wireless LAN <i>a/n</i> (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Dynamic, Cinema, Presentation, sRGB, DICOM SIM 21:9 aspect ratio support, A/V mute, Arc Correction, Auto Power On, Auto source search, Built in speaker, CEC compatible, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen,
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES Security 2D Colour Modes	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11 <i>a</i> / <i>b</i> /g/n/ac, Wireless LAN <i>a</i> /n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Dynamic, Cinema, Presentation, sRGB, DICOM SIM 21:9 aspect ratio support, A/V mute, Arc Correction, Auto Power On, Auto source search, Built in speaker, CEC compatible, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, Horizontal and vertical keystone correction, JPEG Viewer, Long light source life, PC Free,
Projection Lens Focus	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Dynamic, Cinema, Presentation, sRGB, DICOM SIM 21:9 aspect ratio support, A/V mute, Arc Correction, Auto Power On, Auto source search, Built in speaker, CEC compatible, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, Horizontal and vertical keystone correction, JPEG Viewer, Long light source life, PC Free, Power on button, Quick Corner, Schedule Function, Screen Mirroring, Split-Screen-Function,
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES Security 2D Colour Modes	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Dynamic, Cinema, Presentation, sRGB, DICOM SIM 21:9 aspect ratio support, A/V mute, Arc Correction, Auto Power On, Auto source search, Built in speaker, CEC compatible, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, Horizontal and vertical keystone correction, JPEG Viewer, Long light source life, PC Free, Power on button, Quick Corner, Schedule Function, Screen Mirroring, Split-Screen-Function, Super resolution, Ultra-wide display (16:6), Volume control, Web Control, Web Remote,
Projection Lens Focus CONNECTIVITY Interfaces Epson iProjection App Network Protocol ADVANCED FEATURES Security 2D Colour Modes Other features	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN a/n (5GHz), VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Jack plug out, Jack plug in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback Ad-Hoc / Infrastructure HTTPS, IPv6, SNMP, ESC/VP.net, PJLink Kensington lock, Control panel lock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection Dynamic, Cinema, Presentation, sRGB, DICOM SIM 21:9 aspect ratio support, A/V mute, Arc Correction, Auto Power On, Auto source search, Built in speaker, CEC compatible, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, Horizontal and vertical keystone correction, JPEG Viewer, Long light source life, PC Free, Power on button, Quick Corner, Schedule Function, Screen Mirroring, Split-Screen-Function, Super resolution, Ultra-wide display (16:6), Volume control, Web Control, Web Remote, Wireless LAN capable, iProjection App

EB-L635SU

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries

EPSON[®]

- Cable cover
- User guide
- Warranty Documents
- Main unit
- HDMI Cable

PRODUCT SPECIFICATIONS

EB-L635SU

GENERAL	
Power consumption	287 Watt (Normal On-Mode), 164 Watt (Eco On-Mode), 345 Watt (Normal Peak-mode), 258
	Watt (Eco Peak-Mode), 0.3 Watt (Energy saving standby)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	440 x 334 x 136 mm (Width x Depth x Height)
Product weight	8.4 kg
Noise Level	Normal:38 dB (A) - Economy:27 dB (A)
Supported Temperature	Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%
	If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the projector to drop from the ceiling.
	If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.
Options	Connection and control box, Document camera, External Speaker, HDBaseT Transmitter, MB22 ceiling mount, Wireless LAN unit
Loudspeaker	10 Watt
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection
	Mapping, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop
Colour	Black
OTHER	
Warranty	36 months Carry in
	Optional warranty extension available



OPTIONAL ACCESSORIES

- Wireless LAN Adapter ELPAP11 (2.4GHz & 5GHz) V12H005A01
- Air Filter ELPAF56 L600/EB-14XX Series V13H134A56
- Ceiling Mount (White) ELPMB22 V12H003B22
- Ceiling Mount (Low profile) ELPMB30 V12H526040
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- Safety Wire ELPWR01 V12H003W01
- Ceiling Mount ELPMB68 V12H006AE0
- Portrait Adaptor ELPMB69 For ELPMB68 V12H006AF0

LOGISTICS INFORMATION

V11HA29140

8715946695372

Country of Origin Philippines

Wireless Presentation Systems

- Epson ELPWP10 Wireless Presentation System V12HA41040
- Epson ELPWP20 Wireless Presentation System V12HA42040

Visualizers

• ELPDC30

sĸu

EAN code

V12HB09080

* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00

Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711) 465-9621

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

EB-L635SU

EPSON[®]