nexvoo nexbar

USB VIDEO BAR VIDEO CONFERENCING FOR SMALL AND HUDDLE ROOMS

BENEFITS

- 4K USB Video Bar
- AI speaker tracking and auto-framing
- Compatible with your favorite video conferencing platforms (Zoom, Skype for business, Hangouts, Chime…)
- Suitable for Room size up to 150SQFT

Nexvoo NexBar N110

The Nexvoo NexBar N110 has a built-in wide-angle 120-degree FOV lens, it also has a next generation 6 microphone-array, which provides all meeting participants with studio quality video and audio. With the automatic people framing and speaker tracking AI technology, it lets everyone to be seen clearly for huddle rooms and small rooms. This sleek USB video bar is easy to set up and easy to connect with PC or MAC.

- Ideal for rooms of up to 15 participants
- Automatic people framing and speaker tracking
- High quality next generation audio far-field pickup and amazing noise blocking technology
- Works with nearly all video conferencing platforms

Specifications

Camera
- 120° FOV
- Sony High-Sensitivity Camera Sensor
- f/2.2 Aperture
- UHD 2160p (4K) capture resolution
- Automatic people framing and speaker tracking
- 5x digital zoom / EPTZ
- 2 Camera presets
- Camera indicator

Audio
- Support full-duplex conversations, acoustic echo cancellation and background noise suppression
- Mute / Unmute controls
- Stereo microphone
- Built-in 6 beamforming microphone array
  - 16ft / 5 meters voice pickup distance
  - 120 Hz–16 kHz frequency response
- Stereo speaker
  - 100Hz-20KHz Frequency response

Port
- 1xUSB3.0 Type-C port
- Power connector
- Bluetooth 4.2

Security
- 802.1x support
- Certification management

Application Compatibility
- Compatible with any application that supports standard USB audio and video drivers, including but not limited to:
  - Microsoft Skype for Business
  - Microsoft Skype
  - Microsoft Teams
  - Zoom
  - GoToMeeting
  - BlueJeans Network
  - Google Hangouts
  - Amazon Chime
  - Cisco Webex
  - VidyoDesktop
  - And more

Application Requirements
- Supported operating systems
  - Windows 7, 8.1, 10
  - MacOS 10.12, 10.13, 10.14, 10.15
- Supports standard audio and video device drivers
  - UAC1.0 Audio
  - UVC1.1/1.5 Video
  - HID1.11

Environment Requirements
- Working temperature: 0-40°C
- Relative humidity: 15-80%, noncondensing
- Storage temperature: -25-70°C
- Storage humidity: 5-95%, noncondensing

Size
- (H x W x D) 503 x 92 x 64mm
- 3.75lbs / 1.7 kg

Power Requirements
- 5VDC/2A@100~240VAC, 50/60Hz

Package Includes
- Nexvoo NetBar 110 main unit
- Remote control (including 2 AAA batteries)
- Power adapter
- 5m USB3.0 cable (Type-C to Type-A)
- Installation instructions

Website
www.nexvoo.eu

Contact Email
info@nexvoo.eu

Address
PvMG Rood 22
6666 LT Heteren