

ATEO2 with surface ceiling mount

Highlights:

- · Vertical and horizontal mounting
- · 2" full range aluminum driver
- Stunning designed and elegant looking ABS enclosure
- Patented ClickMount™ mounting system

A combination of your trusted ATEO2 speaker and a specially designed surface ceiling mount with ClickMount™ technology*.

The ATEO is a series of extraordinary loudspeakers especially designed for fixed install in indoor applications, ranging from modern residential applications to the most demanding designer applications in environments such as retail stores, pubs, restaurants or even clubs.

The ATEO2 is the ultra-compact model of this series which smoothly integrates into any interior like no other loudspeaker. The sound originates from a 2" aluminum cone driver which provides a full-range, warm and detailed sound, with an improved response in the low frequencies due to the ported design. This way, smooth sound reproduction with clear and crisp sound is guaranteed.

The internal self-resetting network provides optimal overload protection. It features a stunningly designed and elegant looking ABS housing which is fitted with high-quality components.

*The ATEO2S is not compatible with the CleverMount™ mounting system.

Applications:

- Retail
- · Residential
- · Clubs, bars, restaurants









System specifications:

| Speaker type | | Full range |
|----------------------------|-------------------|-------------------------|
| Max. Power | | 20 W |
| RMS Power | | 10 W |
| Impedance | | 8 Ω (ATEO2) |
| | | 16 Ω (ATEO2D) |
| Incline angle | Left | 25° |
| | Right | 25° |
| | Bottom | 25° |
| | Тор | 15° |
| Sensitivity (1W/1m) | | 83 dB |
| Sound Pressure (Max. W/1m) | | 93 dB |
| Frequency | Response (± 3 dB) | 120 Hz - 20 kHz |
| | Range (-10 dB) | 100 Hz - 20 kHz |
| Dispersion | Horizontal | 145° |
| | Vertical | 170° |
| Drivers | | 2" Aluminium full range |

Product Features:

| Dimensions | 80 x 136 x 115 mm (W x H x D) | |
|-----------------------|-------------------------------|--|
| Weight | 0.390 kg | |
| Operating temperature | -20 °C ~ 60 °C | |
| Construction | ABS | |
| Front finish | Steel grill | |
| Colours | Black | |
| | White | |

Variants:

- ATEO2S/B Black version 8Ω
- ATEO2S/W White version 8Ω
- ATEO2SD/B Black version 16Ω
- ATEO2SD/W White version 16Ω

