



KRAMER

K-Cam4K

4K PTZ Camera & 4K UHD camera,
71-degree Wide-angle Lens & 12 Times
Optical Zoom



Ultra-HD camera for premium-clarity video in large spaces. Put every meeting in sharp focus with crystal-clear, ultra-high-definition video capture and advanced, yet easy, control. 4K resolution, high-power optical and digital zooms, smooth PTZ operation and multiple outputs, the K-Cam4K takes video conferencing to a new level

FEATURES

Superior video at any distance -

Wide-angle image capture with advanced PTZ control enables dynamic coverage of medium and large spaces, such as boardrooms, classrooms, and auditoriums

Best-in-class image clarity and highly accurate close-ups, with 4K60 resolution and 12x optical zoom plus 16x digital zoom

Enhanced video quality, even in low-light conditions, with industry-leading CMOS image sensing with 2D and 3D digital noise reduction (DNR)

Easy configuration and control -

All operation, including pan, tilt and zoom, are easily controlled from any Kramer control interface and/or the compact remote control

Multiple ports including RS-232, RJ-45, HDMI 1.4, and USB 3.0 deliver 4K video at up to 60 fps

Works seamlessly with virtually all meeting applications

Fast and simple setting of camera angle, with a choice of 255 pre-set camera positions



TECHNICAL SPECIFICATIONS

Datenports

USB 3.0: On a USB type B connector Up to 4K@30fps compressed video and 1080P original video can be output

RS-232 IN: On an 8-pin Min DIN, Max Distance: 30m, Protocol: VISCA / Pelco-D / Pelco-P

RS-232 OUT: On an 8-pin Min DIN, Max Distance: 30m, Protocol: VISCA / Pelco-D / Pelco-P

RJ-45: 10/100/1000M Adaptive Ethernet Port

RS-485: On a 2-pin phoenix connector, Max Distance: 1200m, Protocol: VISCA / Pelco-D / Pelco-P

Audio Line In: On a 3.5mm mini jack

HDMI: On an HDMI connector

3G-SDI: On a BNC connector, 800mVp-p, 75Ω. Along to SMPTE 424M standard

Camera

Video System: HDMI: 1080P60, 1080P50, 1080I60, 1080I50, 1080P30, 1080P25, 720P60, 720P50, 1080P29.97, 1080I59.94, 1080P59.94, 720P59.94, 4KP29.97, 4KP25, 4KP30

Video System: 3G-SDI: 1080P60, 1080P50, 1080I60, 1080P59.94, 1080I59.94, 1080I50, 1080P30, 1080P29.97, 1080P29.97, 1080P25, 720P60, 720P59.94, 720P50

Sensor: 1/2.5 inch, CMOS, Max Effective Pixel: 8.51M

Scanning Mode: Progressive

Lens: 12x, f = 4.4mm ~ 52.8mm, F1.8 ~ F2.6

Digital Zoom: 16x

Minimal Illumination: 0.5 Lux @ (F1.8, AGC ON)

Shutter: 1/30s ~ 1/10000s

White Balance: Auto, Indoor, Outdoor, One Push, Manual

Backlight Compensation: Support

Digital Noise Reduction: 3D Digital Noise Reduction

Video S/N: ≥55dB

Horizontal Angle of View: 71° ~ 8.2°

Vertical Angle of View: 42.7° ~ 4.5°

Horizontal Rotation Range: ±170°

Vertical Rotation Range: ±30°

Pan Speed Range: 1.6°/s ~ 76°/s

Tilt Speed Range: 0.5°/s ~ 15°/s

H & V Flip: Support

Image Freeze: Support

Number of Presets: 255

Preset Accuracy: 0.1°

USB Features	<p>Video Format: YUY2: max to 1080P@30fps</p> <p>Video Format: H.264 AVC/SVC: max to 2160P@30fps</p> <p>Video Format: MJPEG: max to 4K@30fps</p> <p>Operating System: Windows 7, Windows 8, Windows 10, Mac OS X, Linux, Android</p> <p>Color System / Compression: YUY2 / MJPEG / H.264 / H.265</p> <p>USB Audio: Support</p> <p>USB Video Communication Protocol: UVC 1.1~1.5</p> <p>UVC PTZ: Support</p>
Network	<p>Video Compression: H.264/H.265/MJPEG</p> <p>Video Stream: First Stream, Second Stream</p> <p>First Stream Resolution: 3840x2160, 1920x1080, 1280x720, 1024x576, 720x480, 720x408, 640x480, 640x360</p> <p>Second Stream Resolution: 720x480, 720x408, 640x480, 640x360, 480x320, 320x240</p> <p>Video Bit Rate: H264: ~60Mbps MJPEG: ~200Mbps</p> <p>Bit Rate Type: Variable Rate, Fixed Rate</p> <p>Frame Rate: 50hz: 4K max to 30fps, 1080P max to 50fps 60hz: 4K max to 30fps, 1080P max to 60fps</p> <p>Audio Compression: G711A, AAC</p> <p>Audio Bit Rate: 96K, 128K</p> <p>Protocols: TCP/IP, HTTP, RTSP, RTMP/RTMPS, ONVIF, DHCP, SRT, Multicast</p>
Controls	<p>IR Remote Control Transmitter: OSD</p> <p>Web Interface: Embedded webpages</p>
Energiebedarf	<p>Source: 12V DC, 2A max</p> <p>Consumption: 12W max</p>
Umweltbedingungen	<p>Operating Temperature: -10° to +40°C (14° to 104°F)</p> <p>Storage Temperature: -40° to +60°C (-40° to 140°F)</p> <p>Humidity: 10% to 90%, RHL non-condensing</p> <p>Altitude: Below 5000 meters</p>
Einhaltung von Vorschriften (Einhaltung von Standards)	<p>Safety: CE, FCC</p> <p>Environmental: RoHs, Reach</p>
Gehäuse	<p>Type: Aluminum and plastic</p>
General	<p>Net Dimensions (W, D, H): 14.5cm x 9.8cm x 15cm (5.7" x 3.9" x 5.9")</p> <p>Shipping Dimensions (W, D, H): 23cm x 23cm x 25cm (9" x 9" x 9.8")</p> <p>Net Weight: 0.94kg (2.1lbs) approx</p> <p>Shipping Weight: 2.6kg (5.7lbs) approx</p>
Zubehör	<p>Included: Power adapter and cord, IR remote control transmitter, 1 USB 3.0 cable, wall bracket kit, adn lens cover</p>

