

Proyector de 1 chip DLP™ de óptica fija con resolución True 4K

PT-FRQ60

El proyector PT-FRQ60 1-Chip DLP™ 4K de 6.000 lm ofrece imágenes nítidas y precisas para una experiencia visual intensa



KEY FEATURES

- Proyector láser de 1 chip DLP™, brillo de 6.000lm
- Resolución de salida 4K (3840 x 2160), ideal para exposiciones de museos, educación y oficinas corporativas
- Óptica zoom 2.0x y desplazamiento de la óptica V/H gran angular (V: +71 %, -48 %, H: +34 %, -27 %)
- Admite alta velocidad de fotogramas de 240Hz/1080p con latencia mínima de entrada a salida

Especificaciones del producto

SPECIFICATIONS

Projector type	1-Chip DLP™ projector
DLP™ Chip Panel Size	16.5 mm (0.65 in) diagonal (16:9 aspect ratio)
DLP™ Chip Display Method	DLP™ chip x 1, DLP™ projection system
DLP™ chip Number of Pixels*1	1920 x 1080 pixels (If a signal other than 120 Hz/240 Hz is input, it cannot be displayed at this resolution.)
Light Source	Laser diodes
Light output *2 *3	6,000 lm / 6,200 lm (Center)*4
Time until light output declines to 50 %*5	20,000 hours (NORMAL/QUIET)/24,000 hours (ECO)
Resolución	4K (3840 x 2160 pixels) (With Quad Pixel Drive)
Contrast Ratio*2	20,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1]. HDMI signal input)
Screen Size (Diagonal)	1.02–7.62 m (40–300 in), 16:9 aspect ratio
Center-to-corner zone ratio*2	90 %
Lens	2.0x manual zoom (throw ratio: 1.46–2.93:1), manual focus, F 2.0–3.4, f 21.5–43.0 mm
Lens shift Vertical(From the origin point of the lens mounter)	+71 %, -48 % (manual)
Lens shift Horizontal(From the origin point of the lens mounter)	+34 %, -27 % (manual)
Keystone Correction Range	Vertical: ±40 °, Horizontal: ±20 °
Instalación	Ceiling/floor, front/rear, free 360-degree installation
Terminals HDMI IN 1/2	HDMI 19-pin x 2 (Compatible with HDCP 2.3, Deep Color, 4K/60p signal input6), CEC supported
Terminals Computer In	D-sub HD 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
Terminals Monitor Out	D-sub HD 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
Terminals Audio In/Out	M3 stereo mini-jack x 2
Terminals Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBase™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p signal input*7)
Terminals LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net)
Terminals USB	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module, for USB memory, and for power supply (DC 5 V, maximum 2 A)
Power Supply	AC 100–240 V, 50/60 Hz; AC 110 V, 60 Hz (Taiwan)
Power Consumption	505 W
Cabinet Materials	Molded plastic
Operation Noise*2	36 dB (NORMAL/ECO) / 31 dB (QUIET)
Dimensions (W x H x D)*8	498 x 168 x 492 mm (19 5/8" x 6 5/8" x 19 3/8")
Weight*9	Approx. 16.4 kg (36.2 lbs)
Operating Environment	Operating temperature: 0–45 °C (32–113 °F)*10, operating humidity: 10–80 % (no condensation)
Applicable Software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro*11
Note	*1 If a signal other than 120 Hz/240 Hz is input, it cannot be displayed at this resolution. *2 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *3 When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL]. *4 Average light-output value of all shipped products measured at center of screen in NORMAL Mode. *5 Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m3 of particulate matter). Estimated time until light output declines to 50 % varies depending on environment. *6 4K/60p

signals are converted to the projector's resolution upon projection. *7 4K/60p signal input is converted to projector's resolution, supports YPBPR[?]4:2:0 format only. *8 With legs fully retracted. *9 Average value. May differ depending on the actual unit. *10 When using the projector at an altitude lower than 2,700 m (8,858 ft) above sea level, and the operating environment temperature becomes 35 °C (95 °F) or higher, the light output may be reduced to protect the projector. When optional AJ-WM50 Series Wireless Module is attached, operating temperature range becomes 0-40 °C (32-104 °F). *11 Some features only available after August 2022.

URL: <https://business.panasonic.es/sistemas-visuales/pt-frq60>

CONTACT

Web: <https://business.panasonic.es/sistemas-visuales/contact-us>