

360-Grad-Kamera- Freisprecheinrichtung

TY-CSP1

Realistischeres Gefühl mit der 360-Grad-Kamera-Freisprecheinrichtung



KEY FEATURES

- Optimale Video- und Audioübertragung
- Einfache Bedienung
- Installation und Portabilität

Produktspezifikationen

SPECIFICATIONS

Imaging element	1/2.7"5MP CMOS
Field of view (H x V)	360 x 60
F number of the lens	2.5
Lens TTL	14.7 mm
Distortion	-14.90%
Mikrofon	MEMS Microphone array
Number of microphones	7
Beam forming	Supported
Microphone Sensitivity	-35dBFS
S/N Ratio	68.75 dBA
Speaker Output	1.5 W (When supplying power from USB Type-C) or 3 W (When AC adaptor is connected)
Connection terminals	USB Type-C (Receptacle/USB2.0) DC plug 12 V/2 A
Power Supply	USB Type-C (5 V/3 A) or AC adaptor DC 12 V/2 A
Power consumption (when outputting video)	11 W
Dimensions	Φ64 mm × 285 mm/Φ2.52" × 11.23"(Operation base Φ100 mm (Φ3.94"))
Mass	950 g/2.1 lbs.
Security slot	Noble Wedge lock(mounting Φ11 mm or less)
Operating Conditions	Temperature: 0 °C to 40 °C (32 °F to 104 °F) Humidity: 20 % to 80 % (no condensation)
Usable altitude range	0 m to 2800 m (0 to 9186 ft)

URL: <https://business.panasonic.de/visuelle-systeme/ty-csp1>

CONTACT

Web: <https://business.panasonic.de/visuelle-systeme/contact-us>