


DS SERIES

# DS491LT6


49" High Brightness 5500 Nits Digital Signage Display



SUNLIGHT  
VIEWABLE IMAGE




SUSTAINED  
HIGH BRIGHTNESS



BUILT-IN  
MEDIA PLAYER



24 / 7  
OPERATION



TRUECOLOR™  
CALIBRATED

## FOR MORE INFORMATION

For more information about DynaScan, visit our site at [www.dynascandisplay.com](http://www.dynascandisplay.com). Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.



# DynaScan

# SPECIFICATION

<b>MODEL</b>	DS49ILT6	
<b>PANEL</b>	LCD Panel Size	48.5 inches LCD
	Native Resolution	1920 x 1080
	Backlight	LED
	Default Color Temperature	D65 (6500 K)
	Brightness	5500 nits
	Color Depth	10 bits
	Contrast Ratio	3000 : 1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
<b>POWER</b>	Blackening Defect Free	Up to 110°C (230°F)
	Polarized Sunglasses Support	Yes
	Panel Surface	AR, 2H
	Power Supply	Internal
<b>MECHANICAL SPECS</b>	Rated Voltage	100-240V ~ 50/60Hz
	Power On Mode (Typ./ Max.)	185 W / 340 W
	Power Saving Mode	< 1 W
	AC out	< 100 W
<b>USER INTERFACE</b>	Bezel Width (T/B/L/R)	8.7 / 8.7 / 8.5 / 8.5 mm
	Cabinet Color	Black
	Monitor Dimension (LxHxD)	1096.7 x 627.2 x 82.3 mm
	Monitor Weight	20.9 kg
	Orientation	Portrait / Landscape
	VESA Mounting (LxH)	400 x 400 mm
	Carrying Handles	Yes
	Language	English
	Built-in Video Wall Support	Up to 15x15
	Support SNMP (Up to V3.0)	Yes
<b>INPUT</b>	Dimming Control	Yes
	Image Retention Protection	Yes
	Auto Orientation Sensor	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
	Internal Temperature Sensor	Yes
	OSD Menu Rotation	Yes
	HDMI	x1 (1080p)
	DVI-D	x1
	DisplayPort	x1
<b>OUTPUT</b>	USB	x1 (For Internal Player)
	SD Slot	x1 (For Internal Player)
<b>EXTERNAL CONTROL</b>	RS-232	In x1, Out x1
	RJ-45	x1 (LAN)
<b>INTERNAL PLAYER</b>	Processor	ARM Quad-Core Cortex-A9
	Clock speed	1.6 GHz
	Main memory interface	DDR3L-1066, 1GB
	Graphics	Mali400MP4, support OpenGL ES1.1/2.0, Open VG1.1
	Storage	Internal: Nand flash 8GB(multi sources) External: Support SD , Up to 32GB
	Multimedia	Multi-format 1080P video decoders (H.264,VC-1, MPEG-1/2/4, H.263, H.264 MVC, AVS, VP8/6, RV)
	Wi-Fi Specification	802.11 b/g/n   2412.0MHz - 2462.0MHz
<b>ENVIRONMENT</b>	Operating System	Android 4.4.2
	Operating Temperature	0° C ~ 45° C
	Storage Temperature	-20° C ~ 60° C
<b>CERTIFICATION</b>	Humidity	10% ~ 80% RH Non-condensing
	CE / FCC / RoHS	

# DIMENSIONS

Unit: mm [inch]



# INTERFACE

