



AVer Future Classroom

Create Online & Offline Environments

- Visualizers
- Wireless Visualizers
- 3 A+ Suite & AVerTouch Software
- 4 Charge, Disinfect & Sync Carts/Stations
- 5 Distance Learning & Auto Tracking PTZ Cameras









Digitize All Kinds of Teaching Materials

VISUALIZERS

- All-in-One for Presentations, Videos & Live Broadcasts
- Collaborative Learning with Classroom Software
- Distance Learning & Hybrid Classrooms

Visualizer



A30

4K Ultra HD 60fps

An all-purpose camera combines visualizer functions with a video

camera. The compact design incorporates the camera, microphone,

and speaker, ensuring convenient and effective teaching and learning in any context, even a hybrid class or mobile learning. Dual ports, HDMI & USB, make connecting to a laptop and display hassle-free. Connect

- 13 Megapixels
- 23X Total Zoom
- HDMI & USB Output
- Built-in Mic & Speaker
- 2nd Camera Support



All-In-One



A fully adjustable mechanical arm is robustly expandable and foldable. The rotatable lens enables teachers to capture images of both A3 documents and 3D models from multiple angles, greatly improving education quality.

Mechanical Arm



- 4K Ultra HD 60fps
- 13 Megapixels
- 322X Total Zoom (14X Optical Zoom)
- HDMI & VGA Output / Input







- Full HD 1080p 60fps
- 13 Megapixels
- 35.2X Total Zoom
- HDMI & VGA Output / Input





M17-13M Intro Video





- 4K Ultra HD 60fps
- 13 Megapixels
- 23X Total Zoom
- HDMI Output





- Full HD 1080p 60fps
- 8 Megapixels
- 20X Total Zoom
- HDMI & VGA Output







- 3264 x 2448 (8M)
- 8 Megapixels
- 16X Total Zoom (via AVerTouch)
- USB 2.0 Output





Wireless

Wireless visualizers support both wired and wireless image sharing, and they work as webcams for livestreaming. Also, they feature a high-endurance Li-ion battery so teachers can break space imitations and take learning anywhere.



M70W

- 4K Ultra HD 60fps
- 13 Megapixels
- 230X Total Zoom (10X Optical Zoom)
- HDMI Output / Input



M70W & M15W Intro Video





M15W

- 4K Ultra HD 60fps
- 13 Megapixels
- 23X Total Zoom
- HDMI Output









F50+



- 13 Megapixels
- 230X Total Zoom (10X Optical Zoom)
- HDMI & VGA Output / Input



- 4K Ultra HD 60fps
- 13 Megapixels
- 23X Total Zoom
- HDMI & VGA Output / Input

The 360° flexible arm features high adjustability and mobility. Bend and adjust the gooseneck however you need to without missing a single detail. Plus, portable designs let you carry them anywhere to conveniently upgrade learning environments.

F17+ & F50+ Intro Video



Flexible Arm

USB

USB visualizers are easy to operate, allowing users to transmit images and videos on computers by simply plugging in a USB cable. Online teaching is much easier without complex installation steps and troublesome cables.



U70i

- 4K Ultra HD 30fps
- 13 Megapixels
- 16X Total Zoom
- USB 2.0 Output
- * Available in 202302



U50+

- 3264 x 2448 (8M)
- 8 Megapixels
- 16X Total Zoom
- Mini USB 2.0 Output
- * Available in 2023Q2





AVer Classroom Software

flower

Sphere2 (For Teachers)

Teachers can access the visualizer menu and operate teaching functions through laptops or tablets.



ClassSend (For Students)

Students can log into a virtual classroom to interact by receiving, editing, and sharing files.



CaptiSphere (For Teachers & Students)

Google Cloud Partner

Partner

Google for Education

Teachers can easily edit videos, create materials, and give guizzes. Students can download the materials at any time.



CaptureShare

Teachers can easily record video, live stream, and capture still images during class to rich collaborative experience.



AVerTouch

AVerTouch can one-touch connect AVer visualizers with mobile devices for content sharing. Teachers can sync to the cloud to automatically save annotated, captured, and recorded files.

AVerTouch & Google Classroom Video



CHARGING CARTS

- √ Intelligent Charging Technology
- **√** Safe & Stable Design
- **▼** Service Suitable for Different Mobile Devices
- **√** Unrivaled Warranty
- √ Superb Training & Customer

Charging Cart Promo Video

The intelligent charging system dynamically monitors different charging areas, automatically distributing electricity according to demand, centralizing the power in the lowest battery area and ensuring every device is efficiently charged.



C36i+

US. EU & UK SKUs

- 36-Device Capacity
- Intelligent Charging Technology
- Smooth Slide-Out Shelves
- Adjustable Device Dividers
- Patented Cable-Clip Management





C20i

US, EU & UK SKUs

- 20-Device Capacity
- Intelligent Charging Technology
- Adjustable Device Dividers
- Patented Cable-Clip Management

C20i Intro Video



USB Charging

Teachers can charge and sync data to mobile devices at the same time. The USB ports are installed at the front for easy plug-and-go charging.



E32c+ E24c+

EU & UK SKUs

- 32 or 24-Device Capacity
- Cycle Charging Technology
- Streamlined Cable Management
- Space-Saving Design

E32c & E24c Intro Video





AC Charging

E12

US, EU & UK SKUs

- 12-Device Capacity
- Fully Charging Technology
- DIY Charging Station
- Adjustable Device Dividers
- Patented Cable-Clip Management







C30u+

USB Type-C

- 30-Device Capacity
- DC 5V 3A Charging Power
- 1 USB Port for 1 Device
- Smooth Slide-Out Shelves



DISTANCE LEARNING TRACKING CAMERAS

Perfect for distance learning and hybrid classrooms. Simple controls and plug-and-play connectivity are the biggest advantages and ideal for installing in every classroom. Teachers can present freely onstage while livestreaming so students can learn no matter where they are.



DL30 USB Type-B



- Full HD 1080p at 60fps
- 12X Optical Zoom
- Upside-Down Installation
- No Extra Devices Needed
- Gesture Control Al
- Al Auto Tracking Modes: Presenter/Zone/Hybrid Mode











HELP THE BEE TO GET TO THE HIVE



PRO AV CAMERAS

Broadcast, stream, and record—all with one camera! Equipped with optical zooms and advanced AI tracking technology, Professional PTZ Cameras capture every detail of classrooms, auditoriums, stages, meeting rooms, and houses of worship.

Technology Partners

















****** KALTURA




















NewTek*











PTC330UV2

- 4K Ultra HD 30fps
- 30X Optical Zoom
- Upside-Down Installation
- No Extra Devices Needed
- License Upgrade to NDI®
- Al Auto Tracking Modes: Presenter/Zone/Hybrid











PTC320UV2 PTC320UNV2 NDI HX

- 4K Ultra HD 30fps
- 21X Optical Zoom
- Upside-Down Installation
- No Extra Devices Needed
- License Upgrade to NDI®*
- Al Auto Tracking Modes: Presenter/Zone/Hybrid
- * License Upgrade to NDI® is only available for PTC320UV2





Auto Tracking Cameras



PTC310UV2

- 4K Ultra HD 30fps
- 12X Optical Zoom
- Upside-Down Installation
- No Extra Devices Needed
- License Upgrade to NDI®
- Al Auto Tracking Modes: Presenter/Zone/Hybrid









PTC310HWV2

- Full HD 1080p 60fps
- 12X Optical Zoom
- Upside-Down Installation
- No Extra Devices Needed
- License Upgrade to NDI®
- Al Auto Tracking Modes: Presenter/Zone/Hybrid







Wide Area Mode Presenter Mode



Stage Mode



Segment Mode Zone Mode



Hybrid Mode

License Upgrade to NDI®





PTC500+

- Full HD 1080p 60fps
- 30X Optical Zoom
- Dual Lens Design
- No Extra Devices Needed
- Multi-Presenter Detection
- Al Auto Tracking Modes: Wide Area/Stage/Segment

PTC500S

Intro Video



PTC115+

- Full HD 1080p 60fps
- 22X Optical Zoom
- Dual Lens Design
- No Extra Devices Needed
- Multi-Presenter Detection
- Al Auto Tracking Modes: Wide Area/Stage/Segment





PTZ330UV2 PTZ330UNV2 NDI HX3

- 4K Ultra HD 60fps
- 30X Optical Zoom
- Upside-Down Installation
- Al Function: SmartShoot



PTZ Cameras

PTZ310UV2 PTZ310UNV2 NDI HX3

- Upside-Down Installation





Value-added Software



CaptureShare

Connect Your PTZ Camera to Any Laptop or Desktop



PTZ Control Panel

Replace Your Remote Control with an iPad® & iPhone®



PTZ Link

Turn AVer's PTZ Camera To a Voice Tracking Camera



PTZ Management

Change the Way You Manage 200+ PTZ Cameras



OBS Plugin for PTZ Cameras

Produce Unique Video Capturing with AVer PTZ Cameras

Visualizers Comparison Chart

Model	A30	M90UHD	M17-13M	M15-13M	M11-8MV	M5
Туре	All-In-One			Mechanical		
Sensor (MP)	13	13	13	13	8	8
Wireless Connectivity	X	X	X	X	X	Χ
Digital Zoom	23X	23X	35.2X	23X	20X	16X
Optical Zoom	1X	14X	1X	1X	1X	1X
Max Display Resolution	4K	4K	1080p	4K	1080p, 3168 x 2376 (USB)	3264 x 2448 (8M)
Shooting Area	Larger than A3	Larger than A3	Larger than A3	Larger than A3	Larger than A3	Larger than A3
Max FPS	60fps	60fps	60fps	60fps	60fps	Full HD 1080p at 60fps, 3264 x 2448 at 15fps
External Storage	USB	SD / USB	SD / USB	X	Micro SD / USB	X
USB to PC	√	√	√	√	√	√
Webcam Support (UVC)	√	√	√	√	√	√
Built-in MIC	√	√	√	√	√	√
Line Out	X	√	√	X	X	X
Built-in Speaker	√	X	X	X	X	X
One-touch Recording	√ (Remote Control)	√	√	X	√	X
Onboard Annotation	X	X	√	X	√	Χ
HDMI	Out	Out / In	Out / In	Out	Out	Χ
VGA	X	Out / In	Out / In	X	Out	X
RS-232	X	Optional	X	X	X	X
Remote Control	√	√	√	X	X	X
Rechargeable Battery	X	X	X	X	X	X
Warranty	5 Years	5 Years	5 Years	3 Years	5 Years	1 Year

^{*} Specifications may vary depending on countries and are subject to change without notice.

M70\	M15W	F50+	F17+	U70i	U50+
Mechani	cal & Wireless	Fle	exible	US	В
13	13	13	13	13	8
√	√	X	X	X	X
23X	23X	23X	23X	16X	16X
10X	1X	10X	1X	1X	1X
4K	4K	4K	4K	4K	3264 x 2448 (8M)
Larger than A3	Larger than A3	Larger than A4	Larger than A3	Larger than A3	Larger than A3
60fps	60fps	60fps	60fps	Full HD 1080p at 60fps, 4K at 30fps	Full HD 1080p at 60fps, 3264 x 2448 at 15fps
USB	X	SD / USB	SD / USB	X	X
\checkmark	√	√	√	√	√
\checkmark	√	√	√	√	√
\checkmark	√	√	√	√	√
X	X	√	√	X	X
X	X	X	X	X	X
√	X	√	√	X	X
X	X	X	X	X	X
Out / In	Out	Out / In	Out / In	X	X
X	X	Out / In	Out / In	X	X
X	X	√	X	X	X
\checkmark	X	√	√	X	X
\checkmark	√	X	X	X	X
5 Years	3 Years	5 Years	5 Years	2 Years	2 Years

Carts Comparison Chart

Model	C36i+	C20i	E32c+ / E24c+	E12	C30u+
Туре		AC CI	narging		USB Charging
Device Capacity	36	20	E32c+: 32 E24c+: 24	12	30
Supported Devices	Up to15"	Up to 16"	Up to 15.6"	Up to 15.6"	All USB Charged
Slot Dimensions (W x D x H)	36 x 380 x 260 mm	36 x 419 x 330 mm	E32c+: 26 x 367 x 301 mm E24c+: 32 x 367 x 301 mm	30 x 426 x 311 mm	34 x 380 x 225 mm
Cart Dimensions (W x D x H)	790 x 634 x 1070 mm	688 x 637 x 1060 mm	640 x 632 x 1039 mm	527 x 453 x 445 mm	637 x 686 x 1037 mm
LED Indicator Lights	√	√	×	×	√ (Individual)
Charging/Sync/Disinfection	Charging	Charging	Charging	Charging	Charging/Sync
Power Management	Adaptive Intelligent Charging	Self-monitoring, Smart AC Charging	Smart Cycle AC Charging	Smart AC charging	USB Type-C
Cable Management	√	√	√	√	√
Individual AC Adapter Compartments	√	√	√	×	X
Shelves	Sliding	Fixed	Fixed	Fixed	Sliding
Net Weight	80 kg (176.4 lbs)	65.6 kg (145 lbs)	E32c+: 52 kg (114.64 lbs) E24c+: 50 kg (110.23 lbs)	17 kg (37.48 lbs)	76 kg (168 lbs)
External Power Outlets	2	2	×	×	2
Warranty (Mechanical / Electrical)	10 yr / 5 yr	10 yr / 5 yr	10 yr / 5 yr	10 yr / 5 yr	10 yr / 5 yr

^{*} Specifications may vary depending on location and are subject to change without notice.

Distance Learning Cameras Comparison Chart

Model	DL30	DL10
Camera		
Effective Picture Elements	2 Megapixels CMOS	2 Megapixels CMOS
Output Resolution	Full HD 1080p 60fps	Full HD 1080p 60fps
Optical Zoom	12X	3X
HFOV	76.5° (Wide) to 6.8° (Tele)	82° (Wide) to 31.7° (Tele)
Pan/Tilt Rotation	Pan: ±170°, Tilt: ±90°	Pan: ±170°, Tilt: ±90°
Pan/Tilt Speed	Pan: 1° to 90°/sec, Tilt: 7.85° to 45°/sec	Pan: 1° to 100°/sec, Tilt: 10.8° to 100°/sec
Preset Speed	Pan: 120°/sec, Tilt: 110.84°/sec	Pan: 200°/sec, Tilt: 200°/sec
Output Interfaces	IP, USB	IP, USB
USB Video Formats	MJPEG, YUY2	MJPEG, YUY2
UVC	UVC 1.1	UVC 1.1
UAC	UAC 1.0	UAC 1.0
Control Interfaces	IP, USB	IP, USB
Network Protocols	IPv6, IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, DHCP, RTP / RTCP, RTSP, RTMP, VISCA over IP	IPv6, IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, DHCP, RTP / RTCP, RTSP, RTMP, VISCA over IP
Control Protocols	VISCA (IP), CGI (IP), USB	VISCA (IP), CGI (IP), USB
Auto Tracking Modes	Presenter Mode, Zone Mode, Hybrid Mode	Presenter Mode, Zone Mode, Hybrid Mode
Gesture Control	Tracking Control: Tracking On/Off, Full/Upper Body, Camera Control: Zoom In/Out	
Protection Modes	Privacy Mode, Sleep Mode	Privacy Mode, Sleep Mode
Microphones		
Built-in Microphones	_	2 (Omnidirectional)
Noise Suppression	-	Yes
Pickup Range	-	5 m
Sensitivity	-	-33 dBFS
Frequency Response	-	30 Hz to 20 KHz
Maximum SPL	-	129 dB SPL at 0.5 m
Warranty	Camera: 3 Years, Accessories: 1 Year	Camera: 3 Years, Accessories: 1 Year

^{*} Specifications may vary depending on location and are subject to change without notice.

Pro AV Cameras Comparison Chart

Model	PTC330UV2	PTC320UV2 PTC320UNV2	PTC310UV2	PTC310HWV2
PTZ Camera				
Effective Picture Elements	8 Megapixels Exmor CMOS	8 Megapixels Exmor CMOS	8 Megapixels Exmor CMOS	2 Megapixels Exmor CMOS
Output Resolution	4K 30fps	4K 30fps	4K 30fps	Full HD 1080p 60fps
Optical Zoom	30X	21X	12X	12X
HFOV	65.1° (Wide) to 2.34° (Tele)	52.26° (Wide) to 2.66° (Tele)	70° (Wide) to 6° (Tele)	70° (Wide) to 6° (Tele)
Panoramic Camera				
Effective Picture Elements	-	_	_	_
Output Resolution	-	-	_	-
HFOV	-	-	-	-
Camera Operation				
Pan/Tilt Rotation	Pan: ±170°, Tilt: +90°/-30°	Pan: ±170°, Tilt: +90°/-30°	Pan: ±170°, Tilt: +90°/-30°	Pan: ±170°, Tilt: +90°/-30°
Pan/Tilt Speed	0.1° to 100°/sec	0.1° to 100°/sec	0.1° to 100°/sec	0.1° to 100°/sec
Preset Speed	200°/sec	200°/sec	200°/sec	200°/sec
Output Interfaces	3G-SDI, HDMI, IP, USB	3G-SDI, HDMI, IP, USB	3G-SDI, HDMI, IP, USB	HDMI, IP, USB
USB Video Formats	MJPEG, YUY2	MJPEG, YUY2	MJPEG, YUY2	MJPEG, YUY2
UVC	UVC1.1	UVC1.1	UVC1.1	UVC1.1
UAC	UAC1.0	UAC1.0	UAC1.0	UAC1.0
Control Interfaces	RS-232, RS-422, IP, USB	RS-232, RS-422, IP, USB	RS-232, RS-422, IP, USB	RS-232, RS-422, IP, USB
Network Protocols	IPv6, IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, DHC	P, RTP/RTCP, RTSP, RTMP, VISCA over IP		
Control Protocols	VISCA (RS-232/RS-422/IP), PELCO-D & PELCO-P	(RS-232/RS-422), CGI (IP)		
NDI® HX	License Upgrade	NDI® HX2 (PTC320UNV2 only)	License Upgrade	License Upgrade
Auto Tracking Modes / Al Functions	Presenter Mode, Zone Mode, Hybrid Mode	Presenter Mode, Zone Mode, Hybrid Mode	Presenter Mode, Zone Mode, Hybrid Mode	Presenter Mode, Zone Mode, Hybrid Mode
Warranty	Camera: 3 Years, Accessories: 1 Year			

^{*} Specifications may vary depending on location and are subject to change without notice.









2 Megapixels CMOS	2 Megapixels CMOS	8 Megapixels Exmor CMOS	8 Megapixels Exmor CMOS	
Full HD 1080p 60fps	Full HD 1080p 60fps	4K 60fps	4K 60fps	
30X	22X	30X	12X	
65° (Wide) to 2.3° (Tele)	67° (Wide) to 3.7° (Tele)	62.3° (Wide) to 2.5° (Tele)	72.8° (Wide) to 6.7° (Tele)	
2 Megapixels CMOS	2 Megapixels CMOS	-	_	
Full HD 1080p 60fps	Full HD 1080p 60fps	-	-	
110°	110°	-	-	
Pan: ±175°, Tilt: +90°/-30°	Pan: ±175°, Tilt: +90°/-30°	Pan: ±170°, Tilt: +90°/-30°	Pan: ±170°, Tilt: +90°/-30°	
2° to 50°/sec	2° to 50°/sec	0.1° to 100°/sec	0.1° to 100°/sec	
160°/sec	160°/sec	200°/sec	200°/sec	
3G-SDI, HDMI, IP, USB	3G-SDI, HDMI, IP, USB	3G-SDI, HDMI, IP, USB	3G-SDI, HDMI, IP, USB	
MJPEG, YUY2	MJPEG, YUY2	MJPEG, YUY2	MJPEG, YUY2	
UVC1.1	UVC1.1	UVC1.1	UVC1.1	
UAC1.0	UAC1.0	UAC1.0	UAC1.0	
RS-232, IP, USB	RS-232, IP, USB	RS-232, RS-422, IP, USB	RS-232, RS-422, IP, USB	
IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, DHCP, RTP / RTC	P, RTSP, RTMP, ONVIF, VISCA over IP	IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, DHCP, RTP / RTCP, RTSP, RTMP, SRT, HLS, NDI, LLDP, VISCA over IP		
VISCA, Pelco-D, Pelco-P, CGI		VISCA (RS-232/RS-422/IP), PELCO-D & PELCO-P (RS-232/RS-422), CGI (IP)		
-	-	NDI® HX3 (PTZ330UNV2 only)	NDI® HX3 (PTZ310UNV2 only)	
Wide Area Mode, Stage Mode, Segment Mode	Wide Area Mode, Stage Mode, Segment Mode	SmartShoot	SmartShoot	



AVer Takes Care of Customers:

- Installation & Operation Services
- Technical Support
- Customized Trainings











AVer Information Inc.

©2023 AVer Information Inc. All rights reserved. All brands and logos are trademarks of their respective companies. Distributor/Dealer