

Key Features

- 3rd generation laser phosphor technology with up to a 30,000hour lifespan
- Designed for Xbox with 1440p
 @ 120Hz for an unrivaled
 gaming experience
- True 4K HDR immersive visual experience with up to a 300" screen
- 3,500 ANSI Lumens offering bright images in any environment
- High native contrast ratio through 0.65" DMD chip



Product **Description**

Transform any home into a cinematic experience with the V554K laser home projector. Adopting the 3rd generation laser phosphor technology with 3,500 ANSI Lumens and up to 30,000 hours lifespan, it delivers vibrant and bright visuals without the need for lamp replacement. This projector is designed for Xbox, supporting Xbox-exclusive resolution and refresh rate combinations for a seamless gaming experience. With the support of 1440p at a 120Hz refresh rate, it strikes a perfect balance of visual quality and fluidity that gamers love. Experience enhanced visual depth on a screen size of up to 300" with a high native contrast ratio through 0.65" DMD chip. The V554K features V lens shift, 1.36x optical zoom, H/V keystone, and 4 corner adjustment, allowing you to easily set up a big screen tailored to your preferences.







3. Keypad 4. Top IR 5. Front IR 6. Lens 7. Focus Ring 10. USB-A (5V/1.5A , Service) 11. 12V Trigger 12. Zoom Ring 13. Audio Out 14. DC In

Visit Us

www.viewsonic.com

SPECIFICATION

OTHERS

Native Resolution:	3840x2160	Power Supply Voltage:	Power adaptor: Input: 100~240V Output: 19.5VDC / 9.23A
Brightness:	3500 (ANSI Lumens)		
Contrast Ratio:	3,500,000:1	Develop Organization	Normal: 180W
Display Color:	1.07 Billion Colors	Power Consumption:	Standby: <0.5W
Light Source Type:	Laser Phosphor	Operating Temperature:	0~40°C
Light Source Life (hours) with Normal Mode:	20000	Carton:	Brown
Light Source Life (hours) with	30000 (Eco)	Net Weight:	3.30kg
SuperEco Mode:	,	Gross Weight:	4.70kg
Lens:	F=2.51-2.93, f=15.985- 21.423mm	Dimensions (WxDxH) with Adjustment Foot:	286x216x129mm
Projection Offset:	137%+/-10%	Packing Dimensions:	400x280x155mm
Throw Ratio:	1.06-1.45	OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Arabic, Vietnamese, Greek, Norsk. Total 23 languages
Optical Zoom:	1.36x		
Digital Zoom:	0.8x-2.0x		
Image Size:	30"-300"		
Throw Distance:	1-7m (100"@2.35m)		
Keystone:	H:+/-30° , V:+/-30°		
Lens Shift V. Range:	+15%, -0%		English, S-Chinese, T-
Audible Noise (Normal):	31dB	User Guide Language: STANDARD ACCESSORY	Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
Audible Noise (Eco):	26dB		
Input Lag:	4.2ms		
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p		
Horizontal Frequency:	15K-135KHz	Power Cord:	1
Vertical Scan Rate:	23-240Hz		1
INPUT		Remote Control:	(w/ backlit)
HDMI:	2	QSG:	Yes
	(HDMI 2.0/ HDCP 2.2)	Warranty:	*Warranty offered may differ from market to market
OUTPUT			
Audio-out (3.5mm):	1	OPTIONAL ACCESSORY	
Audio-out (HDMI ARC):	1 (eARC) (Share with HDMI Input)	Wall/Ceiling Mount: Carry Bag:	PJ-WMK-007 PJ-CASE-008
Speaker:	15W	, ,	
USB Type A (Power):	1 (5V/1.5A)		
12V Trigger (3.5mm):	1		
CONTROL			
RS232 (DB 9-pin male):	1		
USB Type A (Services):	1 (share with USB A Output)		