EB-PQ2008B



4K (8.3m pixels)



DATASHEET / BROCHURE



















Perfect for anyone needing an ultra-high resolution experience, the EB-PQ2008B is a powerful, compact 8,000lm 4K projector.

Designed to engage and captivate audiences with ultra-high resolution, large format content, the EB-PQ2008B uses 3LCD technology to deliver outstanding colour reproduction, while Epson's patented 4K Crystal Motion technology offers stunning image quality. Affordable and energy-efficient, the projector also features interchangeable lenses, a light and compact design and extensive connectivity.

Limitless creativity

Building on the success of the EB-PU Series, the EB-PQ2008B is not only small and light, but is highly affordable, versatile, energy-efficient and packed with advanced features. Allowing you the freedom to create unforgettable immersive experiences.

A revolutionary 4K experience

Marvel at the clarity of the images produced by Epson's latest 4K technology. Combining its patented, state of the art 4K Crystal Motion and double micro-lens array technologies, Epson achieves a new benchmark in 4K image quality.

Fantastically flexible

Featuring a wide range of connectivity, including HDMI in/out supporting 120Hz 4K. This high brightness projector also benefits from cross-platform lens compatibility, using the same 4K lenses as the existing EB-PU Series, including the ELPLX02S zero-offset ultra-short throw lens which is perfect for immersive spaces. This projector is supplied 'body-only', allowing you to build the perfect solution for your installation.

Reliable

Built for exceptional reliability, the EB-PQ2008B is compatible with the ELPAF63 External Air Filter and provides up to 20,000 hours maintenance-free operation, or even longer in extended modes.

Extensive software

Compatible with the ELPEC01 camera, Epson Projector Professional Tool and Epson Config Tool for a wealth of calibration, assistance and control functionality.

KEY FEATURES

- Patented 4K and imaging technology Outstanding 4K image quality delivers superb immersivity
- Ultra-compact and lightweight Small, powerful 8,000lm 4K projector
- Cross-platform lens compatibility
 Lets you build the optimal projection
 solution for every requirement
- Fit-and-forget reliability
 Up to 20,000 hours maintenance free
- Reduced environmental impact
 Energy-efficient with reduced
 requirements for packaging and transport
- Legal Statement

Complies with The UK Product Security and Telecommunications Infrastructure (Product Security) requirements. Epson will provide security updates for 7 years from purchase



PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 1.04 inch with C2 Fine

IMAGE

Color Light Output 8,000 Lumen- 5,600 Lumen(economy) In accordance with IDMS15.4

White Light Output 8,000 Lumen - 5,600 Lumen(economy) In accordance with ISO 21118:2020

Portrait Colour Light Output 8,000 lm
Portrait White Light Output 8,000 lm

Resolution 4K 3840 x 2160, 8.3m pixels, 16:9

Aspect Ratio 16:9

Contrast Ratio Over 5,000,000: 1
Native Contrast 3,000: 1
Light source Laser

Laser Light source 20,000 hoursDurability High, 30,000 hoursDurability Eco

Keystone Correction Manual vertical: ± 45 °, Manual horizontal ± 30 °

Colour Video Processing 10 Bits

Colour Reproduction Upto 1.07 billion colours

HDR support HDR10, HLG

OPTICAL

0.34 - 7.16:1 Throw Ratio Zoom Motorized Optical Lens Lens Shift varies by lens Screen Size varies by lens Projection Distance Wide varies by lens Projection Distance Tele varies by lens Projection Distance Wide/Tele varies by lens Projection Lens F Number Projection Lens Focal Length varies by lens Projection Lens Focus Motorized varies by lens Interchangeable Lens Yes Standard Lens Not included

CONNECTIVITY

Interfaces USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet interface (100 Base-TX / 10

Base-T), Wireless LAN IEEE 802.11a/b/g/n (optional), HDMI in (2x), HDMI out, HDBaseT, Jack

plug out, Near Field Communication (NFC), USB content playback, Remote

Network Protocol HTTPS, IPv6, SNMP, ESC/VP.net, PJLink

ADVANCED FEATURES

Video Color Modes

Projector control

Security Kensington lock, Control panel lock, Padlock, Wireless LAN unit lock, Wireless LAN security,

Password protection

Other features 21:9 aspect ratio support, A/V mute, Auto Power On, Auto source search, Direct Power on/off,

Edge Blending, Frame interpolation, Freeze image, Horizontal and vertical keystone correction, Lens position memory, Long light source life, OSD copy function, Point correction, Quick

Corner, Schedule Function, Web Control, Wireless LAN capable, iProjection App Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709 via: Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery

EB-PQ2008B

WHAT'S IN THE BOX

- Cable cover
- Lens connector cap
- Main unit
- Power cable
- Remote control incl. batteries
- Information sheet
- Quick Start Guide
- Document Pack



PRODUCT SPECIFICATIONS

EB-PQ2008B

GENERAL

Power consumption 453 Watt (Normal On-Mode), 502 Watt (Normal Peak-mode), 410 Watt (Eco Peak-Mode), 0.5

Watt (Energy saving standby)

Heat Dissipation 1,707 BTU/hour (max)

Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions 545 x 436 x 189 mm (Width x Depth x Height)

Product weight 18.6 kg

Noise Level Normal:35 dB (A) - Economy:29 dB (A)

Supported Temperature Storage -10° C - 60° C

Supported Humidity Operation 20% - 80%, Storage 10% - 90%

If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could

break and cause the projector to drop from the ceiling.

If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional

assistance

Included Software Epson Creative Projection, Epson Projector Config Tool, Epson Projector Content Manager,

Epson Projector Management, Epson Projector Professional Tool

Options Air filter, Camera module, Ceiling mount, Wireless LAN unit

Room Type / Application Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection

Mapping, Rental / Staging, Signage / Retail, Visitor Attraction

Positioning Ceiling Mounted, Desktop, Floor, Flying Frame, Table Mounted, Wall Mounted

Colour Black

OTHER

Warranty 36 months Carry in

Optional warranty extension available



OPTIONAL ACCESSORIES

- Stacking Frame ELPMB76 EB-PU1000 Series V12H006AN0
- Wireless LAN Adapter ELPAP11 (2.4GHz & 5GHz) V12H005A01
- Air Filter ELPAF46
 - V13H134A46
- Camera Unit ELPEC01
 - V12HA46010
- Ceiling Mount ELPMB68
 - V12H006AE0
- External Air Filter ELPAF63 EB-PU1000 Series
- V13H134AD0
- Portrait Adaptor ELPMB78 EB-PU Series V12H006AQ0
- Rail Adaptor ELPMB85 EB-PU Series
- V12H006AX0
- Tilt Adaptor ELPMB81 EB-PU Series V12H006AT0

LOGISTICS INFORMATION

SKU	V11HB01880
EAN code	8715946718460
Country of Origin	China
Layer	2 Units
Layer Block	2 Units

For more information please contact:

Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus
* 10p per minute plus network extras. www.epson.co.uk www.epson.ie

1. 4K (3840 x 2160) is the maximum physical resolution achieved using 4K Crystal Motion technology.

2. Energy efficient based on the power consumption data publicly available for comparable market leading products. Reductions in packaging and transportation requirements assumed based on physical product size and weight and/or packaging size and weight data available for comparable market leading products. As of February 2024.

EB-PQ2008B

