

ZK708T

High brightness compact 4K UHD professional laser projector



- **7000 lumen 4K UHD projector - High brightness and compact for multiple professional environments**
- **Long life DuraCore laser technology - Delivers 30,000 hours of virtually maintenance free operation**
- **Dust resistant - Independently tested, IP6X certified**
- **Control flexibility of HDBaseT 3.0 - 4K, HDR and HLG compatibility**



At 7000 lumens, with 4K and HDR compatibility, the ZK708T combines a long-lifetime light source of up to 30,000 hours and an independent IP6X certified optical engine for 24/7 operation, offering truly maintenance-free projection. Added features include manual horizontal and vertical lens shift and built-in 15W speakers.

Specifications

UPC: 796435 44 718 2, EAN: 5055387667792, Colour: White



Display/image

| | |
|----------------------------------|--|
| Display technology | DLP |
| Resolution | UHD (3840x2160) |
| Brightness | 7,000 lumens |
| Contrast ratio | 300,000:1 |
| Native aspect ratio | 16:9 |
| Aspect ratio - compatible | 4:3,16:9,16:10 |
| Keystone correction - horizontal | +/-30° |
| Keystone correction - vertical | +/-30° |
| Displayable colours (millions) | 1073.4 |
| Horizontal scan rate | 5k~140kHzKhz |
| Vertical scan rate | 24~120HzHz |
| Uniformity | 85% |
| Screen size | 0.8m ~ 7.67m (31.5" ~ 301.8") diagonal |

Lamp info

| | |
|-------------------|--------------|
| Light source type | Laser |
| LASER life | 30,000 hours |

Optical

| | |
|-------------------------|--|
| Throw ratio | 1.2:1 ~ 1.92:1 |
| Projection distance (m) | 1.3m - 7.8m |
| Zoom | 1.6 |
| Zoom type | Manual |
| Focal length (mm) | 17.63 ~ 27.9 |
| Lens shift | Vertical -106 ~ 126%, Horizontal: +/-10% |
| Native offset | 106% |
| Lens shift | Yes - see product downloads for more information |

Connectivity

| | |
|-------------|--|
| Connections | Inputs 2 x HDMI 2.0, 2 x VGA, 2 x Audio 3.5mm, 1 x USB-A power 1.5A Outputs 1 x HDMI 2.0, 1 x Audio 3.5mm, 1 x 3D sync, 1 x 12V trigger Control 1 x HDBaseT 4K, 1 x RJ45, 1 x RS232 |
|-------------|--|

LAN - wireless networking

No

General

| | |
|-------------------------|--|
| Noise level (min) | 33dB |
| Noise level (max) | 36dB |
| 3D | Full 3D |
| Security | Security bar, Kensington Lock, Password protected interface |
| IP rating | IP6X |
| OSD / display languages | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |

24/7 operation

Yes

360° operation

Yes

Remote control

Backlit ProAV remote

Heat dissipation

883BTU/hour

Speaker count

2

Watts per speaker

15W

In the box

AC power cord
Remote control
2x AAA batteries
Quick Start Guide

Networking

| | |
|---------------------------|-----|
| LAN - control | Yes |
| LAN - wireless networking | No |
| LAN | Yes |

Power

| | |
|-----------------------------|--|
| Power supply | Universal AC 100--240V± 10%~ 50 / 60 Hz with PFC input |
| Power consumption (standby) | <0.5W |
| Power consumption (min) | 300W |
| Power consumption (max) | 366W |

Weight and dimensions

| | |
|---------------------------|-----------------|
| Dimensions (W x D x H) mm | 374 x 302 x 117 |
| Gross weight | 8.6 kg |
| Net weight | 6.3 kg |

