

CleverWall

LED Video Wall Solutions

Take your images and videos to the next level, with stunning picture quality showing every detail. With dynamic colour, enhance your content for the complete immersive experience.

CleverWall is suited to many settings. With pixel pitches and sizes to suit your environment. Easy to install, modular in construction, with a cabinet of less than 5kgs. Get the truest blacks and the whitest whites with CleverWall's high resolution technology.

11:32

•••

Integrate seamlessly for realtime wireless screensharing from up to 4 devices simultaneously. Synchronized annotating from multiple devices. Interact with CleverWall via smartphones and tablet computers.

All our LED Videowalls come with an onboard android, racking and audio speakers.

CLEVERTOUCH*

Featuring All-in-one Design

Integrated design with no external devices

Built-in Android System and audio

Revolutionary 3-in-1 board that integrates a power

supply, a receiving card and a hub board

Unified hardware and software technical support and service

180" | 199" | 220" | 249" | 299" Available in a range of pixel sizes

1.2 | 1.4 | 1.5 | 1.7 | 1.9 | 2.1 | 2.5

Available in a range of sizes 120" | 138" | 150" | 165" 180" | 199" | 220" | 249" | 299"

Key Features







Delivery Simplicity and Efficiency

Ease of use of the monitor functions with the remote control

Plug and play system, one button to turn on/off Smart remote control to access settings



Add a Pico player or CleverHub for a fully functioning, feature rich digital signage and to connect to CleverLive.

CleverWall Specifications

<table-container>Pied Pich form1.51.51.21.31.7.32.08Form1.301.00</table-container>	Display Diagonal (inches)	138"	165"	220"	220"	120"	150"	180"	
<table-container>Name Resolution13519033090135190Resolution1920/16801920/16801920/16801920/16801920/16801920/1680Brightney ResolutionUUSiteSi</table-container>	Pixel Pitch	1.5	1.9	2.54	1.2	1.38	1.73	2.08	
Resolution1920-10801920-10801920-10801920-10801920-10801920-1080Brightang (iff)	Format								
method is in the second of t	Weight (kg)	135	190	330	330	90	135	190	
Area for a serie of the seri	Resolution	1920x1080	1920×1080	1920×1080	3840x2160	1920x1080	1920x1080	1920x1080	
Nervars Rain	Brightness (nits)				≥550		1		
<table-container>New and set of the set of</table-container>	Refresh Rate (Hz)		3840						
Nail and size33001710360020594480275C0.02692414993330173739962248Total Physical Size367327188230.04884228"503.04884228"503.026782118323.0334422004028.54010237928.5Pitter in pictureSSS26782118323.048140237503.026782118323.0334422004028.54010237928.5Picture in pictureSSSSS34422004028.54010237928.5Multer FragencySS <th>Contrast Ratio</th> <th colspan="7">≥3000:1</th>	Contrast Ratio	≥3000:1							
Ted Physical Seq395/3188/300395/3183/300395/3183/300395/3103/300401/02/32/300401/02/	Viewing Angle (H/V)		160° / 140°						
Audio frequencySubmit in 2x 30W audio system, 2.0 channel, full frequency raugeInstallation ModeUUSB InterfaceUUSB InterfaceSubmit in 2x 30W audio system, 2.0 channel, full frequency raugeIDMI InterfaceUCabined ArangemetSu56x68x88x84x45x56x6Cabined ArangemetSu56x68x88x84x45x56x6Cabined ArangemetSu56x68x88x84x45x56x6Cabined ArangemetSu56x68x88x84x45x56x6Cabined ArangemetSu55x56x68x88x88x84x45x56x6Cabined ArangemetSu5Su5Su5Su5Su5Su5Su5Su5Power (nosumption (inckes)2.190,742.891,13Su52.9972.9972.997Su5Su5Su5Pikely Consumption (inckes)19.9°2.49°2.9972.9972.997Su5	Visual Led Size (mm)	3050x1716	3660x2059	4880x2745	4880x2745	2664x1499	3330x1873	3996x2248	
Alido FrequencyBuil- 2- Status - Stat	Total Physical Size	3063X1846X30.5	3673X2188X30.5	4884X2875X30.5	4884X2875X30.5	2678X1630X28.5	3344X2004X28.5	4010X2379X28.5	
Mail ModelUSB InterfaceUSUSUS USE USE USE USE USE USE USE USE U	Picture in picture		Yes - Support HDMI 2.0 PIP						
YesYesYesYesYesYesS55S57S57S55S57 <th colspan<="" th=""><th>Audio Frequency</th><th colspan="7">Built-in 2x 30W audio system, 2.0 channel, full frequency range</th></th>	<th>Audio Frequency</th> <th colspan="7">Built-in 2x 30W audio system, 2.0 channel, full frequency range</th>	Audio Frequency	Built-in 2x 30W audio system, 2.0 channel, full frequency range						
HMI InterfaceSx56x68x84x45x56x6Cabiet ArrangementSx56x68x88x84x45x56x6Cabiet MaterialSx5Sx5Sx5Sx5Sx5Maintenance2x19/07.402x89/1.31Sx5Sx5Sx5Sx5Sx5Sx5Power Consumption Onfices2x19/07.402x89/1.31Sx5 <th>Installation Mode</th> <th colspan="7">Wall Mounting / Mobile Stand - Suitable for trolleys up to 165"</th>	Installation Mode	Wall Mounting / Mobile Stand - Suitable for trolleys up to 165"							
Cabinet Arrangement Gabinet Material5x56x68x88x84x45x56x6Gabinet MaterialManualSysMagnalSysMagnalSysMagnalSysMagnalSysMagnalSysMagnal <td< th=""><th>USB Interface</th><th colspan="7">Yes</th></td<>	USB Interface	Yes							
Cabinet MarcianCabinet AddressionAugualiumMaintenance2.19/0.742.83/1.13 $5 U \cdot T$ $6.202.48$ $1.85/0.4$ $2.42/0.82$ $3.38/1.35$ Power Consumption (Max,/Ave.) (KW) $2.19/0.74$ $2.83/1.13$ $5 U \cdot T$ $6.202.48$ $1.85/0.4$ $2.42/0.82$ $3.38/1.35$ Pise Pitch $2.19/0.74$ $2.83/1.13$ $5 U \cdot T$ $6.202.48$ $1.85/0.4$ $2.42/0.82$ $3.38/1.35$ Pise Pitch 1.97° $6.202.48$ $1.85/0.4$ $2.42/0.82$ $3.38/1.35$ Pise Pitch 1.97° $6.202.48$ $1.85/0.4$ $2.42/0.82$ $3.38/1.35$ Pise Pitch 1.97° $6.202.48$ 9.69° 9.9° Pise Pitch 1.27 $5.202.48$ 9.9° 9.9° Pise Pitch $1.272.48$ $9.822.48$ $9.822.48$ $9.822.48$ Resolution $1.272.482.4893.58$ $9.622.482.4892.58$ $9.622.482.4892.582.482.4892.582.582.582.582.582.582.582.582.582.58$	HDMI Interface				Yes				
Maintenance Ford Resource commption (Max,Ave, (KW)) 2.190.74 2.83/1.13 5∠/r 6.202.48 1.850.74 2.42/0.82 3.38/1.35 Pixel Pixel, (KW) 2.190.74 2.83/1.13 5∠/r 6.202.48 1.850.74 2.42/0.82 3.38/1.35 Display Consumption (Inches) 199° 2 749° 2.42/0.82 3.38/1.35 Pixel Pixch 99° 2 749° 2.42/0.82 3.38/1.35 Pixel Pixch 727 3.38/1.35 3.38/1.35 3.38/1.35 Pixel Pixch Pixel Pixch 727 728/1.52 3.38/1.35 3.38/1.35 <th>Cabinet Arrangement</th> <th>5x5</th> <th>6x6</th> <th>8x8</th> <th>8x8</th> <th>4x4</th> <th>5x5</th> <th>6x6</th>	Cabinet Arrangement	5x5	6x6	8x8	8x8	4x4	5x5	6x6	
Power Consumption (Max,/Ave.) (KW)2.89/.035.21/.135.21/.241.850.441.850.442.42/0.823.38/.13Display Consumption (Inches)99°249°242/023.38/.13Pikel Pitch99°249°249°29°Pikel Pitch1.275.913.87/.35Pikel Pitch1.275.923.87/.35Pikel Pitch1.272.92°3.87/.35Pikel Pitch1.272.92°3.87/.35Pikel Pitch1.272.92°3.87/.35Pikel Pitch1.272.92°3.87/.35Pikel Pitch1.272.92°3.87/.35Pikel Pitch1.272.92°3.87/.35Pikel Pitch1.272.92°3.87/.35Pikel Pitch1.272.92°3.87/.35Pikel Pitch1.272.653.87/.35Pikel Pitch1.272.653.87/.35Pikel Pitch1.275.011.27Pikel Pitch1.271.021.02Pikel Pitch1.271.021.02Pikel Pitch1.271.021.02Pikel Pitch1.021.021.02Pikel Pitch1.021.021.02Pikel Pitch1.021.021.02Pikel Pitch1.021.021.02Pikel Pitch1.021.021.02Pikel Pitch1.021.021.02Pikel Pitch1.021.021.02Pikel Pitch1.021.021.	Cabinet Material				Magnalium				
(My)Image: Market in the second s	Maintenance				Front				
(index)(median control of the second of the sec		2.19/0.74	2.83/1.13	5.2/1.77	6.20/2.48	1.85/0.74	2.42/0.82	3.38/1.35	
(indes)(median definition of the second									
FormatAle of the second se			199"		249"		299"		
Weight (kg)175265375Resolution	Pixel Pitch		1.27		1.59		1.91		
ResolutionImage: Contract of the second of the	Format				32.9				
Arightness (nits)Herish Rate (Hz)S550Refresh Rate (Hz)G3840Contrast RatioG550:1Yiewing Angle (H/V)GG7320x2058Yisual Led Size (mm)A880x1372GMad20x305Total Physical Size (mm)A894x1489x30.5G7334x2175x30.5Istalation ModeG	Weight (kg)		175		265		375		
Refresh Rate (Hz)SakuRefresh Rate (Hz)SakuContrast RatioSakuViewing Angle (H/V)Gotton:Visual Led Size (man)A & & & & & & & & & & & & & & & & & & &	Resolution		3840×1080						
Contrast Ratio6500:1Contrast Ratio6500:1Viewing Angle (H/V)6500:1Visual Led Size (mm)4880x13726100x17157320x2058Total Physical Size (mm)6100x17157320x2058Instalation ModeCWII MountingUSB InterfaceYesChinet Arrangement884100x101512x6Cabinet Quantity3250MittenanceFront	Brightness (nits)		≥550						
Viewing Angle (H/V)Gene Colspan="2">Gene Colspan="2"	Refresh Rate (Hz)		3840						
Visual Led Size (mm)4880x13726100x17157320x2058Total Physical Size (mm)4894x1489x30.56114x1832x30.57334x2175x30.5Instalation Mode	Contrast Ratio		6500:1						
Total Physical Size (mm)4894x1489x30.56114x1832x30.57334x2175x30.5Instalation Mode	Viewing Angle (H/V)		160°/140°						
Instalation ModeWall MountingUSB InterfaceYesHDMI InterfaceYesCabinet Arrangement8x410x512x6Gabinet Quantity325072MaintenanceFrontColspan="2">Colspan="2"Colspan="2">Colspan="2">Colspan="2"Colspan="2"Colspan="2">Colspan="2"Colspan="2"Colspan="2">Colspan="2"Colspan="2"Colspan="2">Colspan="2"Colspan="2"Colspan="2">Colspan="2"Colspan="2">Colspan="2"Colspan="2">Colspan="2"Colspan="2">Colspan="2"Colspan="2">Colspan="2"Colspan="2">Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"Colspan="2"	Visual Led Size (mm)		4880x1372		6100x1715		7320x2058		
USB Interface Yes HDMI Interface Yes Cabinet Arrangement 8x4 10x5 Gabinet Quantity 32 50 72 Maintenance Front	Total Physical Size (mm)		4894x1489x30.5		6114x1832x30.5		7334x2175x30.5		
HDMI Interface Yes Cabinet Arrangement 8x4 10x5 Gabinet Quantity 32 50 72 Maintenance Front Contenant of the second of	Instalation Mode		Wall Mounting						
Cabinet Arrangement8x410x512x6Cabinet Quantity325072MaintenanceFront	USB Interface				Yes				
Cabinet Quantity 32 50 72 Maintenance Front Front	HDMI Interface				Yes				
Maintenance Front	Cabinet Arrangement		8x4		10x5		12x6		
	Cabinet Quantity		32		50		72		
Power Consumption (KW) 3.10 4.38 5.66	Maintenance				Front				
	Power Consumption (KW	0	3.10		4.38		5.66		

1. The installation mode with mobile stand only available for 120", 138", 150", 165".

2. "31mm" from overall dimension refers to thickness of screen.

Note: Specifications are for reference only and are subject to change without notice.

© 2021 Clevertouch. All rights reserved. Sahara Presentations Systems PLC. is part of the Boxlight group of companies, and the owner of trademarks in several global jurisdictions including but not limited to Clevertouch, the Clevertouch logo, UX Pro, IMPACT[™], IM