ViewSonic[®] **Second Contract Second Contract Second Contract Second Contract Second S**

Key Features

- 6,000 ANSI Lumens offering bright images in any environment
- Up to a 300" ultra-large screen with a lower cost-per-inch
- Supports a 21:9 aspect ratio, ideal for Microsoft Teams Rooms
- Installation flexibility: H/V lens shift, 1.6x optical zoom, and H/V keystone correction
- 2nd generation laser phosphor technology with a lifespan up to 30,000 hours



Product **Description**

The LSC601WU is a lamp-free, high-brightness projector designed for commercial, educational, and public spaces. Utilizing 2nd generation laser phosphor technology, this projector delivers 6,000 ANSI Lumens of brightness for up to 30,000 hours and can project an ultra-large screen up to 300" in WUXGA resolution. Ideal for modern workplaces, its 21:9 aspect ratio is optimized for Microsoft Teams Rooms applications, enhancing collaborative environments. Equipped with features like H/V lens shift, 1.6x optical zoom, H/V keystone correction, and 360° projection capabilities, the LSC601WU offers flexible setup possibilities. Additionally, its comprehensive LAN control ensures seamless integration into existing device management networks.

1. Zoom Ring 2. Focus Ring 3. Front IR 4. Rear IR 5. RJ45 6. Service 7. USB-A (5V/2A) 8. HDMI x2 9. Computer 10. HDBaseT 11. Monitor Out 12. Audio Out 13. Audio In 14. RS232 15. AC In 16. LED Indicator 17. Keypad 18. Lens Shift Control Knob x2

Visit Us

www.viewsonic.com

SPECIFICATION

Audio-in (3.5mm):

Audio-out (3.5mm):

USB Type A (Power):

RS232 (DB 9-pin male):

USB Type B (Services):

RJ45 (LAN control):

USB Type A:

HDBaseT:

OUTPUT Monitor out:

Speaker:

CONTROL

1

1

1

1

1

1

1

16W

1 (USB2.0 - 5V/2A, share with USB A Input)

1 (5V/2A)

SPECIFICATION		OTHERS	
Projection System:	3LCD (3x0.64" with MLA)	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz
Native Resolution:	1920x1200		(AC in)
Brightness:	6000 (ANSI Lumens)	Power Consumption:	Normal: 330W Standby: <0.5W
Brightness (Center Lumens):	6500	Operating Temperature:	0~40°C
Contrast Ratio:	300000:1	Carton:	Brown
Display Color:	1.07 Billion Colors	Net Weight:	7.9kg
Light Source Type:	Laser Phosphor	Gross Weight:	10.93kg
Light Source Life (hours) with Normal Mode:	20000	Dimensions (WxDxH) with Adjustment Foot:	405x358x137mm
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	Packing Dimensions:	510x498x260mm
Lens:	F=1.58-2.02, f=15.3-24.6mm	Po Si OSD Language: Ko Da	English, German, French, Italian, Spanish, Polish, Swedish, Dutch ,Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese,Thai, Farsi, total 25 languages
Projection Offset:	0%+/-5%		
Throw Ratio:	1.08-1.76		
Optical Zoom:	1.6X	English, S-Chinese, T-Chinese, Indonesian,	
Digital Zoom:	1.0x-4.0x	Finish, Frei User Guide Language: Korean, Po Spanish, S	Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian,
Image Size:	30"-300"		Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
Throw Distance:	0.70-11.37m (100"@2.33m)	STANDARD ACCESSORY	mai, vietnamese, total zo languages
Keystone:	H:+/-30° , V:+/-30°	Power Cord:	1
Lens Shift V. Range:	+45%, 0%	Remote Control:	1
Lens Shift H. Range:	+21%, -21%	QSG:	Yes
Audible Noise (Normal):	35dB	Air Filter:	Yes
Audible Noise (Eco):	25dB	Warranty Card:	Yes (CN Only)
Input Lag:	60ms	OPTIONAL ACCESSORY	
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)	Air Filter:	Yes
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p	Wall/Ceiling Mount:	PJ-WMK-007
Horizontal Frequency:	15K-100KHz		
Vertical Scan Rate:	23-85Hz		
INPUT			
Computer in (share with component):	1		
HDMI:	2 (HDMI 1.4/ HDCP 1.4)		