

Vero B8 Serie

Vero B278UGbemiqprcuzx

The Professional Business Monitor

The Acer B8 series embodies all the characteristics that a professional workstation monitor must have. From the design, which blends seamlessly into any working environment, to the ergonomic adjustment options and the variety of connections - the B8 series sets standards. The integrated brightness sensor automatically adjusts the brightness to the ambient light level as required. A proximity sensor recognises when the user has moved away from the display and switches to power saving mode after a short time to save electricity costs. When the user returns, the display switches back on automatically. Thanks to the optional USB Type-C docking solution, you can also control all peripherals (including Ethernet) via just one cable.



- Diagonal size: 68.6 cm (27.0 inches)
- Response time: 4ms(GTG)
- Brightness: 350 cd/m²
- Signal input: 1x HDMI, 1xDP(1.2) + 1xDPOut, (1x Type-C with 100W charging power), USB 3.2 x3 (2up 3down), Audio Out, 1x RJ45 + Adj. Webcam 5M IR/Mic array















Vero B278UGbemiqprcuzx

SPECIFICATIONS







Technical Specifications

Chassis colour

68.6 cm (27.0 inches) Diagonal size 597x336 mm Active display area (WxH) Aspect ratio 16:9 Resolution 2560x1440 IPS Technology Panel type Response time 4ms(GTG) Brightness 350 cd/m² Backlight type LED

Acer CrystalBrite No, anti-reflective display Viewing angle (h/v) CR>10:1 178/178°

Static contrast ratio 1000:1 100M:1 Dynamic contrast ratio 16.7M Colors Colour space 99% sRGB Speaker 2 x 2 watts

Signal input 1x HDMI, 1xDP(1.2) + 1xDPOut, (1x Type-C with 100W charging power), USB 3.2 x3 (2up 3down), Audio Out, 1x RJ45 + Adj. Webcam

5M IR/Mic array

(1x Type-C with 100W charging power) USB Type-C

Black

HDMI:31~177.6KHz / 48~120Hz, Frequency (H/V) DP:31~177.6KHz / 48~120Hz

Refresh rate (max.) 1x (HDMI 2.0) DisplayPort 1xDP(1.2) + 1xDPOut

VGA USB 3.1 Type-C Yes USB Hub Yes

1x RJ45 + Adj. Webcam 5M IR/Mic array Additional ports

Power supply and consumption

Power supply Internal EPREL No. tbd Energy Efficiency Class

21 kWh/1000h On-mode Power Standby mode Power 0,5 W Off mode Power 0,3 W

-5°~35° Tilt angle +/-60° Swivel angle 165 mm Height adjust range Pivot function +/-90° VESA wall mounting 100x100 mm

Norms and Standards

Warranty 36 months Carry In Certification TCO Edge, Win 10 compliant, EnergyStar

FPFAT FPFAT Gold 30 000 hrs. at 25°C MTRE

Dimensions and weight

Dimension w/o stand (W \times H \times D)

Weight (unpacked) 5,65 kg Package Dimensions 69.40x51.40x14 Weight (packed) 9,33 kg Weight w/o stand 3,49 kg

48 Pcs (128x114x219.60 cm) Pallet qty and size ($H \times W \times D$)

Container qty (20'/40') 576 / 1,224

Others

PCR 85% + OBP 5% PCR / OBP

Kensington Security Slot Yes

Ordering Information

Vero B278UGbemiqprcuzx Model Product line **B8** Series Part number UM.HB8EE.G01 EAN 4711474360878

Special features

Special features Acer VisionCare Yes KVM Switch Yes Acer Display Widget Yes

HDR Support HDR Ready (HDR 10)

This data sheet is subject to change without notice. Availability may vary from region to region. Acer is not liable for any errors or omissions contained in the product descriptions. In addition to the standard warranty conditions, the statutory warranty regulations also apply to consumers. For more information on exclusions and limitations, please refer to our warranty conditions for the respective product. If the warranty period in the PDF document for the warranty conditions differs from the information on the Acer homepage, the information given on this website applies and not the information contained in the PDF. Copyright 2024 Acer, Inc. all rights reserved. Acer and the Acer logo are registered trademarks of Acer Incorporated. All other trademarks, registered trademarks and/or service marks mentioned or otherwise recognizable are the property of their respective owners. All prices quoted are manufacturer's suggested retail prices.