

# Vero B7-Serie

# Vero B227QEbmiprzxv

Environmentally friendly in everyday business

The Vero B7 series impresses with a unique design paired with all the features that a modern business monitor must have. The ZeroFrame design convinces all along the line and enables a seamless multi-monitor setup without disturbing frames. Thanks to the flexibly adjustable Ergo-Stand, the monitors of the B7 series can be adjusted in height and rotated by 90° (pivot function) - all in the name of ergonomics. This series is ENERGY STAR®, TCO and EPEAT certified, reflecting Acer's commitment to environmental protection. It is made of up to 85% post-consumer recycled (PCR) plastic, up to 5% OBP (Ocean Bound Plastic) and uses 100% recyclable packaging.



- Diagonal size: 54.6 cm (21.5 inches)
- Resolution: 1920x1080
- Response time: 4ms(GTG)
- Brightness: 250 cd/m<sup>2</sup>
- Signal input: 1x VGA, 1x HDMI (1.4), 1x DP, USB 3.2 Hub (4x USB A + 1x USB-B), Audio In/Out











## Vero B227QEbmiprzxv

### SPECIFICATIONS



#### **Technical Specifications**

Diagonal size Active display area (WxH) Aspect ratio Resolution Panel type Response time Brightness Backlight type Acer CrystalBrite Viewing angle (h/v) CR>10:1 Viewing angle (h/v) CR>5:1 Static contrast ratio Dynamic contrast ratio Colors Colour space Speaker Signal input

Chassis colour Frequency (H/V)

Refresh rate (max.) HDMI DisplayPort VGA DVI USB 3.1 Type-C USB Hub Audio

#### Power supply and consumption

Power supply Energy Efficiency Class On-mode Power Standby mode Power Off mode Power Internal E 15 kWh/1000h 0,5 W 0,3 W

-5°~35°

+/-45°

150 mm +/-90°

100x100 mm

#### ErgoStand

Tilt angle Swivel angle Height adjust range Pivot function VESA wall mounting 54.6 cm (21.5 inches) 476x268 mm 0,672916667 1920x1080 IPS Technology 4ms(GTG) 250 cd/m<sup>2</sup> LED No, anti-reflective display 178/178° 178/178° 41,66736111 100M:1 16.7M 72% NTSC 2 x 2 watts 1x VGA, 1x HDMI (1.4), 1x DP, USB 3.2 Hub (4x USB A + 1x USB-B), Audio In/Out Black (PCR 85% + OBP 5%) VGA:30-85KHz / 48-75Hz, HDMI:30-125KHz / 48-100Hz, DP:125-125KHz / 48-100Hz 100Hz HDMI/DP, 75Hz VGA 1x HDMI (1.4) 1x (DP 1.2) Yes USB 3.2 Hub (4x USB A + 1x USB-B) 1x

#### Norms and Standards

Warranty Certification MTBF

#### Dimensions and weight

Dimension (W x H x D) Dimension w/o stand (W x H x D) Weight (unpacked) Package Dimensions Weight (packed) Weight w/o stand Pallet qty and size (H x W x D) Container qty (20'/40')

# Others

OSD languages Operating ambient temperature Operating ambient humidity Storage ambient temperature Kensington Security Slot

#### Ordering Information

Model Product line Part number EAN

Special features

Special features Acer VisionCare Acer Display Widget Sync technology

Vero B227QEbmiprzxv

36 months Carry In

30,000 hrs. at 25°C

490x295x66 90 mm

54.20x48.10x17

5,50 kg

7,09 kg

3,14 kg

520/1,144

5°C bis 35°C

10% bis 85%

-20°C to 60°C

**B7** Series

UM.WB7EE.E06

4711121737794

Yes

TCO, Win 10 compliant, EnergyStar

489.80x357.90~507.90x2.178 mm

52 Pcs (107x107x223.90 cm)

EN, DE, ES, NL, FR, IT, FI, RU, P, CN, PL

Yes Yes FreeSync

This data sheet is subject to change without notice. Availability may vary from region to region. Acer is not liable for any errors or omissions contained in the product descriptions. In addition to the standard warranty conditions, the statutory warranty regulations also apply to consumers. For more information on exclusions and limitations, please refer to our warranty conditions for the respective product. If the warranty period in the PDF document for the warranty conditions differs from the information on the Acer homepage, the information given on this website applies and not the information contained in the PDF. Copyright 2024 Acer, Inc. all rights reserved. Acer and the Acer logo are registered trademarks of Acer Incorporated. All other trademarks, registered trademarks and/or service marks mentioned or otherwise recognizable are the property of their respective owners. All prices quoted are manufacturer's suggested retail prices.

Page 2 of 2