

Are you ready?

With Ace, precision meets dedication. Achieve finesse in every shot with fast counterbalance, and smooth drag adjustments. Lightweight and sturdy, with consistent performance, Ace is along for the journey. From urban jungles to the call of the wild, be ready for every opportunity that comes your way.

Payload

Weight

Counterbalance

Drag

Temperature Range

Tilt Range

Camera plate

Sliding range

Pan bar

Leveling

0 - 4 kg / 0 - 8.8 lbs

 $1.7 \, kg \, / \, 3.7 \, lbs$

5 steps + 0

3 steps vertical and 3 horizontal, $+\ 0$

 -30° to $+60^{\circ}$ C / -22° to $+140^{\circ}$ F

+90° to -75°

Ace plate (slide in)

104 mm / 4.1 in

1, fixed, Type Ace

level bubble



Payload 0-8 kg / 0-17.6 lbs

Weight 1.7 kg / 3.7 lbs

Counterbalance 9 steps + 0

Drag 3 steps vertical and 3 horizontal, + 0

Temperature Range -30° to +60°C / -22° to +140°F

Tilt Range +90° to -75°

Camera plate Ace plate (slide in)

Sliding range 104 mm / 4.1 in

Pan bar 1, fixed, Type Ace

Leveling illuminated level bubble





System Specifications

Ace M MS Mk II Ace M GS Mk II Ace XL MS AL Mk II Ace XL GS AL Mk II 1001M 1002M 1018AM 1019AM Code 0 to 8 kg / 0 - 17.6 lbs 0 to 8 kg / 0 - 17.6 lbs **Payload** 0 to 4 kg / 0 - 8.8 lbs 0 to 4 kg / 0 - 8.8 lbs Mid-level spreader Ground spreader Spreader Mid-level spreader Ground spreader **Tripod Material** Aluminium Aluminium Aluminium Aluminium 87 cm / 34.3 in 86 cm / 33.9 in 87 cm / 34.3 in **Transport Length** 86 cm / 33.9 in 78 - 169 cm / 58 - 173 cm / 78 - 169 cm / 58 - 173 cm / Height (min to max) 30.7 - 66.5 in 22.8 - 68.1 in 30.7 - 66.5 in 22.8 - 68.1 in 4.5 kg / 9.9 lbs 4.4 kg / 9.7 lbs 4.5 kg / 9.9 lbs Weight 4.4 kg / 9.7 lbs

