



MICROFLEX[®] MXP-6 PENDANT CONFERENCING LOUDSPEAKER

OVERVIEW

Pendant-style passive loudspeaker for speech and program audio reproduction in meeting rooms. Microflex Conferencing Loudspeakers are designed for conferencing with clear, intelligible audio.

FEATURES

- Dual-driver architecture delivers full-fidelity, premium audio reproduction and optimum speech intelligibility
- 4-inch main driver features large, well-vented motor for increased power handling; 1-inch tweeter features neodymium magnet and heatsink fins for high efficiency
- Identical voicing to MXP-5 Ceiling Loudspeaker for consistent tonality in blended installations
- Up to 8 MXP-6 loudspeakers can be used with the MXN-AMP PoE+ multichannel amplifier in 70/100V mode
- Rear switch allows for quick adjustment between 70/100v transformer or 8 ohm operation
- Utilize multiple pendants to easily meet the audio coverage needs of almost any room size
- Sleek industrial design available in white or black finish, paintable to match room décor
- Seamless connectivity and compatibility with popular collaboration platforms, including Microsoft Teams and Zoom

SPECIFICATIONS

(subject to change) All specifications are within ± 3 dB unless otherwise noted.

Frequency Response (-3 dB)	90Hz – 20kHz
Nominal Impedance	4 Ω
Coverage Angle	95°
Maximum SPL	AES75 max linear sound levels: 98 dBz, 113 dbZpk, 97 dBA
Sensitivity	93 db SPL
Connector Type	4-pin connector, 0.2 in. (5.08 mm) pitch
Maximum Input Power	28W
Weight	5.5 lbs (2.5 kg)
Product Dimensions	11 x 9 x 9 in. (279 x 230 x 230 mm)
Operating Temperature Range	-7 to 40°C (19.4 to 104°F)



MXP-6B
Pendant Conferencing Loudspeaker
BLACK



MXP-6W
Pendant Conferencing Loudspeaker
WHITE