

Key Features

- 3,700 ANSI Lumens offering bright images in any environment
- 1080p Full HD resolution for captivating visuals
- Unveil hidden details with a high native contrast ratio achieved through the 0.65" DMD chip
- Up to 300" screen size to maximize fun at home
- Easy multimedia access via dual HDMI ports and USB-A power supply



Product **Description**

Visit Us

www.viewsonic.com

SPECIFICATION		OTHERS	
Projection System:	0.65" 1080p	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz
Native Resolution:	1920x1080		(AC in)
Brightness:	3700 (ANSI Lumens)	Power Consumption:	Normal: 300W Standby: <0.5W
Contrast Ratio with SuperEco Mode:	22000:1	Operating Temperature:	0~40°C
Contrast Ratio:	15,000:1	Carton:	Brown
Display Color:	1.07 Billion Colors	Net Weight:	2.4kg
Light Source Type:	203W UHP Lamp	Gross Weight:	3.5kg
Light Source Life (hours) with Normal Mode:	6000	Dimensions (WxDxH) with Adjustment Foot:	293x221x115mm
Light Source Life (hours) with SuperEco Mode:	20000	Packing Dimensions: OSD Language:	365x300x188mm English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S- Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Hindi, Arabic, Vietnamese, Greek, Hungary,
Lens:	F=2.56-2.68, f=22-24.1mm		
Projection Offset:	116%+/-5%		
Throw Ratio:	1.49-1.64		
Optical Zoom:	1.1x		
Digital Zoom:	0.8x-2.0x		Total 24 languages
Image Size:	30"-300"	User Guide Language:	English, S-Chinese, Finnish, French, German, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Czech, Total 13 languages
Throw Distance:	1m-10.96m (100"@3.32m)		
Keystone:	+/- 40° (V)	STANDARD ACCESSORY	
Audible Noise (Normal):	31dB	Power Cord:	1
Audible Noise (Eco):	27dB	Remote Control:	1
Input Lag:	16ms	QSG:	Yes
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking	Warranty Card:	Yes (CN Only)
		OPTIONAL ACCESSORY	
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	Lamp/Light Source:	RLC-131
TIDT V Compatibility.		Wall/Ceiling Mount:	PJ-WMK-007
Horizontal Frequency:	15K-102KHz	Carry Bag:	PJ-CASE-008
Vertical Scan Rate:	23-120Hz		
INPUT			
HDMI:	2 (HDMI 1.4/ HDCP 1.4)		
Ουτρυτ			
Audio-out (3.5mm):	1		
Speaker:	10W	_	
USB Type A (Power):	1 (5V/1.5A)		

RS232 (DB 9-pin male): USB Type A (Services):

CONTROL

1 (share with USB A Output)

1