



BenQ DLP Projector		MX560C
Feature HighLight		
* 4000 ANSI Lumen		
* XGA Lamp light source		
* BenQ SmartEco Energy Conservation		
* 20,000:1 High contrast		
Display		
Projection System	DLP Single 0.55" XGA	
Native Resolution	1024 x 768 pixels	
Brightness	4000 ANSI Lumens	
Contrast Ratio*	20,000:1	
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)	
Light Source	Lamp	
Picture mode	Presentation / Infographic /Spreadsheet	
Light Source life*	Normal mode: Typical 6,000 hours Eco mode: Typical 10,000 hours LampSave: 15000 hours	
Optical		
Throw Ratio	1.96-2.15	
Zoom Ratio	1.1x	
Lens shift	NA	
Keystone Adjustment	1D, +/- 30 degrees (V only)	
Projection Offset	110% (Mode B)± 2.5%	
Projection Size	60" ~ 150"	
Audio		
Built-in Speaker	10W	
Special Feature		
Security(防盜為主)	Security Bar,Kensington lock	
Compatibility		
Resolution Support	VGA(640 x 480) to WUXGA (1920x1200)	
Horizontal Frequency	15K~102KHz	
Vertical Scan Rate	23~120Hz	
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
Video Compatibility	NA	
Power		
Typical Power Consumption (100V)	270W	
Standby Power Comsumption	Normal < 0.5Watts.	
Power Supply	AC 100 to 240 V, 50/60 Hz	
Dimension and Weight		
Product Dimensions (WxHxD)	296 (W) x 221 (D)x 129 (H) mm	
Product Weight	2.3 kg	
Operation Condition		
Noise Level(Normal/Eco)	34/29dBA	
Operating Temperature	0 ~ 40°C	
Accessories		
Accessories (Standard)	Remote control Power Cord x 1 (1.8m) (by region) Warranty Card (by region) QSG User Manual E-edition	
Accessories (Optional)	Ceiling mount Carry bag	
OSD		
On Screen Display Language	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnamese (30 Languages)	
Environment Notice		
*LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.		
* The Contrast is measure by Full On Full Off standard.		



Connectivity

	Quantity
1 HDMI 1.4	1
2 RS232 In (D-sub 9pin, male)	1
3 USB (Type A)	1
4 Audio in/out	1/1
5 USB (Mini B)	1
6 Speaker (10W)	1
7 VGA in	1
8 IR Receiver (Front)	1

Dimension (mm)

