DATA SHEET

EASYCONNECT MPX 250 BYOM COLLABORATION SWITCHER



EasyConnect MPX 250 is an innovative BYOM collaboration switcher with integrated charging, cable management and control of the meeting room equipment.

Simply plug in the USB-C cable to your device and press a button to start sharing, get internet access, and take control of room equipment such as camera, speakers and microphones. Enjoy meetings with reliable connection, fully powered laptops and a clutter free table.

VIVID AND HELPFUL COLORS

Bright and vivid colors guide you during the meeting. In combination with the touch controller it allows the connected participant to control and switch who is sharing their screen and has control of the connected inroom equipment such as cameras, microphones and speakers.



Idle



Charging



Sharing



HDMI Ingest

ARCHITECTS & ENGINEERS SPECIFICATION

The BYOM collaboration switcher shall be designed with a touch panel to control screen sharing. The BYOM collaboration switcher shall allow meeting participants to control and switch who is sharing their screen. The BYOM collaboration switcher shall have a touch control. The BYOM collaboration switcher shall indicate screen sharing with LED indicators on the touch display. The BYOM collaboration switcher shall include four USB-C cables for connections to laptops and mobile devices. The BYOM collaboration switcher shall include cable management with retractable USB-C cables. The BYOM collaboration switcher shall charge connected devices up to 100W. The BYOM collaboration switcher shall support dual video output and network sharing. The BYOM collaboration switcher shall be CE marked and compliant with the RoHS directive. Warranty shall be three years. The BYOM collaboration switcher shall be the EasyConnect MPX 250.



PLATFORM OF YOUR CHOICE

EasyConnect MPX 250 gives you a smooth and seamless setup for all your meetings. No matter what video conferencing platform the experience will be hassle free, with the benefit of increased productivity. Connect to any of the most popular video conference platforms such as Microsoft Teams, Zoom and Google Meet. It is also possible to connect to other wireless screen sharing systems for a hybrid setup.



ONE CABLE. THAT'S IT.

Dual Screen Support

Enhanced connectivity with dual video output



Shared Internet Connection

Network connectivity through USB-C



Charge your devices

Connected devices are charged with up to 100W.



Cable Management

Retractable USB-C cables with integrated retention mechanism



Plug and play

No software installation needed.

SHARE IN SECONDS

Easily share your screen and audio in a meeting with full control of room equipment such as camera, speakers and microphones. All with the touch of your fingertip.



PRODUCT SPECIFICATIONS

Connectivity & Ports

USB-C Input Ports 4 x USB Type-C 3.2 Gen 2, up to 10 Gbps,

DP Alt Mode 1.2-1.4, up to 100W

USB-C Downstream Ports 2 x USB 3.2 Gen 2, up to 10 Gbps,

5V / 3A, Power Delivery 3.0

USB-A Ports 2 x USB 3.2 Gen 2, up to 10 Gbps, 5V / 0.9A

HDMI Output HDMI 2.1, max resolution 8K @ 60Hz

HDCP v2.3, FRL mode

Network RJ45 Port 1: 10/100 Mbps Ethernet (Management)
RJ45 Port 2: 10/100/1000 Mbps Ethernet (Internet Sharing)

Wi-Fi 2.4 GHz Wi-Fi for MPX 250 Management Console

Extension Port USB-C Extension Port: DP Alt Mode 1.4,

up to 4 x 8.1 Gbps, video output

DC IN 20V / 10A power supply input

Touch Controller & Cable Management

Cable Length 4 x 2-meter retractable USB-C cables

Cable Extension Up to 80 cm above tabletop

Integrated guide rails

Touch Interface Capacitive touch buttons for each port

with LED status indicators

Status Indicators Visual LED indicators

(idle, connected, sharing, BYOM mode)

Installation Pre-mounted table installation

with integrated retractable system

Supported Configurations

BYOD/BYOM Setup

Full bring-your-own-device/meeting support

UC Integration

Microsoft Teams, Zoom, Google Meet

Dual Display

Video extension and dual output support via MST hub

(Windows: extended, macOS: mirrored)

Mode Switching Long press switching between

HDMI-ingest (MTR) and BYOM modes

Environmental

Temperature Range: $5^{\circ}-40^{\circ}$ C Humidity: 5%-80%

Compliance: CE, FCC, ETL, RoHS, REACH

MPX 250 TABLE CONNECTION BOX:





INCLUDED WITH THE SYSTEM:

- MPX 250 Table Connection box with touch controller and mounting brackets for under-table installation
- Power adapter with 1-meter AC cord
- Mounting system with retractable cable management
- · 4x USB-C cables with cable weights
- Management console software (PC & Mac)

OPTIONAL ACCESSORIES:



MPX 250 DC
MPX Direct Connection Hub



MPX 250 EXT 30 Wall Side Extension Kit

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice.

Biamp and EasyConnect MPX 250 are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.

