

DATA SHEET

VIDI CONTENT CAM 250

4K CONFERENCING WHITEBOARD CAMERA KIT



The Vidi Content Cam 250 is a specialized 4K content camera designed to digitize and share in-room whiteboard content with remote meeting participants. Leveraging a Microsoft Teams Room feature, the Vidi Content Cam 250 provides keystone correction and translucent layering technology that ensures remote participants always have a clear view of whiteboard content, even when presenters are actively writing. The solution offers installation flexibility, with wall mounting options for 6-8 foot whiteboards and ceiling mounting for whiteboards up to 12 feet. Built on the proven Vidi 250 camera platform and including a 50 foot USB extension cable, the Vidi Content Cam 250 integrates with the existing Biamp TSC compute solutions.

FEATURES

- LED indications for camera activity
- Wide angle 120° Field of View
- Auto framing technology to keep participants in frame
- Electronic Pan/Tilt/Zoom with 5x zoom
- Multi-microphone array
- Wall and ceiling mount options included
- Extender for wider camera angle included
- Compatible with Microsoft Teams
- Captures whiteboard content up to 12ft.
- Covered by a Biamp three year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The conferencing camera shall be designed to connect with soft codec conferencing systems. The conferencing camera shall be capable of transmitting video signals of up to 1080p resolution at 30 frames per second. The conferencing camera shall have a 120° field-of-view. The conferencing camera shall include a camera with 5x zoom and electronic pan, tilt, and zoom (ePTZ). The conferencing camera shall include auto framing capabilities that adjusts the ePTZ to intelligently track users. The conferencing camera shall offer simple installation and shall be mountable on a wall or display. The conferencing camera shall be CE marked and compliant with the RoHS directive. Warranty shall be three years. The conferencing camera shall be the Vidi 250.

VIDI 250 SPECIFICATIONS

Camera and Video		Overall Dimensions	
Diagonal Field of View:	120 Degrees	Height:	1.98 inches (50.3 mm)
Horizontal Field of View:	109 Degrees	Width:	1.97 inches (50 mm)
Vertical Field of View:	75 Degrees	Depth:	2.76 inches (70 mm)
Image Sensor:	12 Megapixel	Weight:	160g
Focus Distance:	174.1 cm	Environmental:	
Lens:	Up to 5x digital zoom	Ambient Operating:	0°C - 40°C
Positioning:	Autoframing capability	Temperature Range:	0°C - 40°C
Camera Indicator:	Electronic Pan/Tilt/Zoom	Humidity:	0% - 95%
	White/Off	Altitude:	10,000 ft
USB Device Video Class (UVC)		Compliance:	CE, UKCA
Supported Video Resolutions:	720p @ 30fps 1080i @ 30fps 1080p @ 30fps 2160p @ 30fps		
Connections			
USB:	USB Type C		
Power:	USB Type C		

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice.

OPTIONAL ACCESSORIES



TB-1
Tile Bridge

Biamp is either a trademark or registered trademark of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.