

DATA SHEET

EASYCONNECT MPX 250 DC

MULTI-UNIT DIRECT CONNECTION HUB



The EasyConnect MPX 250 DC is designed to connect multiple MPX 250 units through distributed connectivity. This comprehensive solution includes everything needed to deploy MPX 250 functionality with seamless expansion capabilities for growing meeting room requirements. The hub provides a cost-effective way to implement MPX 250 technology with built-in scalability for future room modifications and AV system expansions.

FEATURES

- MPX 250 DC connection hub, power supply, and USB-C cables for immediate deployment
 - Multi-unit support enables seamless expansion with up to four MPX 250 units as room requirements grow
- Designed for growth with expandable connectivity that adapts to changing meeting room needs and AV requirements, enabling up to 16 connected devices

PRODUCT SPECIFICATIONS

Expansion Support	Seamless connection with up to 4 MPX 250 units for scalable AV setups	Network Sharing	Internet connectivity shared across all connected MPX 250 units
Video Distribution	Dual display support with MST hub (Windows: extended, macOS: mirrored)	Power Management	Intelligent power distribution with up to 100W per unit capability
USB Pass-Through	Full USB-A and USB-C device connectivity across connected units	Cloud Management	Unified remote management and monitoring with Biamp Workplace*

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice.

* coming soon

ARCHITECTS & ENGINEERS SPECIFICATIONS

The table side multi-unit direct connection hub shall be designed for multi-unit connectivity and scalable AV deployments. The direct connection hub shall include one (1) connection hub, one (1) dedicated power supply, and four (4) USB-C to USB-C connection cables. The system shall support seamless expansion through built-in multi-unit capabilities via USB-C extension ports, connecting up to 4 MPX 250 units and 16 connected devices. The system shall support dual video output up to 8K@60Hz resolution and network connectivity sharing across connected units. All components shall be CE marked and RoHS compliant with 3-year warranty coverage. The direct connection hub shall be EasyConnect MPX 250 DC.

DIRECT CONNECTION HUB BACK PANEL:



INCLUDED WITH THE SYSTEM:

- 1x Table Side Multi-Unit Direct Connection Hub
- 1x Power supply (20V DC, 10A, 200W)
- 4x USB-C to USB-C cables (6.6 feet / 2 meters each)

Note: Used together with EasyConnect MPX 250 (sold separately)

Biamp, EasyConnect, MPX 250, and MPX 250 DC are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. HDMI, HDMI High-Definition multimedia Interface, and the HDMI logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.