

IN2006UT

Ultra-short throw WXGA 3LCD projector



Experience the power of big-screen viewing regardless of your room size. The InFocus IN2006UT is an ultra short throw WXGA projector that delivers large, vivid images from just inches away from your wall, bringing large screen experience to spaces where traditional projectors simply can't fit. With no disruptive shadows or glare to distract, content stays the center of attention – whether in classrooms, lecture halls, or meeting spaces.

Easy to install and seamlessly integrated into different environments, it combines space efficiency with outstanding visual performance, proving big impact doesn't require big installations.

Big Visuals, Minimal Space

With IN2006UT, you can create an expansive 100" image with placement less than a meter from the screen. Whether it's a classroom, or corporate space, you can transform any space into an immersive viewing or presentation environment.

Flexible Projection

Equipped with 360-degree orientation capability, the InFocus IN2006UT adapts seamlessly to ceilings, walls, floors, or angled surfaces without sacrificing image quality. Whether placed on a tabletop or mounted overhead, it delivers consistent performance. With four-corner correction, each corner of the image can be precisely adjusted to achieve a perfectly square picture, even on uneven surfaces.

Uninterrupted, Glare-Free Viewing Experience

The ultra short throw design keeps the projection path safely out of the way without casting shadows that block the image. With the light source positioned close to the screen, presenters and viewers do not have to worry bright light shining directly toward their eyes. The result is a clear, comfortable viewing experience for both presenters and audiences.

Immersive Visuals Bright and Sharp

With the projector placed closer to the wall, every image is delivered with exceptional brightness and sharpness, minimizing light loss and distortion. Colors remain vivid and lifelike, while fine details appear crystal-clear across the entire screen. Even in well-lit classrooms, lecture halls, or meeting spaces, presentations maintain their impact with consistent, high-quality visuals.

IN2006UT

IMAGE

Projection Technology	3LCD
Chip/Panel Size	0.59" x 3
Native Resolution	WXGA, 1280 x 800
Aspect Ratio	16:10
Contrast Ratio	5,000,000:1
Brightness (lumens)	3,800
Light Source	Quantum Laser
Light Source Lifespan (max)	30,000 hours
Horizontal Sync. Range (KHz)	15 ~ 100
Vertical Sync. Range (Hz)	24 ~ 85
Uniformity (%)	80
Vertical Sync. Range (Hz)	24~85



POWER

Power Supply	AC 100-240V~ 50 / 60 Hz
Power Consumption Max (Normal/Eco1/Eco2)	260W/170W/150W
Standby Power Consumption (W)	<0.5

OPTICAL

Lens	1.7
Throw Ratio	0.254:1
f	2.94
Focus/Zoom Adjustment	Manual
Vertical Keystone Correction	± 5°
Horizontal Keystone Correction	± 5°

CONNECTIVITY

Input	VGA, 2 x HDMI™, USB-A, USB-B, 3.5mm mini-jack, RJ45
Output	VGA, 3.5mm mini-jack
Control	RS232

GENERAL

Dimensions (WxDxH) (mm/in)	470x410x166 / 18.5x16.1x6.5
Product Weight (kg/lb)	8.5/18.7
Fan Noise (Normal/Eco1/Eco2)	37dB / 30dB / 28dB
Audio (w)	16
Operating Temperature (C/F)	0°~40° /32° ~104°
Operating Humidity (%)	20-80
Max. Operating Altitude (m/ft)	≤3,000 / 9,843
Storage Temperature (C/F)	-10°~50° / 14°~122°
Storage Humidity (%)	10 -85
Shipping Dimensions (WxDxH) (mm/in)	612x533x274 / 24.1x21x10.8
Shipping Weight (kg/lb)	11 / 24.3
Safety and Regulatory	CCC, CB, cTUVus, FCC, FDA, CE-EMC, CE-LVD, CE-ERP, PSB
In the Box	Projector, Power Cord, Remote Control, Simplified User Guide*

