



Key Features

- 5,200 ANSI Lumens offering bright images in any environment
- Up to a 300" ultra-large screen with a lower cost-per-inch
- Supports a 21:9 aspect ratio, ideal for Microsoft Teams Rooms
- Installation flexibility: V lens shift, 1.6x optical zoom, and H/V keystone correction
- 3rd generation laser phosphor technology with a lifespan up to 30,000 hours



Product Description

The LSC521WU is a lamp-free, high-brightness projector designed for commercial, educational, and public spaces. Utilizing 3rd generation laser phosphor technology, this projector delivers 5,200 ANSI Lumens of brightness for up to 30,000 hours and can project an ultra-large screen up to 300" in WUXGA resolution. Ideal for modern workplaces, its 21:9 aspect ratio is optimized for Microsoft Teams Rooms applications, enhancing collaborative environments. Equipped with features like V lens shift, 1.6x optical zoom, H/V keystone correction, and 360° projection capabilities, the LSC521WU offers flexible setup possibilities. Additionally, its comprehensive LAN control ensures seamless integration into existing device management networks.

1. Zoom Ring	8. Audio Out	15. Audio In
2. Focus Ring	9. Computer	16. Monitor Out
3. Front IR	10. HDMI x2	17. RS232
4. AC In	11. Service	18. LED Indicator
5. HDBaseT	12. USB-A (5V/1.5A)	19. Keypad
6. Audio In(L)	13. RJ45	20. Power Button
7. Audio In(R)	14. Video	21. Lens Shift Control Knob

Visit Us

www.viewsonic.com

SPECIFICATION		OTHERS	
Projection System:	3LCD (3x0.64" with MLA)	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)
Native Resolution:	1920x1200	Power Consumption:	Normal: 240W Standby: <0.5W
Brightness:	5200 (ANSI Lumens)	Operating Temperature:	0~40°C
Brightness (Center Lumens):	6000	Carton:	Brown
Contrast Ratio:	3000000:1	Net Weight:	5.2kg
Display Color:	1.07 Billion Colors	Gross Weight:	7.23kg
Light Source Type:	Laser Phosphor	Dimensions (WxDxH) with Adjustment Foot:	390x294x128mm
Light Source Life (hours) with Normal Mode:	20000	Packing Dimensions:	492x443x239mm
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	OSD Language:	English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portuguese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese, Thai, Farsi, total 25 languages
Lens:	F=1.5-2.08, f=17.2-27.7mm	User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
Projection Offset:	0%+/-5%	STANDARD ACCESSORY	
Throw Ratio:	1.2-2.01	Power Cord:	1
Optical Zoom:	1.6X	Remote Control:	1
Digital Zoom:	1.0x-4.0x	QSG:	Yes
Image Size:	30"-300"	Air Filter:	Yes
Throw Distance:	0.78-12.99m (100"@2.58m)	Warranty Card:	Yes (CN Only)
Keystone:	H:+/-30°, V:+/-30°	OPTIONAL ACCESSORY	
Lens Shift V. Range:	+60%, 0%	Air Filter:	Yes
Audible Noise (Normal):	35dB	Wall/Ceiling Mount:	PJ-WMK-007
Audible Noise (Eco):	26dB		
Input Lag:	60ms		
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160@30Hz)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p@30Hz		
Horizontal Frequency:	15K-100KHz		
Vertical Scan Rate:	23-85Hz		
INPUT			
Computer in (share with component):	1		
Composite:	1		
HDMI:	2 (HDMI 1.4/ HDCP 1.4)		
Audio-in (3.5mm):	1		
Audio-in (RCA R/L):	1		
USB Type A:	1 (5V/1.5A)		
HDBaseT:	1		
OUTPUT			
Monitor out:	1		
Audio-out (3.5mm):	1		
Speaker:	16W		
USB Type A (Power):	1 (USB2.0 - 5V/1.5A, share with USB A Input)		
CONTROL			
RS232 (DB 9-pin male):	1		
RJ45 (LAN control):	1		
USB Type B (Services):	1		