

DALI SONIK

TECHNICAL SPECIFICATIONS

	SONIK 1	SONIK 3	SONIK 5	SONIK 7	SONIK 9	SONIK ON-WALL	SONIK CINEMA
Frequency range	51 - 26,000 Hz ±3 dB	47 - 26,000 Hz ±3 dB	39 - 26,000 Hz ±3 dB	36 - 30,000 Hz ±3 dB	34 - 30,000 Hz ±3 dB	55 - 26,000 Hz ±3 dB	46 - 26,000 Hz ±3 dB
Sensitivity	86 dB @ 1 m for 2.83 V	87 dB @ 1 m for 2.83 V	88 dB @ 1 m for 2.83 V	88.5 dB @ 1 m for 2.83 V	90 dB @ 1 m for 2.83 V	87 dB @ 1 m for 2.83 V	89,5 dB @ 1 m for 2.83 V
Nominal impedance	6 ohm	6 ohm	6 ohm	6 ohm	4 ohm	6 ohm	6 ohm
Maximum SPL	106 dB	108 dB	108 dB	110 dB	111 dB	107 dB	109 dB
Crossover frequency	2,800 Hz	2,300 Hz	2,200 Hz	2,300 / 14,000 Hz	400 / 2,100 / 14,000 Hz	2,400 Hz	2,200 Hz
Crossover principle	2-way	2-way	2-way	2½-way	2½ + ½-way	2-way	2-way
Recommended amplifier power	25 - 100 Watt	25 - 150 Watt	30 - 150 Watt	30 - 180 Watt	50 - 300 Watt	25 - 100 Watt	25 - 150 Watt
High frequency driver(s)	1 × 29 mm low loss soft dome	1 × 29 mm low loss soft dome	1 × 29 mm low loss soft dome	17 × 45 mm planar magnetostatic tweeter 1 × 29 mm low loss soft dome	17 × 45 mm planar magnetostatic tweeter 1 × 29 mm low loss soft dome	1 × 29 mm low loss soft dome	1 × 29 mm low loss soft dome
High frequency diaphragm	Soft woven fabric	Soft woven fabric	Soft woven fabric	Planar magnetostatic Soft woven fabric	Planar magnetostatic Soft woven fabric	Soft woven fabric	Soft woven fabric
Low/Mid frequency driver(s)	1 × 5¼-inch	1 × 7-inch	2 × 5¼-inch	2 × 7-inch	3 × 7-inch	5¼-inch	2 × 5¼-inch
Low/Mid frequency diaphragm	Clarity Cone™ paper and wood fibre	Clarity Cone™ paper and wood fibre	Clarity Cone™ paper and wood fibre	Clarity Cone™ paper and wood fibre	Clarity Cone™ paper and wood fibre	Clarity Cone™ paper and wood fibre	Clarity Cone™ paper and wood fibre
Connection input(s)	Single wire	Single wire	Single wire	Single wire	Single wire	Single wire	Single wire
Enclosure type	Bass reflex	Bass reflex	Bass reflex	Bass reflex	Bass reflex	Bass reflex	Bass reflex
Bass reflex tuning frequency	51 Hz	46 Hz	43 Hz	39 Hz	35 Hz	50 Hz	46 Hz
Other features	Integrated wall bracket	N/A	N/A	N/A	N/A	LORS	LORS
Recommended placement	Stand/shelf	Stand/shelf	Floor	Floor	Floor	Wall	Stand/shelf
Recommended distance from rear wall	1 - 50 cm	5 - 50 cm	15 - 100 cm	20 - 100 cm	20 - 120 cm	0 - 10 cm	0 - 50 cm
Dimensions (H × W × D)	274 × 162 × 231 mm 10.8 × 6.4 × 9.1 inches	350 × 200 × 306 mm 13.7 × 7.8 × 12.1 inches	826 × 249 × 270 mm 32.5 × 9.8 × 10.6 inches	1,006 × 304 × 330 mm 39.6 × 12 × 13 inches	1,126 × 318 × 376 mm 44.3 × 12.5 × 14.8 inches	385 × 245 × 123 mm 15.2 × 9.7 × 4.8 inches	170 × 571 × 214 mm 6.7 × 22.5 × 18.4 inches
Weight incl. grille	4.1 kg 9.03 lb	6.5 kg 14.13 lb	10.8 kg 23.80 lb	16.2 kg 35.71 lb	24.6 kg 54.23 lb	4.9 kg 10.80 lb	7.90 kg 17.41 lb
Shipping weight	10 kg (pair) 22.04 lb (pair)	15.1 kg (pair) 33.28 lb (pair)	26.6 kg (pair) 58.64 lb (pair)	19.7 kg 43.43 lb	30.1 kg 66.35 lb	10.9 kg (pair) 24.03 lb (Pair)	9.6 kg 21.16 lb
Finishes	Black Ash White Walnut Natural Oak	Black Ash White Walnut Natural Oak	Black Ash White Walnut Natural Oak	Black Ash White Walnut Natural Oak	Black Ash White Walnut Natural Oak	Black Ash White Walnut Natural Oak	Black Ash White Walnut Natural Oak
Accessories (included)	Front grilles Rubber feet Rubber pads Document pack	Front grilles Rubber pads Document pack	Front grilles Rubber pads Spikes Lock nuts Hemispherical rubber feet Spike outriggers Spike outrigger screws Toolkit Document pack	Front grilles Rubber pads Spikes Lock nuts Hemispherical rubber feet Spike outriggers Spike outrigger screws Toolkit Document pack	Front grilles Rubber pads Spikes Lock nuts Hemispherical rubber feet Spike outriggers Spike outrigger screws Toolkit Document pack	Front grilles Rubber pads Document pack	Front grille Rubber pads Document pack

All technical specifications are subject to change without notice.