



kramer

WM-8P

8" Two-way Wall Mounted Passive Speaker

| Speakers



The WM-8P wall mounted passive speaker deliver exceptional sound performance for commercial indoor applications. The WM-8P is a high-end 8" wall mounted passive speaker featuring exceptional sound, optimized for conferencing and background music. The speaker supports both 8Ω low impedance as well as several 70V/100V high impedance modes. The speaker is supplied with Kramer's EasyMount mounting bracket for horizontal and vertical installations as well as for installation in corners, in addition the speaker has standard 75mm VESA mount threads for additional installation options. The speaker is available in both black & white colors

FEATURES

Exceptional sound performance

Low-impedance (8Ω) / high-impedance (70V/100V)

Power ratings: 60W continuous / 80W peak

Sensitivity (1W@1m, free field): 90dB SPL

Maximum SPL (@1m): Continuous 108dB SPL / Peak 109dB SPL

UL1480A certified

Industrial design: hidden wall-mount bracket for horizontal, vertical and corner installation, standard 75mm VESA mount threads, removable logo, available in black & white colors

Eco-friendly mono-material packaging

Included in the Box - 1 speaker (single unit), 2 speakers are packed in a single master box

1 EasyMount mounting bracket + 2 bracket screws

4-pin pluggable Euroblock connector, 28-12AWG

L-shaped Allen key (M6)

Quick Start Guide



kramer

TECHNICAL SPECIFICATIONS

DESCRIPTION:	Premium 8" two-way wall mounted passive speaker. Available in black & white colors
Audio	<p>Driver:</p> <p>LF Driver: 200 mm (8") with polypropylene cone and rubber surround</p> <p>HF Driver: 25 mm (1") liquid cooled soft-dome tweeter</p> <p>Frequency characteristics</p> <p>Frequency Range (-10dB): 60Hz-20kHz</p> <p>Frequency Response (± 3dB) 79Hz-20kHz</p> <p>Dispersion angle: 124 deg. (1 kHz to 4 kHz)</p> <p>Power ratings</p> <p>@ 8Ω Low impedance: 60W continuous / 80W peak</p> <p>@ 100 V High impedance: 60W/30W/15W</p> <p>@ 70 V High impedance: 60W/30W/15W/7.5W</p> <p>Sound Pressure Level (SPL)</p> <p>Sensitivity (1W@1m, free field) 90dB SPL</p> <p>Maximum SPL: Continuous: 108dB SPL / Peak: 109dB SPL</p>
Mechanisch	<p>Installation</p> <p>Type: Surface mounted vertical, horizontal or in corners</p> <p>Mounting: EasyMount bracket included, standard 75mm VESA mount threads</p> <p>Connectors: 4-pin pluggable Euroblock connector, 28-12AWG</p> <p>Weight per single speaker (including mounting bracket): 5.1kg (11.3lbs)</p> <p>Dimensions</p> <p>Dimensions without Bracket: 250mm x 222mm x 390mm / 9.9" x 8.8" / 15.4"</p> <p>Dimensions with Bracket: 250mm x 306mm x 390mm / 9.9" x 12.1" / 15.4"</p> <p>Shipping</p> <p>Packed as single, 2 single boxes are packed in a master box</p> <p>Shipping Dimensions (single unit): 422mm x 332mm x 480mm / 16.6" x 13.1" x 18.9"</p> <p>Shipping dimensions (2 units in a Master box): 670mm x 430mm x 498mm / 26.4" x 17" x 19.6"</p> <p>Shipping weight (single unit): 7kg / 15.5lbs</p> <p>Shipping weight (2 units in a Master box): 15Kg / 33lbs</p> <p>Packaging Eco-friendly mono-material packaging made entirely from recyclable carton, designed for durability and ease of recycling</p> <p>Material</p> <p>Grill: Powder Coated Steel, removable logo</p> <p>Baffle: V-0 Flame Retardant</p> <p>Bracket: Aluminium</p>

Environmental
Operating Temperature: -5° to +50°C (23° to 122°F)

Storage Temperature: -10° to +55°C (14° to 131°F)

Humidity: 30% to 85%, RHL non-condensing

Verordnung UL1480A Certified: Meets safety standards for fire-protective signaling in commercial spaces

Environmental
: RoHS, REACH, WEEE

In the Box
1 speaker (single unit), 2 speakers are packed in a single master box
1 EasyMount mounting bracket + 2 bracket screws
4-pin pluggable Euroblock connector, 28-12AWG
L-shaped Allen key (M6)
Quick Start Guide



kramer

CONFIGURATIONS

WM-8P-(W)-(SINGLE)

WM-8P-(B)-(SINGLE)
