

HZ41

Compact high brightness Full HD laser home projector



- **Bright 4400 lumens for lights on viewing - Full HD 1080p laser projector, 4K UHD and HDR compatible**
- **Eco-friendly design - Low power consumption, energy saving and a long product lifespan**
- **External power supply - More reliability, portability and energy efficiency**
- **Lightning-fast gaming - Supports 1080p 120Hz with a 8.6ms response time**



The ZH401e is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 4400-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

An added benefit, the ZH401e features an external power supply offering more reliability, portability and energy efficiency.

Specifications

EAN: 5055387669703, Colour: Black

The following specifications are preliminary and subject to change without notice

Display/image

Display technology	DLP®
Resolution	1080p Full HD (1920x1080)
Brightness	4,400 lumens
Contrast ratio	300,000:1
Contrast ratio - dynamic	2,000,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.76m ~ 3.89m (30" ~ 153") diagonal

Lamp info

Light source type	Laser
LASER life	30,000 hours

Optical

Throw ratio	1.48:1 ~ 1.62:1
Projection distance	1m - 10m / 39.37" - 393.7"
Zoom	1.1
Zoom type	Manual
Focal length	21.86 ~ 24mm
Native offset	116%

Connectivity

Connections	Inputs 2 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm Outputs 1 x Audio 3.5mm, 2 x USB-A power 1.5A Control 1 x RS232, 1 x 12V trigger, 1 x RJ45, 1 x 3D sync
-------------	--

General

Noise level (min)	29dB
Noise level (max)	31dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2500m
Remote control	Card style
Speaker count	1
Watts per speaker	15W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual

Power

Power supply	100V ~ 240V, 50-60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	110W
Power consumption (max)	150W

Weight and dimensions

Dimensions (W x D x H)	274 x 216 x 114 mm / 10.79" x 8.5" x 4.49"
Gross weight	4.2 kg / 9.26 lbs
Net weight	3 kg / 6.61 lbs