

11.2 Technical Specifications

Basic Specifications

Dimensions	Main Device: OD 78mm; H 293.5mm Remote: H 160mm; W 42mm; D 21mm
System Requirements	Windows 7 or later; macOS 10.8 or later
Compatibility	Zoom, Tencent Meeting, GoToMeeting, Skype, Teams, BlueJeans, DingTalk, Slack, CloudLink, Polycom, StarLeaf, Google Meet, Huawei Cloud Meeting, Wolink, Cisco Webex, Tianyi Cloud, and other UVC-compliant platforms.
Resolution	4K, 1080p, 720p @ 30fps
Encoding Format	MJPEG
LED Indicator	Red / Blue / Green
Physical Buttons	Volume+, Volume-, Mute (Record Screen), Power, Mode Switch
Speaker	48mm voice-enhanced driver; Power: 10W; Sensitivity: 92dB SPL
Microphone Array	8-mic array with beamforming; 5.5m pickup range; Features: AGC, AEC, AI Noise Reduction, AI Dereverberation, Voice Enhancement.
Expansion	Daisy Chain Mic: BT; Daisy Chain Camera: 1. Dual-camera link with Meeting Pro 2 / Kandao Meeting Ultra series. 2. Supports up to 8 units via Kandao Meeting Omni.
USB Type-C Out	USB 2.0 (UVC/UAC) for Video/Audio output
USB Type-C In	Power input

Basic Specifications

Ethernet (RJ45)	Supported
USB-A	For external peripherals (Mouse, Keyboard)
HDMI	HDMI 1.4 for Video Output and System Interface display
Wi-Fi	5G / 2.4G; Wi-Fi 6 (ax); Supports STA mode 支持STA模式
Bluetooth	BT 4.1
Storage	64GB Internal
Micro SD Card	Supports FAT32 format (Up to 256GB)
Power Adapter	Input: AC100-240V 50/60Hz 1.5A Max Output: DC 20V 3A
Net Weight	1.1KG