

# ClickShare Hub Pro and Control Panel Kit

Premium modular video conferencing room system for enhanced hybrid meetings in Microsoft Teams Rooms with Control Panel



ClickShare Hub Pro is a premium, modular wireless video conferencing system for enhanced hybrid meetings.

The Hub Pro works with the ClickShare Control Panel and it enables participants to start their meeting with a simple tap. Sharing 4K content is just as easy with two next-gen ClickShare Buttons. Paired with dual display support, the Hub enhances engagement and collaboration.

For IT managers and integrators, ClickShare Hub Pro offers a customizable solution for all room types. Built on the Microsoft Device Ecosystem Platform (MDEP), it guarantees enterprise-grade security and compliance.

## Product specifications

## CLICKSHARE HUB PRO AND CONTROL PANEL KIT

### General Specifications

|                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating system                         | Android (MDEP)                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Microsoft Teams Rooms license required   | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| System requirements                      | For ClickShare App: Minimum: Intel Core i3 or AMD Ryzen 5, 8GB RAM, Windows 10 20H5; Intel Core i3 or Apple Silicon M1, 8GB RAM, macOS 11 Big Sur Recommended: Intel Core i5/Ultra 5 or AMD Ryzen 7, 8GB RAM, Windows 11 latest build; Apple Silicon M3, 8GB RAM, macOS latest build                                                                                                                                                                                                |
| Video outputs                            | HDMI-1: UWSK WUHD (5120*2160) @30Hz HDMI 2.0 HDMI-2: 4K UHD (3840*2160) @30Hz HDMI 2.0 eDP (Control Panel): HD (1280*800) @60Hz DP 1.4                                                                                                                                                                                                                                                                                                                                              |
| Video inputs                             | 4K UHD (3840*2160) @30Hz HDMI 2.0                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Audio output                             | USB-A 2.0/3.0 USB-C 2.0/3.0 HDMI 2.0                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| ClickShare Buttons                       | 2 ClickShare Button 5th Generation                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| ClickShare App                           | Desktop                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Maximum sources simultaneously on screen | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Noise Level                              | Maximum 25 dBA @ 30°C                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Wireless transmission protocol           | IEEE 802.11 a/b/g/n/ac/ax/be and IEEE 802.15.1 BT 5.3                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Reach                                    | Max. 30m (100ft) between ClickShare Button and ClickShare Base Unit                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Frequency band                           | 2.4GHz, 5GHz and 6GHz DBS/HBS (DFS channels supported in select number of countries)                                                                                                                                                                                                                                                                                                                                                                                                |
| Connections                              | Back: 1x Ethernet LAN 1Gbit 1x USB-C Power delivery 3.1 EPR (for power adapter) 2x HDMI 2.0 output 2x USB-C 2.0/3.0 1x USB-A 2.0/3.0 1x USB-C 2.0/3.0 Device + USB-C DisplayPort™ output 1x USB-C 2.0 + USB-C DisplayPort™ output Front: 1x USB-C 2.0/3.0<br>Operating: 0°C + 40°C (+32°F to +104°F) Max 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F)<br>Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing |
| Temperature range                        | Kensington lock                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Humidity                                 | FCC/CE                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Anti-theft system                        | LAN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Certifications                           | Yes, XMS Cloud                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Network connection                       | 3 years standard                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Management and reporting                 | 37 * 180 * 180 (mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Warranty                                 | Operational: 160W (max) Standby                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Dimensions (HxWxD)                       | External USB-C charger 100W (PD3.0 SPR), 180W (PD3.1 EPR)                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Power consumption                        | 720g                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Power supply                             | ClickShare Hub Pro Base Unit, 2 ClickShare Hub Button 5th Gen, Mounting disc, Safety manual, Quick setup guide, ClickShare Control Panel, ClickShare 10M 20W USB-C AOC cable, L-Shape mounting plate, Round base, Screw pack, Safety manual, USB-C cable lock kit, Power cord, Power supply                                                                                                                                                                                         |
| Weight                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Box content                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

### ClickShare 10M 20W USB-C AOC Cable (Directional)

|                         |                                                                                                                                                       |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cable Length / Diameter | 10M / 6mm                                                                                                                                             |
| Interface               | USB Type-C 3.2 Gen1, DP 1.4                                                                                                                           |
| Power Delivery          | 20W                                                                                                                                                   |
| Bend Radius             | 60mm/30mm (Fixed/Temporarily) While a minimum bend of 30mm is acceptable during handling or routing, it must not be maintained as a permanent fixture |
| Temperature range       | Operating: -10°C + 60°C (+14°F to +140°F) Storage: -20°C to +70°C (-4°F to +158°F)                                                                    |
| Humidity                | Storage/Operation: 0 to 85% relative humidity, non-condensing                                                                                         |
| Flame rated             | VW-1 (Not plenum rated)                                                                                                                               |

### Power supply

|                         |                                                                                              |
|-------------------------|----------------------------------------------------------------------------------------------|
| AC Input                | 100-240V~50-60Hz 2.4A                                                                        |
| DC Output               | 180W max (36V 5A) / 140W (28V 5A) / 100W (20V 5A) / 45W (15V 3A) / 27W (9V 3A) / 15W (5V 3A) |
| Output Plug             | USB Type-C                                                                                   |
| Input AC Type           | IEC60320-C6                                                                                  |
| Energy Efficiency Level | Comply with DOE standard Level VI                                                            |
| Altitude                | 5,000 meters                                                                                 |
| DC cable length         | 1.5m                                                                                         |

### Power cord

|                |                                        |
|----------------|----------------------------------------|
| Color          | Black                                  |
| Length         | 0.5m                                   |
| Plug Type      | EU / US / UK / CN / CH / IN / ZA / ANZ |
| Connector Type | IEC60320-C5                            |

### Control Panel

|                        |                                                                                                                                                                  |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Touchscreen            | 10.1-inch projected capacitive touchscreen with anti-fingerprint and anti-glare coatings, supporting up to 4 touch points for enhanced visibility and durability |
| Resolution             | 1280*800 @60Hz                                                                                                                                                   |
| Brightness             | 300 nits                                                                                                                                                         |
| Contrast ratio         | Automatically detects in-room human movement within a 2-meter range and 90° field of view to wake the system.                                                    |
| Viewing angle          | USB Type-C 2.0, DisplayPort Alt Mode, PD3.0 Recommend using the included ClickShare 10M USB-C AOC cable for optimal performance                                  |
| Human detection sensor | 80° (Up/Down/Left/Right)                                                                                                                                         |
| Connections            | USB Type-C 2.0, DisplayPort Alt Mode, PD3.0 Recommend using the included ClickShare 10M USB-C AOC cable for optimal performance                                  |
| Anti-theft system      | Kensington lock                                                                                                                                                  |
| Temperature range      | Operating: 0°C + 40°C (+32°F to +104°F) Storage: -20°C to +60°C (-4°F to +140°F)                                                                                 |
| Humidity               | Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing                                                        |
| Dimensions (HxWxD)     | 254.5 x 187.9 x 76.9 (mm)                                                                                                                                        |
| Power consumption      | Powered over USB from connected Base Unit. Operational: 7.3W (max) Standby:                                                                                      |
| Weight                 | 820g                                                                                                                                                             |

Last updated: 09 Jul 2026

© 2026 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.