



LW655

BenQ DLP Projector


- Supports LAN Control & FW upgrade
- Supports Wireless Control & FW upgrade*
- Supports BenQ DMS Local & Agent Mode**
- Supports Wireless Casting via QP30 Dongle

Display	
Projection System	DLP Single
DMD Type	0.65" WXGA
Native Resolution	1280 x 800 pixels (WXGA)
Brightness	4000 ANSI Lumens
Contrast Ratio*	3,000,000 : 1
Display Colour	30 Bits (1.07 Billion Colours)
Aspect Ratio	Native 16:10 (6 Aspect Ratio Selectable: 16:9/16:10/4:3/1:1/5:4/Auto)
Light Source	Laser Phosphor
Light Source Life** (Normal / Eco)	20,000 / 30,000 hours
Optical	
Throw Ratio	1.19 ~1.54
Zoom Ratio	1,3
Keystone Correction	2D Vertical & Horizontal (±40 degrees); Auto ID Keystone (Vertical)
Projection Offset	110%
Projection Size	40"-120"
Audio	
Built-In Speaker	15W x1
Special Feature	
Security	Security Bar, Kensington Lock
Features	Industry Expert Colour Modes, Firmware (FW) upgrade and BenQ DMS Local via DM01, Wireless Casting via QP30 Dongle (Optional), IP6X Dustproof Engine
Compatibility	
Resolution Support	VGA (640 x 480) to FHD (1920 x 1080)
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	23-120Hz
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p
Power	
Power Consumption (Max / Normal / Eco)	175W @100V AC; 170W @220V AC
Standby Power Consumption	< 0.5W
Power Supply	100-240V AC
Dimension and Weight	
Product Dimensions (W x H x D)	279.2 x 224.8 x 120.5 mm
Product Weight	3.0 Kg+/- 100g
Operation Condition	
Noise Level (Normal/Eco)	32/29 dB
Operating Temperature	0 ~ 40°C
Accessories	
Accessories (Standard)	QSG, Remote Control (RCA011), AAA Battery x2, HDMI cable (1.5m), Power Adapter(1.8m), Power Cord (1m), Warranty Card (by Region)
Accessories (Optional)	Ceiling Mount (CM00G3), USB Dongle (EZC5201BS), Wireless Casting Dongle (QP30)
OSD	
On Screen Display Language	Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Farsi/ Vietnamese/ (30 Languages)
Other	
Part Number / EAN Code	9H.JV377.74E / 471 8755 09852 9

* Via EZC5201BS Dongle. / ** DMS Cloud under development. / *** The Contrast is measure by Full On Full Off standard. / **** LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

BenQ


INPUT AND OUTPUT TERMINALS



- 1 - HDMI-1 (HDMI 1.4a / HDCP 1.4)
 - 2 - HDMI-2 (HDMI 1.4a / HDCP 1.4)
 - 3 - RS232 In (D-sub 9pin, male)
 - 4 - USB Type-A -1 (5V/1.5A power / Wired FW Upgrade)
 - 5 - Audio out (3.5 mini jack)
 - 6 - LAN
 - 7 - USB Type-A -2 (5V/1A power / Wireless Control & FW Upgrade)
 - 8 - Kensington anti-theft lock slot
 - 9 - IR Receiver (Top)
- *via optional E2C5201BS Dongle
- Security Bar


CEILING / WALL MOUNT INSTALLATION

BenQ ceiling
mount CM00G3
(5J.JAM10.001)



Ceiling/Wall
mount screw:
M4 x 8L

PROJECTION DIMENSIONS




The Projection performance will differ based on actual projection size and ambient light.

DIMENSIONS

279.2 (W) x 224.8 (H) x 120.5 (D) mm

Unit: mm



DISTANCE CHART

Screen Size				Projection Distance		Vertical Offset (mm) (110%)
Diagonal		H (mm)	W (mm)	Max. zoom	Min. zoom	
Inch	mm					
30	762	404	646	767	998	40
40	1016	538	862	1023	1330	54
50	1270	673	1077	1278	1663	67
60	1524	808	1292	1534	1995	81
70	1778	942	1508	1790	2328	94
80	2032	1077	1723	2045	2661	108
90	2286	1212	1939	2301	2993	121
100	2540	1346	2154	2557	3326	135
110	2794	1481	2369	2812	3658	148
120	3048	1615	2585	3068	3991	162
130	3302	1750	2800	3324	4323	175
140	3556	1885	3015	3579	4656	188
150	3810	2019	3231	3835	4988	202
160	4064	2154	3446	4091	5321	215
170	4318	2289	3662	4346	5654	229
180	4572	2423	3877	4602	5986	242
190	4826	2558	4092	4858	6319	256
200	5080	2692	4308	5113	6651	269
210	5334	2827	4523	5369	6984	283
220	5588	2962	4739	5625	7316	296
230	5842	3096	4954	5880	7649	310
240	6096	3231	5169	6136	7982	323
250	6350	3365	5385	6392	8314	337
260	6604	3500	5600	6647	8647	350
270	6858	3635	5816	6903	8979	363
280	7112	3769	6031	7159	9312	377
290	7366	3904	6246	7414	9644	390
300	7620	4039	6462	7670	9977	404

All measurements are approximate and may vary from the actual sizes. | BenQ recommends that if you intend to permanently install the projector, you should physically test the projection size and distance using the actual projector on site before you permanently install it, so as to make allowance for this projector's optical characteristics. This will help you determine the exact mounting position so that it best suits your installation location.



benq.eu/en-eu/business/projector.html

© 2026 BenQ Corp. Specifications may vary by region, please visit your local stores for details. Actual product's features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.

BENQ