



# BASSO112

## 12" ultra-high power infra-subwoofer

### Highlights:

- 2000 Watt program power
- Low frequency extension down to 26Hz without processing
- 124 dB of Max SPL (continuous)
- Indoor model with Polyurea coated 18/36mm multiply plywood
- Extremely ridged chassis and inner framing

### Product information:

Engineered for demanding environments such as nightclubs, concert venues, theme parks, and hospitality spaces, the BASSO Series combines cutting-edge technologies like the pure carbon fiber cone and AeroVent for exponential low-noise venting with meticulous craftsmanship to set a new standard in low-frequency fidelity.

With a focus on ultra-high power output and exceptional sound clarity, the BASSO Series offers a flexible, efficient solution for diverse applications. Each model is designed to deliver a visceral sound experience with immersive infra-sub performance and extremely low distortion.

### Applications:

- Bars & Restaurants
- Hotels
- Clubs
- Sporting facilities
- Events
- Concert venues
- Museums & Themeparks



### Impedance:

$\Omega$  8 Ohm

### Usage:



Indoor

System specifications:

|                            |                   |                                                                                    |
|----------------------------|-------------------|------------------------------------------------------------------------------------|
| Speaker type               |                   | 12" Infra-Sub                                                                      |
| Configuration              |                   | AeroVent                                                                           |
| Peak power handling        |                   | 4000 W                                                                             |
| Program power handling     |                   | 2000 W                                                                             |
| Continuous power (AES)     |                   | 1000 W                                                                             |
| Impedance                  |                   | 8 Ω                                                                                |
| Max SPL (Continuous/AES)   |                   | 124 dB                                                                             |
| Sensitivity (1W/1m)        |                   | 94 dB                                                                              |
| Frequency                  | Response (- 3 dB) | 33 Hz - 120 Hz                                                                     |
|                            | Range (-10 dB)    | 26 Hz - 200 Hz                                                                     |
| Bass port tuning frequency |                   | 39 Hz                                                                              |
| Drivers                    |                   | 12" carbon cone with dual suspension (low-loss) and 3.5" high excursion voice coil |
| Connectors                 |                   | High-current terminal block with linkthrough                                       |

Product Features:

|                       |                |                                                                                              |
|-----------------------|----------------|----------------------------------------------------------------------------------------------|
| Dimensions            |                | 608 x 366 x 595 mm (W x H x D) (excluding feet)                                              |
|                       |                | 608 x 371 x 595 mm (W x H x D) (including feet)                                              |
| Weight                |                | 26 kg                                                                                        |
| Construction          |                | 18 mm Multiply plywood                                                                       |
|                       |                | Metal parts - Stainless steel bolts & fasteners                                              |
| Finish                | Cabinet finish | Multi-Layer polyurea coating (4-layer)                                                       |
|                       | Front finish   | 2.0 mm Zinc plated steel with hexagon perforations and powder coat & acoustical foam backing |
| Mounting & handling   | Rigging points | 8 x M10 mounting bracket installation holes on both sides                                    |
|                       | Stand fitting  | 1 x M20 internal thread stand adapter                                                        |
| Operating temperature |                | -20 °C ~ 70 °C                                                                               |
| Colours               |                | Black                                                                                        |

Variants:

- BASSO112/B - Black version

Shipping & Ordering:

|                          |                  |
|--------------------------|------------------|
| Packaging                | Cardboard box    |
| Shipping weight & volume | 29 kg - 0.19 Cbm |