

20,000 lm of SOLID SHINE Laser Power in a Compact, Lightweight Projector That Cuts Total Cost of Ownership



PT-RZ21K Series		
	PT-RZ21K	PT-RS20K
Brightness		20,000 lm
Resolution	WUXGA	SXGA+
Contrast		20,000:1

Original Technology Assures Elite Performance

- Combines 3-Chip DLP™ with Panasonic SOLID SHINE Laser Phosphor Technology for Bright, Natural, and Immersive Picture Quality
- Latest Standard Compatibility for Accurate Color-space Reproduction
- Minimal Maintenance Required Under Continuous Operation
- Dust-resistant Design Featuring Hermetically Sealed Laser Modules
- Efficient Cooling System for Stable Operation and Long Life

Reference Image Quality Maintained Longer

- High 20,000 lm Brightness in a Compact, Lightweight, Easy-to-Handle Body
- Dynamic Contrast Laser Light-source Modulation Achieves High Contrast
- Detail Clarity Processor Clarifies and Enhances Fine Details with Advanced Processing Algorithm
- Daylight View Function Improves Color Perception in Bright Environments and in Mapping Applications

Versatile System Installation and Rigging Flexibility

- Free 360-degree Installation (Vertical and Horizontal)
- Shares Optional Lenses with Panasonic 3-Chip DLP™ Projector Family Including Ultra-Short Throw Lens
- DIGITAL LINK Supports Transmission of Uncompressed Full HD Video and Control Commands Through Single LAN Cable
- Multi-Screen Support System Seamlessly Connects Multiple Screens
- Multi-Unit Brightness and Color Control
- Free Geometry Manager Pro and Optional Upgrade Kit

Specifications (Tentative)

Model	PT-RZ21K	PT-RS20K	
Power supply	AC 100-120 V, AC 200-240 V (Brightness decreases at voltages less than AC 200 V)		
Power consumption	TBD		
DLP™ chip	Panel size	24.4 mm (0.96 inches) diagonal (16:10 aspect ratio)	
	Display method	DLP™ chip × 3, DLP™ projection system	
	Pixels	6,912,000 (1920 × 1200 × 3) pixels	
Refresh rate	120 Hz ^{*1}		
Lens	Optional (no lens included with this model)		
Light source	Laser diode, Light source life: 20,000 hours (Normal Mode, brightness decreases to approx. 50 %)		
Screen size (diagonal)	1.78–25.4 m (70–1,000 in) with 16:10 aspect ratio	1.78–25.4 m (70–1,000 in) with 4:3 aspect ratio	
	1.78–15.24 m (70–600 in) with the ET-D75LE8, 16:10 aspect ratio	1.78–15.24 m (70–600 in) with the ET-D75LE8, 4:3 aspect ratio	
	3.05–15.24 m (120–600 in) with the ET-D75LE95, 16:10 aspect ratio	3.05–15.24 m (120–600 in) with the ET-D75LE95, 4:3 aspect ratio	
Brightness	20,000 lm / 21,000 lm (Center)		
Center-to-corner uniformity	90 %		
Contrast	20,000:1 (Full On/Full Off, Dynamic Contrast Mode: 3)		
Resolution	1920 × 1200 pixels	1400 × 1050 pixels	
Scanning frequency	SD-SDI	SMPTE ST 259 compliant, [YCbCr 4:2:2 10-bit] 480/60i, 576/50i	
	HD-SDI	SMPTE ST 292 compliant, [YPbPr 4:2:2 10-bit] 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/25p, 1080/24p, 1080/24sF, 1080/30p	
	Dual-link HD-SDI	SMPTE ST 372 compliant, [YPbPr 4:2:2 10-bit] 1080/50p, 1080/60p [RGB 4:4:4 12-bit/10-bit] 1080/60i, 1080/50i, 1080/25p, 1080/24p, 1080/24sF, 1080/30p, 2048 × 1080/24p, [X'Y'Z' 4:4:4 12-bit] 2048 × 1080/24p	
	3G-SDI	SMPTE ST 424 compliant, [RGB 4:4:4 12-bit/10-bit] 1080/60i, 1080/50i, 1080/25p, 1080/24p, 1080/24sF, 1080/30p, 2048 × 1080/24p, 2048 × 1080/25p, 2048 × 1080/30p, [YPbPr 4:2:2 10-bit] 1080/60p, 1080/50p, 2048 × 1080/48p, 2048 × 1080/50p, 2048 × 1080/60p, [X'Y'Z' 4:4:4 12-bit] 2048 × 1080/24p, 2048 × 1080/25p, 2048 × 1080/30p	
	Dual-link 3G-SDI	SMPTE ST 425 compliant, [YPbPr 4:4:4 12-bit/10-bit] 1080/60p, 1080/50p, 2048 × 1080/60p, 2048 × 1080/50p, 2048 × 1080/48p, [RGB 4:4:4 12-bit/10-bit] 1080/60p, 1080/50p, 2048 × 1080/60p, 2048 × 1080/50p, 2048 × 1080/48p	
	HDMI/DVI-D	480/60i ^{**} , 576/50i ^{**} , 480/60p, 720/60p, 720/50p, 1080/60i, 1080/50i, 1080/24p, 1080/24sF, 1080/25p, 1080/30p, 1080/60p, 1080/50p, 640 × 400–WUXGA ^{**3} (1920 × 1200) (compatible with non-interlaced signals only), dot clock: 25–162 MHz	
	RGB	fh: 15–100 kHz, fv: 24–120 Hz, dot clock: 20–162 MHz	
	YPbPr (YCbCr)	fh: 15.73 kHz, fv: 59.94 Hz [480/60i], fh: 15.63 kHz, fv: 50 Hz [576/50i], fh: 31.47 kHz, fv: 59.94 Hz [480/60p], fh: 31.25 kHz, fv: 50 Hz [576/50p], fh: 45.00 kHz, fv: 60 Hz [720/60p], fh: 37.50 kHz, fv: 50 Hz [720/50p], fh: 33.75 kHz, fv: 60 Hz [1080/60i], fh: 28.13 kHz, fv: 50 Hz [1080/50i], fh: 28.13 kHz, fv: 25 Hz [1080/25p], fh: 27.00 kHz, fv: 24 Hz [1080/24p], fh: 27.00 kHz, fv: 48 Hz [1080/24sF], fh: 33.75 kHz, fv: 30 Hz [1080/30p], fh: 67.50 kHz, fv: 60 Hz [1080/60p], fh: 56.25 kHz, fv: 50 Hz [1080/50p]	
	Video/YC	fh: 15.73 kHz, fv: 59.94 Hz (NTSC/NTSC4.43/PAL-M/PAL60), fh: 15.63 kHz, fv: 50 Hz (PAL/PAL-N/SECAM)	
	Optical axis shift ^{*4}	Vertical (from center of screen)	±55 % (±44 % with ET-D75LE6, +68 % – +78 % with ET-D75LE95) (powered)
Horizontal (from center of screen)		±20 % (±15 % with ET-D75LE6, ±12 % with ET-D75LE95) (powered)	
Keystone correction range	Vertical: ±40 ° (±22 ° with ET-D75LE50, ±28 ° with ET-D75LE6), Horizontal: ±15 °		
Keystone correction range with optional Upgrade Kit ET-UK20	Vertical: ±45 ° (±40 ° with ET-D75LE10/20, ±22 ° with ET-D75LE50, ±28 ° with ET-D75LE6), Horizontal: ±40 ° (±15 ° with ET-D75LE50/6), Up to a total of ±55 ° during simultaneous horizontal and vertical correction.		
Installation	Horizontal/vertical, free 360-degree installation		
Terminals	SDI 1 IN	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-A), Dual-link 3G-SDI (Link 1)	
	SDI 2 IN	BNC × 1: 3G/HD/SD-SDI input, Dual-link HD-SDI (Link-B), Dual-link 3G-SDI (Link 2)	
	HDMI IN	HDMI 19-pin × 1 (Deep Color, compatible with HDCP)	
	DVI-D IN	DVI-D 24-pin × 1 (DVI 1.0 compliant, compatible with HDCP)	
	RGB 1 IN	RGB × 1 (BNC × 5): RGB/YPbPr/YCbCr/YC/VIDEO	
	RGB 2 IN	D-sub HD 15-pin (female) × 1: RGB/YPbPr	
	MULTI PROJECTOR SYNC IN	BNC × 1	
	MULTI PROJECTOR SYNC OUT	BNC × 1	
	SERIAL IN	D-sub 9-pin (female) × 1 for external control (RS-232C compliant)	
	SERIAL OUT	D-sub 9-pin (male) × 1 for link control	
	REMOTE 1 IN / OUT	M3 × 1 for wired remote control, link control	
	REMOTE 2 IN	D-sub 9-pin (female) × 1 for external control (parallel)	
	DC OUT	USB (type A) × 2, DC 5 V, max 900 mA	
	LAN/DIGITAL LINK	RJ-45 × 1 for network, DIGITAL LINK connection, 100Base-TX, compatible with Art-Net, PjLink™ (class 1), Deep Color, HDCP	
Dimensions (W × H × D)	TBD		
Weight	TBD		
Operation noise ^{*5}	TBD		
Cabinet materials	Molded plastic		
Operating environment	TBD		
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro (ET-UK20 Upgrade Kit), Smart PJ Control		

^{*1} Refresh rate varies depending on scanning frequency. ^{*2} Only compatible with dot-clock frequency of 27 MHz (pixel repetition signal). ^{*3} WUXGA resolution is supported when the signals are compliant with VESA CVT-RB (Coordinated Video Timing-Reduced Blanking). ^{*4} Optical axis shift is not supported on the ET-D75LE50. ^{*5} Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards.

Optional Accessories

- Fixed-Focus Lens
ET-D75LE50 / ET-D75LE95
- Zoom Lens
ET-D75LE6 / ET-D75LE10
ET-D75LE20 / ET-D75LE30
ET-D75LE40 / ET-D75LE8

- Replacement Filter Unit
TBD
- Smoke Cut Filter
TBD

- Ceiling Mount Bracket for High Ceilings
ET-PKD520H
- Ceiling Mount Bracket for Low Ceilings
ET-PKD520S

- Projector Mount Bracket
ET-PKD520B

- Geometry Manager Pro Software Upgrade Kit
ET-UK20 Series
- Auto Screen Adjustment Upgrade Kit
ET-CUK10



Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. DLP, DLP logo and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. PjLink™ is a registered trademark or pending trademark in Japan, the United States, and other countries and regions. All other trademarks are the property of their respective trademark owners. © 2017 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
 Projector Global Website – panasonic.net/avc/projector
 Facebook – www.facebook.com/panasonicprojector
 YouTube – www.youtube.com/user/PanasonicProjector

All information included here is valid as of February 2017.

PT-RZ21KPRE1 Printed in Japan.