

MEDIUM THININSTALL™ DUAL SWING ARM WALL
DISPLAY MOUNT - 25" EXTENSION



Certifications	UL Listed
Color	Black
Lateral Shift	406 mm
Manual Height Adjustment	25.4 mm
Maximum Extension	652.8 mm
Maximum Screen Thickness	127 mm
Minimum Depth	46 mm
Mounting Pattern Compatibility (Universal Versions)	100 x 100mm - 600 x 400 mm
Orientation	Landscape
Overall Dimensions (HxWxD)	437 x 749 x 46 mm
Pivot (numerical value)	±90° (depending on screen width)
Post-Installation Leveling (Roll)	Yes
Shipping Weight	14 kg
Solution Type	Universal
Tilt	+ 0°, - 15°
Typical Screen Sizes*	26 - 52"
Weight Capacity	34 kg



Color option:



*Always check compatibility with the Chief mountfinder on the Chief website.

SPECIFICATIONS

- Low profile Mount design has 46 mm depth when collapsed.
- For LED, LCD displays with max 127mm depth
- 63,5 cm maximum extension
- Provides up to 15° of fingertip tilt.
- 2.5 degrees post installation display levelling
- Post-installation lateral shift allows up to 406 mm of adjustment left and right
- Fully integrated cable management. Enclosed, tool-free cable covers
- Wide open wall plate design for power outlet and signal cables routing.
- 25mm of post installation height adjustment
- Compatible with dedicated AV component shelves and AV camera shelves
- Universal Screen interface is included.
- Mount is fully assembled.
- VESA compatible: 100 x 100mm - 600 x 400 mm
- Overall Dimensions (HxWxD): 437 x 749 x 46 mm
- Weight capacity: 34 kg per display
- Color: Black
- Certifications: UL

RECOMMENDED ACCESSORIES



TA200

THININSTALL™ Video Conferencing Camera Shelf - 20 cm



PAC526

Large in-Wall Storage Box for organized, recessed space for routing excess cables and attaching power.



