

IMPORTANT SAFETY INSTRUCTIONS

1. Read these instructions.
2. Keep these instructions.
3. Heed all warnings.
4. Follow all instructions.
5. For indoor use only.
6. Do not use this product near water.
7. Clean only with dry cloth.
8. Do not block ventilation openings. Maintain minimum distance around the product for sufficient ventilation. Ventilation should not be impeded by covering the ventilation openings with items such as newspapers, tablecloths, curtains, etc. Install in accordance with the manufacturer's instructions.
9. No open flame sources, such as lighted candles, should be placed on the product.
10. Do not install near any heat sources such as radiators, heat registers, stoves, or other product (including amplifiers) that produce heat. .
11. Do not defeat the safety purpose of the grounding-type plug. A grounding type plug has two blades and a third grounding prong. The third prong is provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.
12. Protect the power cord from being walked on or pinched, particularly at plugs, convenience receptacles and the point where they exit from the product.
13. Only use attachments/accessories specified by the manufacturer.
14. Use only with equipment rack, cart, stand or table designed to provide adequate mechanical strength, heat dissipation and securement to the building structure. When a cart is used, use caution when moving the cart and product combination to avoid injury from tip-over.
15. Unplug this product during lightning storms or when unused for long periods of time.
16. Refer all servicing to qualified service personnel. Servicing is required when the product has been damaged in any way, such as if power supply cord or plug is damaged, liquid has been spilled or objects have fallen into the product, the product has been exposed to rain or moisture, does not operate normally, or has been dropped.



Explanation of Graphical Symbols



Lightning Bolt: Hazardous Live voltages present when this unit is in operation. Do not touch terminals marked with this symbol while the unit is connected to live power.



Exclamation Point: Replace components (i.e. fuses) only with the values specified by the manufacturer. Failure to do so will compromise safe operation of this unit.




Hazardous Moving Fan Blades: Remove power before servicing and keep away from moving fan blades.



Earth Ground: Protective conductor terminal

This product is intended for Installation and Service by Skilled Personnel Only.

WARNING

- To reduce the risk of fire or electric shock, do not expose these products to rain or moisture. These products must not be exposed to dripping or splashing and no objects filled with liquids, such as vases, shall be placed on these products.
- 100 Volt speaker terminals marked with the symbol  are Hazardous Live. External wiring connected to these terminals requires installation by a Skilled or Instructed Person.
- MAINS powered products employ Safety Grounding and must be connected to a MAINS socket that is properly grounded to provide a protective earthing connection. The MAINS plug is used to disconnect MAINS power and must remain readily operable.

CAUTION

- When POTS Telephone Interface options are provided, connections to the telecom circuits of this device must be made by qualified, trained personnel. To reduce the risk of fire, use only No. 26 AWG (0.129 mm²) solid copper wire for telecom circuit connections.
- To reduce the Risk of Electric Shock, Installation and Service of Biamp Products should be conducted only by Skilled Persons who are Biamp Qualified Audio Installation Professionals.
- Do not perform any servicing other than that contained in the Operating Instructions unless you are a Skilled Person qualified to do so. Skilled Persons must disconnect AC MAINS Power before opening product.
- The Installation steps for 'Auxiliary Power' are for use by Skilled Personnel only and must comply with all local codes.
- National Electrical Code, ANSI/NFPA 70 for United States.
- Canadian Electrical Code, Part 1, CSA C22.1, Sections 2-128, 12-010(3) and 12-100 for Canada.
- For PLUGGABLE EQUIPMENT, the socket should be installed near the equipment and easily accessible.
- Changes or modifications not approved by Biamp could void the user's authority to operate the equipment.

Wall Mounting Instructions

Wall mounted products must be installed 2 meters or less from the floor and be securely fastened to drywall or similar surface using a minimum of 4 wood screws (2 screws for products having only two mounting holes). Wood screws should be inserted a minimum of ½ inch (1.3 cm) into wood studs. Alternate fasteners which may be used include drywall anchors and self-tapping sheet metal screws inserted into metal studs.