

Hub Core, Hub Pro

ClickShare



Safety manual

Barco NV
Beneluxpark 21, 8500 Kortrijk, Belgium
www.barco.com

Manufacturer: Barco NV
President Kennedypark 35, 8500 Kortrijk, Belgium

1 Safety

1.1	General considerations	3
1.2	Environmental Condition Check	4
1.3	International safety standards	4
1.4	Product compliance EU	4
1.5	Product compliance UK	4
1.6	Product compliance Ukraine	5
1.7	Product compliance US	5
1.8	Product compliance Canada	6
1.9	Product compliance Brazil	6
1.10	Product compliance Mexico	7
1.11	Product compliance Taiwan	7
1.12	Product compliance India	7
1.13	Trademark notice	7

About this document

Read this document attentively. It contains important information to prevent personal injury while installing and using the ClickShare product. Furthermore, it includes several cautions to prevent damage to the unit. Ensure that all safety guidelines, safety instructions and warnings mentioned in this chapter are understood and followed before installing the ClickShare product.

Clarification of the term “Base Unit” used in this document

When referring in this document to the term “Base Unit” means that the content is applicable for following Barco products:

- Hub Core
- Hub Pro

Clarification of the term “Button” used in this document

When referring in this document to the term “Button” means that the content is applicable for following Barco products:

- 5th gen Button

Clarification of the term “Control Panel” used in this document

When referring in this document to the term “Control Panel” means that the content is applicable for following Barco products:

- ClickShare Control Panel

Model certification names

- **Base Unit:** C-100RS, C-300RS
- **Button:** CSBTN005
- **Control Panel:** CSTUC001

Countries and peripherals

The Base Unit and peripherals are regionalized. An up to date list of the certified countries and applicable peripherals can be found on the product support page. For more information, see <https://www.barco.com/en/support>.



The Base Unit is region locked and cannot be used outside its original region.

1.1 General considerations

General safety instructions

The installation of the device must comply with the guidelines in the ClickShare installation manual.

- Installation must be performed by qualified personnel only, and must conform to all local codes.
- External power connections must be properly insulated.
- Do not connect directly to mains power for any reason.
- To prevent injuries and physical damage, always read this manual and all labels on the system before connecting to the wall outlet.

- The ClickShare product is intended to be used in office and indoor environments only.
- Only use the power adapter and/or power cord supplied by Barco. While appearing to be similar, other power adapters have not been safety tested at the factory and may not be used to power the device. For a replacement power adapter, contact your integrator.
- If the power adapter has three pins, then it must be plugged into a grounded outlet. This important safety feature of those three pinned adapters is not compatible with any other outlets.
- Do not allow anything to rest on the power cord. Do not locate this product where persons will walk on the cord. To disconnect the cord, pull it out by the plug. Never pull the cord itself.
- If an extension cord is used with this product, make sure that the total of the Ampere ratings on the products plugged into the extension cord does not exceed the extension cord Ampere rating.
- Never spill liquid of any kind on the product. Should any liquid or solid object fall into the cabinet, unplug the set and have it checked by qualified service personnel before resuming operations.
- Lightning - for added protection for this product during a lightning storm, or when it is left unattended and unused for long periods of time, unplug it from the wall outlet. This will prevent damage to the device due to lightning and AC power-line surges.
- Only use attachments/accessories specified by the manufacturer.

Power supply

Power method	Power specifications	
	OUT	IN
FSP100-A1BR3, FSP180-A1BR3	• 20-36VDC • 5A • 100-180W	• 100-240VAC • 1.4-2.4A • 47-63Hz

Environment

Do not place this equipment on an unstable cart, stand, or table. The product may fall, causing serious damage to it.

Risk of electric shock

Do not open. To reduce the risk of electric shock, do not remove the cover of the unit or of the power supply unit. No user-serviceable parts inside. Refer all servicing to qualified service personnel.

Unplug this product from the wall outlet and refer servicing to qualified service personnel under the following conditions:

- When the power cord or plug is damaged or frayed.
- If liquid has been spilled into the equipment.
- If the product has been exposed to rain or water.
- If the product does not operate normally when the operating instructions are followed. Adjust only those controls that are covered by the operating instructions since improper adjustment of the other controls may result in damage and will often require extensive work by a qualified technician to restore the product to normal operation.
- If the product has been dropped or the cabinet has been damaged.
- If the product exhibits a distinct change in performance, indicating a need for service.
- Replacement parts: When replacement parts are required, be sure the service technician has used original Barco replacement parts or authorized replacement parts which have the same characteristics as the Barco original part. Unauthorized substitutions may result in degraded performance and reliability, fire, electric shock or other hazards. Unauthorized substitutions may void warranty.
- Safety check: Upon completion of any service or repairs to this device, ask the service technician to perform safety checks to determine that the product is in proper operating condition.

Heat and fire hazard



CAUTION: Risk of fire or explosion if the battery is replaced by an incorrect type.



WARNING: Do not place flammable or combustible materials near the device!

Barco products are designed and manufactured to meet the most stringent safety regulations.

This device radiates heat on its external surfaces during normal operation, which is both normal and safe. Exposing flammable or combustible materials into close proximity of this device could result in the spontaneous ignition of that material, resulting in a fire. For this reason, it is absolutely necessary to leave an "exclusion zone" around all external surfaces of the device where no flammable or combustible materials are present. The exclusion zone must be not less than 40 cm (16") for all Barco devices. Do not cover the device with any material while it is in operation.

Mount the device in a well ventilated area away from sources of ignition and out of direct sun light.

Slots and openings in this equipment are provided for ventilation. To ensure reliable operation of the device and to protect it from overheating, these openings must not be blocked or covered. The openings should never be blocked by placing the device too close to walls, or other similar surface. This device should never be placed near or over a radiator or heat register. This device should not be placed in a built-in installation or enclosure unless proper ventilation is provided.

In the event of fire, use sand, CO₂, or dry powder fire extinguishers; never use water on an electrical fire.

Fusing: Internal fuse for Line is provided in the power supply. A blown internal fuse is an indication of catastrophic failure of circuit component(s). Repair must be performed by authorized personnel. Fuses must be replaced with same type and ratings.

1.2 Environmental Condition Check

Environment condition check

For installations in environments where the device is subject to excessive dust, then it is highly advisable and desirable to have this dust removed prior to it reaching the device clean air supply. Devices or structures to extract or shield excessive dust well away from the device are a prerequisite; if this is not a feasible solution then measures to relocate the device to a clean air environment should be considered.

It is the client's responsibility to ensure at all times that the device is protected from the harmful effects of hostile airborne particles in the environment of the device. The manufacturer reserves the right to refuse repair if a device has been subject to negligence, abandon or improper use.

Ambient temperature conditions

Max. ambient temperature : +40°C or 104°F at sea level, +35°C or 95°F at 3000m

Min. ambient temperature: 0°C or 32°F

Storage temperature: -10°C to +60°C (14°F to 140°F)

Humidity Conditions

Storage: 0 to 90% relative humidity, non-condensing

Operation: 0 to 85% relative humidity, non-condensing

Altitude

Maximum allowed altitude is 3000m (9843Ft) and 2000m (6561Ft) for China.

Environment



The ClickShare product is intended to be used in office and indoor environments only.

Do not install the device in a site near heat sources such as radiators or air ducts, or in a place subject to direct sunlight, excessive dust or humidity. Be aware that room heat rises to the ceiling; check that temperature near the installation site is not excessive.

1.3 International safety standards

Standards overview

This equipment is built in accordance with the requirements of the international safety standards (IEC62368-1, EN62368-1, UL62368-1, CAN/CSA C22.2 No.62368-1), which are the safety standards of information technology equipment including electrical business equipment. These safety standards impose important requirements on the use of safety critical components, materials and insulation, in order to protect the user or operator against risk of electric shock and energy

hazard and having access to live parts. Safety standards also impose limits to the internal and external temperature rises, radiation levels, mechanical stability and strength, enclosure construction and protection against the risk of fire. Simulated single fault condition testing ensures the safety of the equipment to the user even when the equipment's normal operation fails.


1.4 Product compliance EU

European Union



Batteries, battery packs, and accumulators should not be disposed of as unsorted household waste. Please use the public collection system to return, recycle, or treat them in compliance with the local regulations.

CE certification



C-100RS, C-300RS (R9861711EUB1; R9861710EUB2; CSBTN005) are fit for use in all European Union countries, EFTA and Turkey.

The C-100RS, C-300RS is restricted to indoor use only when operating in the 5150 to 5350 MHz and frequency range.

Devices operating in Low Power Indoor (LPI) mode within the 5925 MHz to 6425 MHz (UNII-5) are restricted to indoor use only.

Hereby, Barco NV declares that the radio equipment type C-100RS, C-300RS is in compliance with the Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address:

<https://www.barco.com/en/support/docs/TDE13557> (Base Unit)

For 2.4 GHz band:

- 2402 MHz - 2482 MHz
- Max EIRP: 18.28 dBm

For 5 GHz band:

- 5150 MHz - 5350 MHz
- 5470 MHz - 5725 MHz
- Max EIRP: 19.4 dBm

For 6 GHz band:

- 5925 MHz - 6425 MHz
- Max EIRP: 17.31 dBm

For Bluetooth®:

- 2402 MHz - 2480 MHz
- Max EIRP: 14.78 dBm

<https://www.barco.com/en/support/docs/TDE13558> (Button)

The ClickShare Button has been tested and meets the EU RF exposure standards. The maximum SAR value reported is 0.453 W/kg.

For 2.4 GHz band:

- 2402 MHz - 2482 MHz
- Max EIRP: 20 dBm

For 5 GHz band:

- 5150 MHz - 5350 MHz
- 5470 MHz - 5850 MHz
- Max EIRP: 23 dBm

For 6 GHz band:

- 5925 MHz - 6425 MHz
- Max EIRP: 23 dBm

1.5 Product compliance UK

UK Compliance



C-100RS, C-300RS (R9861711EUB1; R9861710EUB2; CSBTN005) are fit for use in the UK.

The C-100RS, C-300RS is restricted to indoor use only when operating in the 5150 to 5350 MHz frequency range.

Hereby, Barco NV declares that the radio equipment type C-100RS, C-300RS is in compliance with the Radio Equipment Regulations 2017: Great Britain. The full text of the UK declaration of conformity is available at the following internet address:

<https://www.barco.com/en/support/docs/TDE13559> (Base Unit)

For 2.4 GHz band:

- 2402 MHz - 2482 MHz
- Max EIRP: 18.28 dBm

For 5 GHz band:

- 5150 MHz - 5350 MHz
- 5470 MHz - 5725 MHz
- Max EIRP: 19.4 dBm

For 6 GHz band:

- 5925 MHz - 6425 MHz
- Max EIRP: 17.31 dBm

For Bluetooth®:

- 2402 MHz - 2480 MHz
- Max EIRP: 14.78 dBm

<https://www.barco.com/en/support/docs/TDE13560> (Button)

For 2.4 GHz band:

- 2402 MHz - 2482 MHz
- Max EIRP: 20 dBm

For 5 GHz band:

- 5150 MHz - 5350 MHz
- 5470 MHz - 5850 MHz
- Max EIRP: 23 dBm

For 6 GHz band:

- 5925 MHz - 6425 MHz
- Max EIRP: 23 dBm

Authorised Representative: Barco UK Ltd

Address: Building 329, Doncastle Road
Bracknell RG12 8PE, Berkshire, United Kingdom

Importer:

- Midwich Ltd, Vince's Rd, Diss IP98 6BB
- Exertis UK Ltd, Chineham Park, Crockford Ln, Chineham, Basingstoke RG24 8EH

1.6 Product compliance Ukraine

Відповідність вимогам України



Технічний регламент радіообладнання, затвердженого Постановою Кабінету Міністрів України від 24 травня 2017 р. №355:

справжнім «Barco NV» заявляє, що тип радіообладнання: Безпроводова система конференц-з'язку (ClickShare) моделі C-100RS, C-300RS відповідає Технічному регламенту радіообладнання.

Повний текст декларації про відповідність доступний на веб-сайті за такою адресою: www.barco.com/en/support

Відповідність виробу (ClickShare) моделі C-100RS, C-300RS іншим Технічним регламентам:

- Технічному регламенту обмеження використання деяких небезпечних речовин в електричному та електронному обладнанні, затвердженого Постановою Кабінету Міністрів України від 10 березня 2017 р. №139;
- Технічного регламенту щодо вимог до екодизайну для споживання електроенергії електричним і електронним побутовим та офісним обладнанням у режимі "очікування", "вимкнено" та мережевому режимі "очікування", затвердженого Постановою Кабінету Міністрів України від 14 серпня 2019 р. №733.

Попереджаємо, що зміни або модифікації, які не будуть схвалені стороною, що забезпечує відповідність вимогам, можуть призвести до позбавлення користувача права на експлуатацію обладнання.

Вимоги щодо радіочастотного опромінення:

- Передавач виробу не можна розміщувати поруч з іншою антеною чи передавачем або експлуатувати разом із такою антеною чи передавачем.
- Виріб слід встановлювати для експлуатації таким чином, щоб відстань між випромінювачем і вашим тілом становила не менше 20 см.
- В пристрої реалізована радіотехнологія 5G NR, з офіційним впровадженням технології в Україні, виробником буде проводитися оцінка відповідності даної радіотехнології вимогам Технічного Регламенту радіообладнання.

Відомості про C-100RS, C-300RS

Модуль Base Unit приймає бездротовий сигнал від пристроїв Button, а також управляє показом вмісту в конференц-залі і периферійними пристроями, підключеними до Base Unit (динаміки, мікрофони, веб-камери і звукова панель). Крім того, він відправляє вміст з камери і спикерфона на пристрій Button.

Радіотехнологія	Смуги радіочастот Radio	Максимальна потужність випромінювання
WLAN 802.11b/g/n	2400 – 2483,5 МГц	20 дБм EIRP
WLAN 802.11a/n/ac	5150 – 5850 МГц	20 дБм EIRP
IEEE 802.15.1 BT LE 4.1	2400 – 2483,5 МГц	20 дБм EIRP

Щоб дізнатися, який регіональний варіант необхідно використовувати у вашій країні, зверніться до місцевого торгового представника. (www.barco.com/en/support)

Регіональну версію C-100RS, C-300RS неможливо змінити. Це означає, що продукт не можна буде використовувати в іншому регіоні.

1.7 Product compliance US

Federal Communication Commission Interference Statement

You are cautioned that changes or modifications not expressly approved by the part responsible for compliance could void the user's authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

You may also find helpful the following booklet, prepared by the FCC: "How to Identify and Resolve Radio-TV Interference Problems.". This booklet is available from the U.S. Government Printing Office, Washington D.C. 20402.

Changes and Modifications not expressly approved by the manufacturer or registrant of this equipment can void your authority to operate this equipment under Federal Communications Commissions rules.

In order to maintain compliance with FCC regulations shielded cables must be used with this equipment. Operation with non-approved equipment or unshielded cables is likely to result in interference to radio & television reception.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC RF Radiation Exposure Statement: This device is capable of operating in 802.11a mode. For 802.11a devices operating in the frequency range of 5.15 - 5.25 GHz, they are restricted for indoor operations to reduce any potential harmful interference for Mobile Satellite Services (MSS) in the US. WIFI Access Points that are capable of allowing your device to operate in 802.11a mode (5.15 - 5.25 GHz band) are optimized for indoor use only. If your WIFI network is capable of operating in this mode, please restrict your WIFI use indoors to not violate federal regulations to protect Mobile Satellite Services.

1. This Transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.
2. This equipment complies with RF radiation exposure limits set forth for an uncontrolled environment.

This equipment should be installed and operated with a minimum distance of 20 cm between the radiator and your body.

Base Unit contains FCC ID: PPQ-WCBN816A

Button FCC ID (model CSBTN004): 2AAED-CSBTN005

ClickShare Button 2AAED-CSBTN005 has been tested and meets the FCC RF exposure guidelines. The maximum SAR value reported is 1.2 W/kg.

ClickShare Button 2AAED-CSBTN005 should be installed and operated with a minimum distance of 5 mm between the radiator and your body.

FCC responsible: Barco Inc., 3059 Premiere Parkway Suite 400, 30097 Duluth GA, United States, Tel: +1 678 475 8000

For country code selection usage (WLAN devices):

Note: The country code selection is for non-US model only and is not available to all US model. Per FCC regulation, all WiFi product marketed in US must fixed to US operation channels only.

California, USA

The button cell battery may contain perchlorate material and requires special handling when recycled or disposed of in California.

For further information please visit: <https://dtsc.ca.gov/perchlorate/>

1.8 Product compliance Canada

Canada, Industry Canada (IC) Notices

This device complies with Industry Canada licence-exempt RSS standard (s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Radio Frequency (RF) Exposure Information

The radiated output power of the Barco Wireless Device is below the Industry Canada (IC) radio frequency exposure limits. The Barco Wireless Device should be used in such a manner such that the potential for human contact during normal operation is minimized.

Caution: Exposure to Radio Frequency Radiation.

1. To comply with the Canadian RF exposure compliance requirements, this device and its antenna must not be co-located or operating in conjunction with any other antenna or transmitter.
2. To comply with RSS 102 RF exposure compliance requirements, a separation distance of at least 20 cm must be maintained between the antenna of this device and all persons.

Base Unit contains FCC ID: 4491A-WCBN816A

Button IC (model CSBTN004): 21559-CSBTN005

ClickShare Button 21559-CSBTN005 has been tested and meets the IC RF exposure guidelines. The maximum SAR value reported is 1.2 W/kg.

ClickShare Button 21559-CSBTN005 should be installed and operated with a minimum distance of 5 mm between the radiator and your body.

IC Antenna statement

Under Industry Canada regulations, this radio transmitter may only operate using an antenna of a type and maximum (or lesser) gain approved for the transmitter by Industry Canada. To reduce potential radio interference to other users, the antenna type and its gain should be so chosen that the equivalent isotropically radiated power (e.i.r.p.) is not more than that necessary for successful communication.

This radio transmitter 4491A-WCBN816A has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain and required antenna impedance for each antenna type indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.

Indoor use only warning

Operation in the band 5150 MHz - 5250 MHz, 5925 MHz - 6425 MHz, 6425 MHz - 6525 MHz, 6525 MHz - 6875 MHz and 6875 MHz - 7125 MHz are only for indoor use to reduce the potential for harmful interference to co-channel mobile satellite systems.

Certification information (SAR)

This device is also designed to meet the requirements for exposure to radio waves established by the Industry Canada.

The SAR limit adopted by Canada is 1.6 W/kg averaged over one gram of tissue. The highest SAR value reported to the IC for this device type complies with this limit.

The highest SAR value reported to the IC for this device type when using in portable exposure conditions is 1.2 W/kg.

Canada, avis d'Industry Canada (IC)

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Informations concernant l'exposition aux fréquences radio (RF)

La puissance de sortie émise par l'appareil de sans fil Barco est inférieure à la limite d'exposition aux fréquences radio d'Industrie Canada (IC). Utilisez l'appareil de sans fil Barco de façon à minimiser les contacts humains lors du fonctionnement normal.

Avertissement: L'exposition aux rayonnements fréquences radio

1. Pour se conformer aux exigences de conformité RF canadienne l'exposition, cet appareil et son antenne ne doivent pas être co-localisés ou fonctionnant en conjonction avec une autre antenne ou transmetteur.
2. Pour se conformer aux exigences de conformité CNR 102 RF exposition, une distance de séparation d'au moins 20 cm doit être maintenue entre l'antenne de cet appareil et toutes les personnes.

Base Unit contient FCC ID: 4491A-WCBN816A

IC Button (modèle CSBTN004): 21559-CSBTN005

ClickShare Button 21559-CSBTN005 a été testé et répond aux directives d'exposition RF de la IC. La valeur SAR maximale rapportée est de 1.2 W/kg.

ClickShare Button 21559-CSBTN005 devrait être installé et utilisé avec une distance minimale de 5 mm entre le radiateur et votre corps.

Déclaration d'antenne d'Industrie Canada (IC)

Conformément à la réglementation d'Industrie Canada, le présent émetteur radio peut fonctionner avec une antenne d'un type et d'un gain maximal (ou inférieur) approuvé pour l'émetteur par Industrie Canada. Dans le but de réduire les risques de brouillage radioélectrique à l'intention des autres utilisateurs, il faut choisir le type d'antenne et son gain de sorte que la puissance isotrope rayonnée équivalente (p.i.r.e.) ne dépasse pas l'intensité nécessaire à l'établissement d'une communication satisfaisante.

Le présent émetteur radio 4491A-WCBN816A a été approuvé par Industrie Canada pour fonctionner avec les types d'antenne énumérés ci-dessous et ayant un gain admissible maximal et l'impédance requise pour chaque type d'antenne. Les types d'antenne non inclus dans cette liste, ou dont le gain est supérieur au gain maximal indiqué, sont strictement interdits pour l'exploitation de l'émetteur.

Utilisation à l'intérieur seulement

La bande 5150 MHz - 5250 MHz, 5925 MHz - 6425 MHz, 6425 MHz - 6525 MHz, 6525 MHz - 6875 MHz and 6875 MHz - 7125 MHz sont réservés uniquement pour une utilisation à l'intérieur afin de réduire les risques de brouillage préjudiciable aux systèmes de satellites mobiles utilisant les mêmes canaux.

Informations de certification (DAS)

Cet appareil est également conçu pour satisfaire aux exigences concernant l'exposition aux ondes radioélectriques établies par Industrie Canada.

Le seuil du DAS adopté par le Canada est de 1.6 W/kg pour 1g de tissu. La plus grande valeur de DAS signalée à IC pour ce type d'appareil ne dépasse pas ce seuil.

La valeur maximale de DAS signalée à IC pour ce type d'appareil lors du test dans des conditions d'exposition portative est de 1.2 W/kg.

1.9 Product compliance Brazil

Visão geral da conformidade ANATEL

Este equipamento não (C-100RS, C-300RS; CSBTN005) tem direito à proteção contra interferência prejudicial e não pode causar interferência em sistemas devidamente autorizados. O uso deste equipamento é restrito a ambientes fechados e é proibido em plataformas petrolíferas,

veículos automotores, trens, embarcações e no interior de aeronaves abaixo de 3.048 metros (10.000 pés).

Este equipamento não possui direito à proteção contra interferência prejudicial e não pode causar interferência em sistemas devidamente autorizados. Para mais informações, consulte o site da ANATEL: www.gov.br/anatel

1.10 Product compliance Mexico

Cumplimiento

La operación de este equipo está sujeta a las siguientes dos condiciones: (1) es posible que este equipo o dispositivo no cause interferencia perjudicial y (2) este equipo o dispositivo debe aceptar cualquier interferencia, incluyendo la que pueda causar su operación no deseada.

NOM certification



IFETEL ID: RCPBACxxx-xxxx

1.11 Product compliance Taiwan

NCC warning statement

根據 NCC LP0002(低功率射頻器材技術規範_章節3.8.2:

取得審驗證明之低功率射頻器材，非經核准，公司、商號或使用者均不得擅自變更頻率、加大功率或變更原設計之特性及功能。

低功率射頻器材之使用不得影響飛航安全及干擾合法通信；經發現有干擾現象時，應立即停用，並改善至無干擾時方得繼續使用。

前述合法通信，指依電信管理法規定作業之無線電通信。

低功率射頻器材須忍受合法通信或工業、科學及醫療用電波輻射性電機設備之干擾。

Taiwan



For better environmental protection, waste batteries should be collected separately for recycling or special disposal.

廢電池請回收

1.12 Product compliance India

Plastic waste management

- **Importer EPR Regn. No.:** IM-05-000-12-ADPPA7994P-23 (under India PWM, 2016 as amended)
- **Thickness:** ≥ 0.05 mm
- **Category:** 04
- **Company:** CEECO Technologies Pvt Ltd, Inflow Technologies Pvt Ltd

1.13 Trademark notice

USB Type-C™

USB Type-C and USB-C are a registered trademarks of USB Implementers Forum

Bluetooth®

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Barco is under license



All other trademarks and registered trademarks are trademarks or registered trademarks of their respective holders. In this manual, ™ and ® marks are not specified.



R5918651 /02 | 2026-01-16

www.barco.com